

TEREX-DEMAG AC650  
W H 仕様(ラフイングジブ)  
定格総荷重表

仕様	アウトリガ 長さ×幅 (m)	カウンタウエイト (t)	DZ番号
WIHI	12.2 × 12.0	160	DZ-0072-1
		140	DZ-0072-2
		120	DZ-0072-3
		100	DZ-0072-4
		80	DZ-0072-5
		60	DZ-0072-6
	10.44 × 10.03	120	DZ-0072-7
		100	DZ-0072-8
		80	DZ-0072-9
		60	DZ-0072-10
	9.02 × 8.45	100	DZ-0072-11
		80	DZ-0072-12
		60	DZ-0072-13



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 160t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 20.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	24.0			27.0			30.0			33.0			36.0			39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
12.0	116.0/13m			109.0/13m			100.0/13m			89.9/13m								
14.0	114.0			107.0			98.5			89.2			78.5					71.0/15m
16.0	110.0			104.0			96.0			87.9			77.5					70.9
18.0	104.0			100.0			94.0			86.5			77.0					70.6
20.0	98.5	92.5		96.5			92.0			84.8			77.0					70.3
22.0	92.5	87.0		91.7	82.7		89.5	80.0		83.0	73.3/23m		76.5					69.7
24.0	87.0	82.0		84.0	80.7		86.5	76.5		81.2	72.1		76.0	66.5				68.9
26.0		77.5	72.5	76.3	76.1		81.5	73.0		78.0	69.7		74.5	65.0				68.0
28.0		73.5	69.0	68.3	71.9	68.9	75.5	70.0	66.0	71.0	67.3		72.0	63.5				67.2
30.0			65.5	66.7	64.0		64.0	66.5	62.5	64.0	64.7	60.8	68.5	61.5				65.2
32.0			61.0	62.2	59.6		63.0	60.0	56.9	61.1	58.5	62.0	59.5	56.0	59.9	57.1	52.5/33m	57.1
34.0					55.7		59.0	56.5	47.9	57.1	54.6	53.5	57.5	54.0	54.5	55.5	51.8	51.8
36.0					52.4			53.0		53.6	51.2	45.0	54.5	52.5	49.2	53.1	50.3	50.3
38.0								50.0		50.5	48.2		51.5	49.5	43.8	49.9	47.7	47.7
40.0											45.5		48.5	46.5	38.1	47.1	45.0	45.0
42.0											44.3/41m			44.0		44.6	42.5	42.5
44.0														42.0		42.3	40.3	40.3
46.0																	38.3	38.3
48.0																		37.4/47m
(°)	29~67	30~59	25~50	22~69	23~58	16~50	26~71	26~61	22~55	20~73	20~62	21~54	23~73	24~63	20~53	18~73	19~62	19~55
索数	9	8	6	9	7	6	8	7	5	7	6	5	6	5	6	5	4	4
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02
DSコード	30030	30030	30030	30043	30043	30043	30031	30031	30031	30044	30044	30044	30032	30032	30032	30045	30045	30045

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	42.0			45.0			48.0			51.0			54.0			60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	63.5			57.8			52.0/17m											
18.0	63.5			57.8			52.0			48.1			44.0/19m					
20.0	63.0			57.7			52.0			48.1			44.0					37.0
22.0	63.0			57.6			52.0			48.1			44.0					37.0
24.0	62.5			57.5			52.0			48.1			44.0					37.0
26.0	62.0	57.5/27m		57.0			51.5			48.1			44.0					37.0
28.0	61.5	57.0		56.5	54.0		51.0			47.5			44.0					37.0
30.0	61.0	56.0		56.0	52.9		51.0	50.0		46.8	46.5/31m		44.0					37.0
32.0	58.0	54.5		55.2	51.7		50.5	49.0		46.1	46.1		43.5	43.0				37.0
34.0	55.5	53.5	48.5/35m	54.3	50.6		50.0	48.0		45.4	45.2		43.0	42.5				37.0
36.0	51.0	51.5	48.0	50.6	49.4	45/37m	48.0	47.0		44.5	44.3		42.5	41.5				35.0/35m
38.0	46.5	50.0	46.5	46.9	48.2	44.5	46.0	46.0	41.5/39m	43.6	43.4		41.5	41.0				37.0
40.0	41.5	48.0	45.0	43.3	46.2	43.4	43.0	45.0	41.0	41.2	42.4	40.0	40.0	40.0				37.0
42.0	35.5	45.5	43.5	39.6	43.6	41.5	40.0	43.5	40.5	38.8	41.4	39.1	39.0	39.0	38.0	37.0	34.5	34.5
44.0		43.0	41.5	35.9	41.3	39.3	37.0	42.0	39.5	36.4	39.9	38.3	37.0	38.0	37.0	36.0	34.5	31.5/45m
46.0		41.0	39.0	34.1/45m	39.2	37.3	33.0	40.0	38.5	34.0	38.3	36.3	35.0	37.0	36.0	35.0	34.0	31.5
48.0			37.0		37.3	35.4	28.5	38.0	36.5	31.6	36.3	34.4	33.0	36.0	35.5	33.0	33.0	31.0
50.0			35.0		36.5/49m	33.7		36.0	34.5	28.4	34.6	32.7	30.0	35.0	34.0	31.5	32.5	30.5
54.0						31.6/53m			31.0		31.5	29.8	22.8	32.0	30.5	27.5	31.0	29.3
58.0												27.3		27.4	27.9	21.8	29.2	27.9
62.0															26.1/61m		25.9	25.4
66.0																		23.4
(°)	22~73	22~62	18~54	21~74	21~63	18~54	20~74	27~62	24~54	23~73	23~63	20~55	19~73	19~63	20~54	23~74	24~63	22~55
索数	5	5	4	5	5	4	4	4	4	4	4	3	4	4	3	3	3	3
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02
DSコード	30033	30033	30033	30046	30046	30046	30034	30034	30034	30047	30047	30047	30035	30035	30035	30036	30036	30036

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	66.0			72.0			78.0			84.0			90.0			96.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
22.0	30.0																	
24.0	30.0			25.9														
26.0	29.9			25.8			21.7			17.6/27m								
28.0	29.7			25.7			21.5			17.5			14.0/29m					
30.0	29.5			25.7			21.3			17.4			13.8					11.1/31m
32.0	29.2			25.6			21.2			17.2			13.6					10.9
34.0	29.0			25.6			21.0			17.0			13.3					10.6
36.0	28.7			25.6			20.8			16.8			13.1					10.4
38.0	28.5	29.6		25.6			20.6			16.6			12.8					10.1
40.0	28.2	29.3		25.5	25.2		20.3			16.3			12.6					9.8
42.0	28.0	29.0		25.4	25.2		20.1			16.0			12.3					9.6
44.0	27.7	28.7		25.3	25.2		19.9	20.3		15.7			12.1					9.3
46.0	27.4	28.4		25.2	25.2		19.6	20.1		15.4	16.0		11.9					9.1
48.0	26.8	28.1	27.4/49m	24.9	25.2		19.3	19.8		15.1	15.7		11.6	12.0/49m				8.9
50.0	26.2	27.8		24.7	25.2	24.2/52m	19.1	19.6		14.8	15.4		11.4	11.9				8.7
54.0	24.4	27.0	25.9	24.0	25.2	24.0	18.5	19.1	19.1/56m	14.2	14.7		11.0	11.4				8.3
58.0	22.6	25.9	24.7	23.0	24.6	23.6	17.9	18.5	18.8	13.6	14.1	14.6/59m	10.5	11.0				7.9
62.0	19.6	24.8	23.9	21.2	23.6	23.0	17.2	18.0	18.2	12.9	13.6	14.1	10.1	10.6	11.1/63m			7.6
66.0	15.9/65m	23.2	22.6	17.4	22.6	22.0	16.6	17.5	17.6	12.4	13.0	13.5	9.8	10.2	10.8	7.3	7.6	8.1
70.0		18.5	20.8	13.6	20.7	20.2	15.7	16.9	17.1	11.9	12.5	13.0	9.4	9.8	10.3	7.0	7.3	7.6
74.0			19.7/73m		17.0	18.6	12.6	16.4	16.6	11.5	12.1	12.5	9.1	9.4	9.8	6.7	7.0	7.1
78.0					17.3	10.1/77m	15.7	16.1	11.1	11.7	12.0	8.8	9.1	9.4	6.4	6.7	6.7	6.7
82.0							13.2/81m	15.6	8.8	11.3	11.6	8.5	8.8	9.1	6.1	6.4	6.3	6.3
86.0								15.4/84m		11.0	11.3	7.9	8.5	8.7	5.8	6.1	6.0	6.0
90.0											11.0	6.8/88m	8.3	8.5	5.6	5.8	5.8	5.8
94.0													8.1/92m	8.2	5.0	5.5	5.5	5.5
98.0														8.1/96m		5.3	5.4	5.4
102.0																		5.3/101m
(°)	20~74	17~63	18~54	21~73	22~63	20~55	18~73	18~63	19~54	20~74	27~62	24~54	19~74	19~63	17~54	18~73	19~63	19~55
索数																		



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 160t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 30.5m+4.0m

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	24.0			27.0			30.0			33.0			36.0			39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
14.0	96.5/15m			88.4/15m			80.5/15m			70.5/15m								
16.0	93.0			87.0			80.5			70.2			62.0					55.5/17m
18.0	87.0			83.5			78.5			69.6			62.0					55.5
20.0	81.5			79.3			76.0			69.1			62.0					55.5
22.0	77.0			74.9			72.5			67.1			61.5					55.5
24.0	73.5	62.0		70.6			68.5	58.0		64.8			60.5					55.1
26.0	71.0	58.0		66.9	57.4		65.0	56.5		62.5	52.4/27m		59.0					54.2
28.0		55.0		64.2	54.5		62.0	53.5		60.2	51.0		57.5	49.0				53.4
30.0		52.5	46.5/31m	63.0	51.9		59.5	51.5		57.9	48.6		55.5	46.5				52.5
32.0		51.0	45.0		50.1	43.6/33m	59.0	49.5	43/33m	55.6	46.7		53.5	44.0				50.9
34.0			43.0		48.2	42.5		47.5	42.0	53.3	44.8	39.4/35m	51.0	42.0				49.3
36.0			41.5		47.0	40.8		46.0	40.0	44.4	43.5		48.5	41.0	36.0/37m			47.0
38.0						39.1		44.5	38.5		42.3	36.6	42.0	39.5	35.0	44.8		38.7
40.0						38.0			37.0		41.8	35.3		39.0	33.5	42.5		38.1
42.0									36.0		41.3	34.0		39.0	32.0	35.7		37.5
44.0												33.3		39.0	31.5			36.9
46.0												32.7			30.5			36.3
48.0															30.0			35.7
50.0																		28.2
(°)	25~64	24~56	26~47	16~68	15~55	18~47	22~70	21~61	23~53	15~72	13~60	16~52	20~72	19~61	21~53	13~72	12~60	24~52
索数	8	5	4	7	5	4	7	5	4	6	4	3	5	4	3	5	4	3
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	30030	30030	30030	30043	30043	30043	30031	30031	30031	30044	30044	30044	30032	30032	30032	30045	30045	30045

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	42.0			45.0			48.0			51.0			54.0			60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	50.0			44.6			40.0/19m			36.9			33.5/21m					
20.0	50.0			44.6			40.0			36.9			33.5			30.0		
22.0	50.0			44.6			40.0			36.9			33.5			30.0		
24.0	50.0			44.6			40.0			36.9			33.5			30.0		
26.0	49.5			44.6			40.0			36.9			33.5			30.0		
28.0	49.0			44.4			40.0			36.9			33.5			30.0		
30.0	49.0	43.5/31m		44.3			40.0			36.9			33.5			30.0		
32.0	48.5	42.5		44.1	41.4		40.0			36.9			33.5			30.0		
34.0	48.0	40.5		43.9	39.6		40.0	38.5		36.9	36.2/35m		33.5			30.0		
36.0	46.0	39.0		42.9	38.0		40.0	37.0		36.9	35.7		33.5	33.5		30.0		
38.0	44.0	37.5		42.0	36.4		40.0	35.5		36.9	34.6		33.5	32.5		30.0	28.1/39m	
40.0	42.0	36.0	32.5	40.3	35.2		38.5	34.0		36.2	33.5		33.5	31.5		30.0	27.9	
42.0	40.0	35.0	30.5	38.7	34.0	30.3	37.0	33.0		35.5	32.5		33.5	31.0		30.0	27.7	
44.0	33.5	34.5	29.7	37.1	33.2	29.0	35.5	32.0	28.5	34.3	31.6	27.5/45m	32.5	30.0		29.9	27.3	
46.0		33.5	28.5	35.4	32.3	27.6	34.5	31.0	27.2	33.1	30.6	27.0	31.5	29.7	26.2/47m	29.9	27.0	
48.0		33.0	27.7	32.9/47m	31.9	26.7	32.0	30.5	26.1	31.9	30.2	26.0	30.5	29.1	25.6	29.1	26.7	
50.0		33.0	26.9		31.4	25.8	26.9	30.0	25.1	30.8	29.8	25.0	29.5	28.5	24.6	28.4	26.3	22.8
54.0			26.4		31.1/53m	24.7		29.6	23.7	24.9/53m	29.0	23.3	25.5	27.5	22.8	26.9	25.5	21.7
58.0					24.4			22.9		26.9	22.5		26.7	21.5	23.9	24.6	20.7	
62.0											21.8		25.3	20.6	19.2/61m	23.7	19.7	
66.0															20.1	22.6	18.9	
70.0																	18.1	
(°)	18~72	17~61	19~53	18~73	17~61	14~53	17~73	24~61	25~53	16~73	20~61	21~54	23~73	15~62	17~53	19~73	21~62	22~54
索数	4	4	3	4	4	3	3	3	3	3	3	3	3	3	2	3	3	2
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	30033	30033	30033	30046	30046	30046	30034	30034	30034	30047	30047	30047	30035	30035	30035	30036	30036	30036

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	66.0			72.0*			78.0*			84.0*			90.0#			96.0#		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
24.0	23.3																	
26.0	23.3			20.2			17.6/27m											
28.0	23.3			20.2			17.6			14.2/29m								
30.0	23.3			20.2			17.6						11.6/31m					
32.0	23.3			20.2			17.6			14.2			11.6			9.0/33m		
34.0	23.3			20.2			17.6			14.2			11.4			8.9		
36.0	23.3			20.2			17.6			14.1			11.3			8.8		
38.0	23.2			20.2			17.6			14.1			11.2			8.6		
40.0	23.2			20.2			17.5			14.1			11.1			8.5		
42.0	23.2	25.7		20.2			17.5			14.0			10.9			8.3		
44.0	23.1	25.2		20.2	19.7		17.4			13.9			10.8			8.2		
46.0	23.1	24.8		20.2	19.7		17.3	17.2/47m		13.8			10.7			8.0		
48.0	23.0	24.3		20.2	19.6		17.2	17.2		13.7			10.5			7.9		
50.0	23.0	23.9		20.2	19.6		17.1	17.1		13.6	13.7		10.4	10.6/53m		7.7		
54.0	22.3	23.0	21.1	20.1	19.5		16.8	16.9		13.3	13.4		10.1	10.6		7.4	7.8/55m	
58.0	21.6	22.2	19.7	19.6	19.4	18.2	16.6	16.7	15.7/61m	13.0	13.1		9.8	10.3		7.1	7.6	
62.0	20.9	21.5	18.3	19.0	19.2	17.3	16.3	16.4	15.6	12.7	12.9	12.3/65m	9.5	10.0		6.8	7.2	
66.0	16.5	20.9	17.4	18.4	18.8	16.4	16.0	16.1	14.9	12.4	12.6	12.1	9.3	9.7	9.7/68m	6.5	6.9	
70.0		20.2	16.9	14.9	18.4	15.7	15.7	15.8	14.2	12.1	12.4	11.6	9.0	9.4	9.5	6.2	6.6	7.0/72m
74.0		18.4/73m	16.4	11.8/73m	18.0	15.2	13.6	15.4	13.7	11.8	12.2	11.0	8.7	9.1	9.1	5.9	6.3	
78.0			15.9		16.0	14.7	10.4	15.0	13.2	11.4	12.0	10.5	8.4	8.9	8.7	5.6	6.0	6.5
82.0					14.1			14.5	12.8	11.8	12.0	10.5	8.1	8.6	8.3	5.4	5.8	6.2
86.0								12.2/85m	12.4	8.2/84m	11.6	9.6	7.9	8.3	8.0	5.1	5.5	5.9
90.0									12.2/89m		10.9	9.2	6.3	8.0	7.6	5.0	5.3	5.6
94.0												8.9		7.8	7.3	4.8	5.1	5.3
96.0														7.6	7.1	4.5	5.0	5.2
98.0															6.9		4.9	5.1
102.0																6.7/101m	4.8	4.8
106.0																	4.6	
(°)	20~73	17~61	15~54	17~73	19~62	20~53	19~73	16~62	17~54	18~73	18~62	19~53	17~73	17~62	16~54	17~73	16~62	17~53
索数	2	2	2	2	2													

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 160t  
アウドリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 35.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	24.0			27.0			30.0			33.0			36.0			39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	81.5			73.2/17m			67.5			60.2			54.5/17m					
18.0	77.0			72.1			66.5			59.9			54.5					49.3
20.0	72.5			69.2			65.0			59.5			54.5					49.3
22.0	68.0			66.0			62.5			58.8			54.5					49.3
24.0	64.5			62.7			60.0			56.8			53.5					49.3
26.0	62.0	50.5		59.7			57.5	46.5/27m		55.1			52.5					48.7
28.0		48.0		57.4	46.6		55.5	45.5		53.7	43.4/29m		51.0					48.0
30.0		45.5		56.0	44.3		54.0	43.0		52.5	42.2		50.0	41.5				47.4
32.0		44.0		42.5			53.5	41.0		51.6	40.3		49.5	39.5				46.7
34.0			36.5	40.8			39.5			50.8	38.3		48.5	37.5				46.1
36.0			35.0	39.6	33.8		38.0	32.5		49.4	37.0		48.0	36.0				45.4
38.0			33.0	38.5	32.4		37.0	31.5		35.7	30.9		45.5	34.5	30.0/39m			44.8
40.0					31.3			30.0		35.1	29.7		33.5	29.3	44.1			33.4
42.0					30.2			29.3		34.5	28.4		33.0	27.9	39.6			32.5
44.0								28.6		34.3	27.5		33.0	26.9				31.9
46.0											26.7			25.9				31.4
48.0											26.3			25.3				30.8
50.0														24.8				30.3
52.0																		23.2
54.0																		22.9
(°)	28~63	32~54	27~44	21~64	8~53	19~45	25~69	28~60	24~50	19~71	7~59	17~50	23~71	26~60	22~52	17~71	6~59	16~52
索数	7	4	3	6	4	3	6	4	3	5	4	3	5	4	3	4	3	3
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	30030	30030	30030	30043	30043	30043	30031	30031	30031	30044	30044	30044	30032	30032	30032	30045	30045	30045

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	42.0			45.0			48.0			51.0			54.0			60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	45/19m			39.8/19m														
20.0	45.0			39.8			35.5			32.8/21m								
22.0	45.0			39.8			35.5			32.8			30.0					27.0/23m
24.0	45.0			39.8			35.5			32.8			30.0					27.0
26.0	45.0			39.8			35.5			32.8			30.0					27.0
28.0	44.5			39.8			35.5			32.8			30.0					27.0
30.0	44.5			39.7			35.5			32.8			30.0					27.0
32.0	44.0	37.5/33m		39.6			35.5			32.8			30.0					27.0
34.0	43.5	36.5		39.5	35.7		35.5			32.8			30.0					27.0
36.0	43.0	35.0		39.2	34.2		35.5	33.0		32.8	31.7/37m		30.0					27.0
38.0	42.5	33.5		38.9	32.7		35.5	32.0		32.8	31.2		30.0	30.0				27.0
40.0	41.5	32.0		38.5	31.5		35.0	30.5		32.7	30.2		30.0	28.9				24.9/41m
42.0	41.0	31.0	26.2/43m	38.1	30.3		35.0	29.7		32.6	29.2		30.0	27.9				27.0
44.0	35.5	30.0	25.6	37.6	29.4	24.4/45m	34.5	28.8		32.3	28.2		29.9	27.1				27.0
46.0		29.5	24.4	37.1	28.6	23.8	34.0	27.8	23.5	32.1	27.2		29.8	26.2				27.0
48.0		28.9	23.5	32.6	27.9	22.8	33.5	27.2	22.4	31.8	26.6	22.0	29.6	25.5				26.9
50.0		28.4	22.6		27.3	21.8	28.6	26.5	21.4	31.6	26.0	21.1	29.5	24.8	20.5			26.7
54.0			21.7		26.7	20.5		25.8	19.8	24.7	25.3	19.4	26.6	23.7	18.8			26.4
58.0						19.9			18.9	24.6	24.6	18.4	23.0	17.5	15.9			26.7
62.0									18.5			17.8	22.5	16.5	15.9			26.4
66.0												17.2						26.4
70.0																		26.4
74.0																		26.4
(°)	21~71	23~60	27~52	16~72	19~61	23~51	19~72	28~60	18~53	15~72	24~61	13~52	24~72	21~61	24~52	17~73	25~61	16~53
索数	4	3	2	3	3	2	3	3	2	3	3	2	3	3	2	2	2	2
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	30033	30033	30033	30046	30046	30046	30034	30034	30034	30047	30047	30047	30035	30035	30035	30036	30036	30036

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	66.0			72.0 *			78.0 *			84.0 #			90.0 #			96.0 #		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
24.0	21.0/25m																	
26.0	21.0			18.5/27m														
28.0	21.0			18.5			16.0											
30.0	21.0			18.5			16.0			13.0								
32.0	21.0			18.5			16.0			13.0			11.0					
34.0	21.0			18.5			16.0			13.0			10.9					8.5
36.0	21.0			18.5			16.0			13.0			10.9					8.4
38.0	21.0			18.5			16.0			13.0			10.8					8.3
40.0	21.0			18.5			16.0			13.0			10.8					8.1
42.0	21.0			18.5			16.0			13.0			10.7					8.0
44.0	21.0	24.6		18.5			16.0			13.0			10.6					7.9
46.0	21.0	23.7		18.5	18.0		16.0			13.0			10.5					7.8
48.0	21.0	22.9		18.5	18.0		16.0			13.0			10.5					7.6
50.0	21.0	22.1		18.5	17.9		16.0	15.3/49m		13.0			10.4					7.5
54.0	21.0	20.7	17.3/57m	18.5	17.8		16.0	15.3		13.0	12.5		10.2	10.5/55m				7.2
58.0	21.0	19.6	16.9	18.5	17.6	15.3/61m	16.0	15.3		13.0	12.5		10.0	10.3				6.9
62.0	21.0	18.6	15.4	18.5	17.3	14.9	16.0	15.3	13.4/64m	13.0	12.5		9.8	10.1				6.6
66.0	17.2	17.9	14.2	18.5	17.0	13.7	15.9	15.3	12.9	12.8	12.5	10.9/68m	9.6	9.9				6.3
70.0		17.4	13.3	15.4	16.6	12.6	15.9	15.0	12.1	12.5	12.5	10.5	9.3	9.7	9.5/71m			6.1
74.0		17.1	12.8	11.3	16.1	11.8	14.0	14.7	11.3	12.1	12.3	9.9	9.1	9.5	9.2			5.8
78.0			12.5															

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフイングジブ)

カウンタウエイト 160t  
アウトリガ 12.2 × 12.0m

主ジブ長さ+アダプタ長さ 40.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	60.4/17m			48.8/17m											
18.0	60.3			48.8			38.9/19m								
20.0	60.1			48.8			38.9			32.1					
22.0	56.9			48.8			38.9			32.1				27.2	
24.0	54.2			47.7			38.9			32.1				27.2	
26.0	51.9			46.1			38.8			32.1				27.2	
28.0	50.1			44.7			38.4			32.1				27.2	
30.0	48.8	38.8		43.6	35.5/31m		38.0			32.1				27.2	
32.0		36.9		42.8	34.6		37.7			32.0				27.2	
34.0		35.0		42.1	32.7		37.3	30.7		32.0				27.1	
36.0		33.9		41.8	31.3		36.9	29.5		31.8	27.3/37m			27.1	
38.0		32.7	27/39m		29.9		36.5	28.2		31.7	26.7			27.1	24.9/39m
40.0			26.4		29.1	24.9	36.1	27.0		31.4	25.6			27.1	24.5
42.0			25.1		28.3	23.7	35.7	25.9		31.2	24.5			27.0	23.6
44.0			24.3		28.1	22.7		25.5	21.1	30.9	23.6			26.9	22.7
46.0						21.8		25.1	20.1	30.6	22.7			26.7	21.9
48.0						21.2		24.7	19.4	30.3	22.1	18.4		26.5	21.1
50.0						20.6		24.3	18.6	30.3	21.5	17.5		26.3	20.3
52.0									18.2	30.3	21.2	16.9		26.2	20.0
54.0									17.7	30.3	20.9	16.2		26.0	19.7
56.0												15.7		26.0	19.3
58.0												15.3		26.0	19.0
60.0												15.1		26.0	18.7
62.0												14.9		26.0	18.4
64.0														26.0	18.4
66.0														26.0	18.4
(°)	24~66	22~52	20~42	22~70	19~58	18~50	20~70	18~58	25~50	19~72	24~58	15~50	17~72	15~60	22~51
索数	5	3	2	4	3	2	3	3	2	3	3	2	3	2	2
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	30043	30043	30043	30044	30044	30044	30045	30045	30045	30046	30046	30046	30047	30047	30047

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフイングジブ)

カウンタウエイト 160t  
アウトリガ 12.2 × 12.0m

主ジブ長さ+アダプタ長さ 45.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	48.4/19m			40.1											
20.0	48.3			40.1			32.7								
22.0	47.2			40.1			32.7			27.8			24.5/23m		
24.0	45.1			39.9			32.7			27.8			24.5		
26.0	43.3			38.9			32.7			27.8			24.5		
28.0	41.9			38.0			32.6			27.8			24.5		
30.0	40.8			37.2			32.4			27.8			24.5		
32.0	40.1	31.3		36.6	28.8/33m		32.3			27.8			24.5		
34.0		29.7		36.1	28.1		32.1			27.7			24.4		
36.0		28.5		35.7	26.8		32.0	25.5		27.7			24.4		
38.0		27.3		35.4	25.5		31.8	24.5		27.6	22.6/39m		24.3		
40.0		26.6	21.2/41m		24.6		31.6	23.4		27.5	22.1		24.3	20.8/41m	
42.0			20.7		23.7	19.2/43m	31.5	22.3		27.4	21.0		24.2	20.4	
44.0			19.9		23.3	18.8	31.3	21.7		27.2	20.1		24.1	19.6	
46.0			19.1		22.8	18.0		21.0	16.6/47m	27.1	19.2		24.0	18.8	
48.0						17.4		20.7	16.3	26.9	18.5		23.8	18.0	
50.0						16.7		20.3	15.6	26.7	17.8	14.7	23.7	17.2	
52.0									15.1	17.4	14.1		23.6	16.6	
54.0									14.5	17.0	13.4	23.4	16.1	12.9	
56.0									14.2	16.7	12.9		15.8	12.4	
58.0									13.9	16.5	12.4		15.5	11.8	
60.0											12.1		15.2	11.3	
62.0											11.7		14.9	10.9	
64.0														10.6	
66.0														10.3	
68.0														10.1	
70.0														9.8	
(°)	15~62	18~50	21~42	13~70	16~57	28~48	12~70	24~57	17~48	11~70	14~57	24~50	20~71	21~59	15~50
架数	4	3	2	3	3	2	3	2	2	3	2	2	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	30043	30043	30043	30044	30044	30044	30045	30045	30045	30046	30046	30046	30047	30047	30047



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフイングジブ)

カウンタウエイト 160t  
アウトリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 50.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0				29.9/19m											
20.0	35.0			29.7			24.1/21m								
22.0	34.2			29.2			24.1			21.1/23m					
24.0	33.9			28.7			24.1			21.1			18.6		
26.0	33.6			28.6			24.1			21.1			18.6		
28.0	33.3			28.5			24.1			21.1			18.6		
30.0	32.7			28.4			24.1			21.1			18.6		
32.0	32.2			28.2			24.0			21.0			18.6		
34.0		25.0		28.0	22.9/35m		23.9			20.9			18.6		
36.0		23.8		27.8	22.0		23.8			20.8			18.5		
38.0		22.7		27.5	20.9		23.8	19.2		20.7			18.4		
40.0		22.0			20.1		23.7	18.3		20.6	16.9/41m		18.3		
42.0		21.2			19.2		23.6	17.4		20.5	16.4		18.2		
44.0			17.3		18.7		23.5	16.8		20.4	15.7		18.1	14.9	
46.0			16.5		18.1	15.0		16.1		20.3	14.9		18.0	14.3	
48.0			15.8		17.8	14.3		15.7		20.1	14.4		17.9	13.7	
50.0					13.6			15.2	12.4	20.0	13.8		17.8	13.1	
52.0					13.1			15.0	11.9	13.3	10.7/53m	17.7	17.7	12.5	
54.0					12.7			14.8	11.3	12.9	10.4	17.6	17.6	11.9	
56.0									11.0	12.6	10.0		11.7	9.1/57m	
58.0									10.6	12.4	9.5		11.5	8.9	
60.0											9.2		11.3	8.5	
62.0											8.8		11.0	8.1	
64.0											8.6		10.8	7.8	
66.0											8.4		10.6	7.5	
68.0														7.3	
70.0															7.1
(°)	20~61	13~49	21~39	18~69	12~55	19~46	16~69	11~56	26~47	15~69	20~57	16~49	22~71	9~57	22~49
架数	3	2	2	3	2	2	2	2	2	2	2	2	2	2	2
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73
DSコード	30043	30043	30043	30044	30044	30044	30045	30045	30045	30046	30046	30046	30047	30047	30047

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフイングジブ)

カウンタウエイト 160t  
アウトリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
20.0	28.0/21m			22.5											
22.0	26.0			22.6			18.1								
24.0	27.8			22.6			18.1			16.6			14.7/25m		
26.0	27.2			22.5			18.1			16.6			14.7		
28.0	26.6			22.3			18.1			16.6			14.7		
30.0	26.1			22.1			18.1			16.6			14.7		
32.0	25.6			21.9			18.1			16.4			14.7		
34.0				21.7			18.1			16.3			14.7		
36.0		19.2		21.6	17.1/37m		18.1			16.1			14.6		
38.0		18.2		21.4	16.7		18.1			16.0			14.5		
40.0		17.6			16.0		18.1	14.9		15.8			14.3		
42.0		16.9			15.4		18.1	14.2		15.7	12.8/43m		14.2		
44.0					14.9		18.1	13.6		15.6	12.5		14.1		
46.0			12.9/47m		14.4			13.1		15.5	11.9		13.9	11.1	
48.0			12.7		14.0	11.3/49m		12.7		15.4	11.4		13.8	10.6	
50.0			12.2			11.1		12.2		15.4	10.9		13.7	10.2	
52.0						10.6		12.0	9.4/53m		10.5		13.7	9.7	
54.0						10.2		11.7	9.2		10.1		13.6	9.3	
56.0									8.8		9.8	7.8		8.9	
58.0									8.5		9.6	7.4		8.6	
60.0									8.2			7.1		8.4	6.3
62.0									7.9			6.7		8.2	6.0
64.0												6.5		8.1	5.7
66.0												6.2		7.9	5.4
68.0															5.2
70.0															5.0
74.0															4.7
(°)	24~60	24~47	22~36	21~68	22~54	29~44	19~69	20~55	18~45	18~69	25~56	24~47	24~70	17~56	16~47
架数	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83
DSコード	30043	30043	30043	30044	30044	30044	30045	30045	30045	30046	30046	30046	30047	30047	30047







TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 140t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 30.5m+4.0m

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)						
	24.0			27.0			30.0			33.0			36.0			39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
14.0	96.5/15m			88.4/15m			80.5/15m			70.5/15m									
16.0	93.0			87.0			80.5			70.2			62.0					55.5/17m	
18.0	87.0			83.5			78.5			69.6			62.0					55.5	
20.0	81.5			79.3			76.0			69.1			62.0					55.5	
22.0	77.0			74.9			72.5			67.1			61.5					55.5	
24.0	73.5	62.0		70.6			68.5	58.0/25m		64.8			60.5					55.1	
26.0	71.0	58.0		66.9	57.4		65.0	56.5		62.5	52.4/27m		59.0					54.2	
28.0		55.0		64.2	54.5		62.0	53.5		60.2	51.0		57.5	49.0				53.4	
30.0		52.5	46.5/31m	63.0	51.9		59.5	51.5		57.9	48.6		55.5	46.5				52.5	45.7
32.0		51.0	45.0		50.1	43.6/33m	59.0	49.5	43.0/33m	55.6	46.7		53.5	44.0				50.9	43.9
34.0			43.0		48.2	42.5		47.5	42.0	53.3	44.8		51.0	42.0				49.3	42.1
36.0			41.5		47.0	40.8		46.0	40.0	44.4	43.5	39.4/35m	48.5	41.0			36.0/37m	47.0	40.4
38.0						39.1		44.0	38.5		42.3	36.6	42.0	39.5	35.0			44.8	38.7
40.0						38.0			37.0		40.8	35.3		39.0	33.5			42.5	38.1
42.0									36.0		38.3	34.0		38.5	32.0			35.7	37.5
44.0												33.1		36.0	31.5				35.6
46.0												31.3			30.5				33.5
48.0															29.9				31.7
50.0																			27.5
(°)	64~25	56~24	47~26	16~68	15~55	18~47	70~22	61~21	53~23	15~72	13~60	16~52	72~20	61~19	52~21	13~72	12~60	24~52	
索数	8	5	4	7	5	4	7	5	4	6	4	3	5	4	3	5	4	3	
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	31030	31030	31030	31043	31043	31043	31031	31031	31031	31044	31044	31044	31032	31032	31032	31045	31045	31045	31045

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)						
	42.0			45.0			48.0			51.0			54.0			60.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
18.0	50.0			44.6			40.0/19m												
20.0	50.0			44.6			40.0			36.9			33.5/21m						
22.0	50.0			44.6			40.0			36.9			33.5					30.0	
24.0	50.0			44.6			40.0			36.9			33.5					30.0	
26.0	49.5			44.6			40.0			36.9			33.5					30.0	
28.0	49.0			44.4			40.0			36.9			33.5					30.0	
30.0	49.0	43.5/31m		44.3			40.0			36.9			33.5					30.0	
32.0	48.5	42.5		44.1	41.4		40.0			36.9			33.5					30.0	
34.0	48.0	40.5		43.9	39.6		40.0	38.5		36.9	36.2/35m		33.5					30.0	
36.0	46.0	39.0		42.9	38.0		40.0	37.0		36.9	35.7		33.5	33.5				30.0	
38.0	44.0	37.5		42.0	36.4		40.0	35.5		36.9	34.6		33.5	32.5				30.0	28.1
40.0	42.0	36.0	32.5	40.3	35.2		38.5	34.0		36.2	33.5		33.5	31.5				30.0	27.9
42.0	40.0	35.0	30.5	38.7	34.0	30.3	37.0	33.0		35.5	32.5		33.5	31.0				30.0	27.7
44.0	33.5	34.5	29.7	37.1	33.2	29.0	35.5	32.0	28.5	34.3	31.6	27.5/45m	32.5	30.0				29.9	27.3
46.0		33.5	28.5	35.4	32.3	27.6	34.5	31.0	27.2	33.1	30.6	27.0	31.5	29.7			26.2/47m	29.9	27.0
48.0		31.5	27.7	32.9/47m	30.9	26.7	32.0	30.5	26.1	31.9	30.1	26.0	30.5	29.1			25.6	29.1	26.7
50.0		30.0	26.9		29.2	25.8	26.9	29.4	25.1	30.8	28.4	25.0	29.5	28.5			24.6	28.4	26.3
54.0			24.9		27.1/53m	24.0		26.5	23.7	24.9/53m	25.5	23.1	25.5	25.9			22.8	26.9	25.5
58.0						21.8			22.0		23.1	20.8		23.5	21.3			23.9	23.5
62.0												18.9		21.5	19.4			19.2/61m	21.4
66.0																			19.7
70.0																			16.3
(°)	18~72	17~61	19~53	18~73	17~61	14~53	17~73	24~61	25~53	16~73	20~61	21~54	23~73	15~62	17~53	19~73	21~62	22~54	
索数	4	4	3	4	4	3	3	3	3	3	3	3	3	3	2	3	3	2	
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	31033	31033	31033	31046	31046	31046	31034	31034	31034	31047	31047	31047	31035	31035	31035	31036	31036	31036	31036

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)						
	66.0			72.0*			78.0*			84.0*			90.0#			96.0#			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
24.0	23.3																		
26.0	23.3			20.2			17.6/27m												
28.0	23.3			20.2			17.6			14.2/29m									
30.0	23.3			20.2			17.6						11.6/31m						
32.0	23.3			20.2			17.6			14.2			11.6					9.0/33m	
34.0	23.3			20.2			17.6			14.2			11.4					8.9	
36.0	23.3			20.2			17.6			14.1			11.3					8.8	
38.0	23.2			20.2			17.6			14.1			11.2					8.6	
40.0	23.2			20.2			17.5			14.1			11.1					8.5	
42.0	23.2	25.7		20.2			17.5			14.0			10.9					8.3	
44.0	23.1	25.2		20.2	19.7		17.4			13.9			10.8					8.2	
46.0	23.1	24.8		20.2	19.7		17.3	17.2/47m		13.8			10.7					8.0	
48.0	23.0	24.3		20.2	19.6		17.2	17.2		13.7			10.5					7.9	
50.0	23.0	23.9		20.2	19.6		17.1	17.1		13.6	13.7		10.4	10.6/53m				7.7	
54.0	22.3	23.0	21.1	20.1	19.5		16.8	16.9		13.3	13.4		10.1	10.6			7.4	7.8/55m	
58.0	21.6	22.2	19.7	19.6	19.4	18.2	16.6	16.7	15.7/61m	13.0	13.1		9.8	10.3			7.1	7.6	
62.0	20.9	20.6	18.3	19.0	19.2	17.3	16.3	16.4	15.6	12.7	12.9	12.3	9.5	10.0			6.8	7.2	
66.0	16.5	18.8	16.8	18.4	18.2	16.1	16.0	16.1	14.9	12.4	12.6	12.1	9.3	9.7	9.7/68m		6.5	6.9	
70.0		17.2	15.3	14.9	16.6	14.6	15.7	15.8	14.2	12.1	12.4	11.6	9.0	9.4	9.5		6.2	6.6	7.0/72m
74.0		16.3/73m	14.0	11.8/73m	15.3	13.3	13.6	15.4	13.4	11.8	12.2	11.0	8.7	9.1	9.1		5.9	6.3	
78.0			12.9		14.1	12.1	10.4	14.1	12.2	11.4	12.0	10.5	8.4	8.9	8.7		5.6	6.0	6.5
82.0						11.1		13.0	11.2	9.7	11.8	10.0	8.1	8.6	8.3		5.4	5.8	6.2
86.0								12.2/85m	10.2	8.2/84m	11.6	9.6	7.9	8.3	8.0		5.1	5.5	5.9
90.0									9.7		10.9	9.2	6.3	8.0	7.6		5.0	5.3	5.6
94.0												8.5		7.8	7.3		4.8	5.1	5.3
96.0														7.6	7.1		4.5	5.0	5.2
98.0															6.9			4.9	5.1
102.0																6.7/101m		4.8	4.8
106.0																			



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 140t  
アウドリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 40.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	24.0			27.0			30.0			33.0			36.0			39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
16.0	65.5/17m			60.4/17m			56.0/17m			48.8/17m									
18.0	65.5			60.3			56.0			48.8			43.0					38.9/19m	
20.0	63.0			60.1			56.0			48.8			43.0					38.9	
22.0	60.0			56.9			55.0			48.8			43.0					38.9	
24.0	56.5			54.2			52.0			47.7			43.0					38.9	
26.0	53.5			51.9			49.5			46.1			42.0					38.8	
28.0		41.5		50.1			47.5	40.0/29m		44.7			41.0					38.4	
30.0		39.0		48.8	38.8		46.0	38.5		43.6	35.5/31m		40.5					38.0	
32.0		37.5			36.9		45.5	36.5		42.8	34.6		40.0	32.5				37.7	
34.0		35.5			35.0			34.5		42.1	32.7		39.5	31.0				37.3	30.7
36.0			29.9		33.9			33.0		41.8	31.3		39.0	29.7				36.9	29.5
38.0			27.8		32.7	27.0/39m		31.5	26.9/39m	29.9			38.5	28.3				36.5	28.2
40.0			26.7			26.4		31.0	26.3	29.1	24.9		27.5					36.1	27.0
42.0						25.1			25.0	28.3	23.7		26.6	22.7				35.7	25.9
44.0						24.3			24.0	28.1	22.7		26.2	21.7				25.5	21.1
46.0									23.0		21.8		25.9	20.7				25.1	20.1
48.0											21.2		20.1					24.7	19.4
50.0											20.6		19.4					24.3	18.6
52.0																			18.2
54.0																			17.7
(°)	31~62	29~52	28~45	24~66	22~52	20~42	28~68	26~59	24~48	22~70	19~58	18~50	25~70	23~59	30~50	20~70	18~58	25~50	
索数	5	4	3	5	3	2	5	3	2	4	3	2	4	3	2	3	3	3	2
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	31030	31030	31030	31043	31043	31043	31031	31031	31031	31044	31044	31044	31032	31032	31032	31045	31045	31045	

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	42.0			45.0			48.0			51.0			54.0			60.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
20.0	35.5			32.1			29.2/21m												
22.0	35.5			32.1			29.2			27.2			25.2/23m						
24.0	35.5			32.1			29.2			27.2			25.2					21.9	
26.0	35.5			32.1			29.2			27.2			25.2					21.9	
28.0	35.5			32.1			29.2			27.2			25.2					21.9	
30.0	35.5			32.1			29.2			27.2			25.2					21.9	
32.0	35.0			32.0			29.2			27.2			25.2					21.9	
34.0	35.0	29.4/35m		32.0			29.2			27.1			25.2					21.9	
36.0	34.5	28.7		31.8	27.3/37m		29.2			27.1			25.1					21.9	
38.0	34.5	27.4		31.7	26.7		29.1	26.2		27.1	24.9/39m		25.1					21.9	
40.0	34.0	26.3		31.4	25.6		29.0	25.1		27.1	24.5		25.1	23.3/41m				21.9	
42.0	33.5	25.2		31.2	24.5		28.8	24.0		27.0	23.6		25.1	22.8				21.9	19.9/43m
44.0	33.0	24.4		30.9	23.6		28.7	23.1		26.9	22.7		25.0	22.0				21.9	19.6
46.0		23.6	19.8	30.6	22.7		28.5	22.2		26.7	21.9		25.0	21.1				21.9	19.1
48.0		23.1	19.0	30.3	22.1	18.4	28.2	21.5	17.6/49m	26.5	21.1		24.9	20.4				21.9	18.6
50.0		22.7	18.2		21.5	17.5	28.0	20.8	17.2	26.3	20.3	16.5/51m	24.7	19.7	15.5/53m			21.8	18.1
54.0			17.0		20.9	16.2		19.9	15.7	26.0	19.7	15.5	24.5	18.6	15.2	21.6	17.2	14.1/56m	
58.0			16.4			15.3		19.4	14.6		19.0	14.2		17.8	13.9	21.4	16.5	13.6	
62.0						14.9			13.9		18.4	13.6		17.3	12.9	19.6	15.9	12.6	
66.0												13.1			12.2		15.4	11.8	
70.0															11.8		15.0	11.1	
74.0																			10.6
(°)	23~70	28~59	20~50	19~72	24~58	15~50	22~72	20~59	26~51	17~72	15~60	22~51	26~72	25~59	18~51	19~72	18~60	23~52	
索数	3	3	2	3	3	2	3	2	2	3	2	2	2	2	2	2	2	2	2
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	31033	31033	31033	31046	31046	31046	31034	31034	31034	31047	31047	31047	31035	31035	31035	31036	31036	31036	

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	66.0 *			72.0 *			78.0 #			84.0 #			90.0 #			96.0 #			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
26.0	17.0																		
28.0	17.0			14.3			12.6/29m												
30.0	17.0			14.3			12.6			10.0/31m									
32.0	17.0			14.3			12.6			10.0			8.3/33m						
34.0	17.0			14.3			12.5			10.0			8.3					6.4/35m	
36.0	17.0			14.3			12.5			10.0			8.3					6.3	
38.0	17.0			14.3			12.4			10.0			8.2					6.2	
40.0	17.0			14.3			12.4			10.0			8.2					6.1	
42.0	17.0			14.3			12.4			10.0			8.2					5.9	
44.0	17.0			14.3			12.4			10.0			8.1					5.8	
46.0	17.0	19.1		14.3			12.4			10.0			8.1					5.7	
48.0	17.0	18.5		14.3	13.7/49m		12.4			10.0			8.1					5.6	
50.0	17.0	17.9		14.3	13.7		12.4	12.6/52m		10.0			8.0					5.5	
54.0	17.0	16.8		14.3	13.5		12.4	12.5		10.0	9.5		8.0					5.3	
58.0	17.0	15.6	12.7/60m	14.3	13.3		12.4	12.2		10.0	9.5		7.9	7.8/59m				5.1	5.4/60m
62.0	17.0	14.8	12.2	14.3	13.1	11.2/63m	12.3	12.0		10.0	9.5		7.8	7.8				4.9	5.3
66.0	17.0	14.3	11.1	14.3	12.8	10.4	12.3	11.7	8.9/67m	9.9	9.5		7.7	7.7				4.7	5.1
70.0		13.8	10.1	14.3	12.4	9.5	12.3	11.4	8.4	9.8	9.5	7.7	7.6	7.6				4.6	4.9



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 140t  
アウトリガ 12.2 × 12.0m

主ジブ長さ+アダプタ長さ 45.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	48.4/19m			40.1											
20.0	48.3			40.1			32.7								
22.0	47.2			40.1			32.7			27.8			24.5/23m		
24.0	45.1			39.9			32.7			27.8			24.5		
26.0	43.3			38.9			32.7			27.8			24.5		
28.0	41.9			38.0			32.6			27.8			24.5		
30.0	40.8			37.2			32.4			27.8			24.5		
32.0	40.1	31.3		36.6	28.8/33m		32.3			27.8			24.5		
34.0		29.7		36.1	28.1		32.1			27.7			24.4		
36.0		28.5		35.7	26.8		32.0	25.5		27.7			24.4		
38.0		27.3		35.4	25.5		31.8	24.5		27.6	22.6/39m		24.3		
40.0		26.6	21.2/41m		24.6		31.6	23.4		27.5	22.1		24.3	20.8/41m	
42.0			20.7		23.7	19.2/43m	31.5	22.3		27.4	21.0		24.2	20.4	
44.0			19.9		23.3	18.8	31.3	21.7		27.2	20.1		24.1	19.6	
46.0			19.1		22.8	18.0		21.0	16.6/47m	27.1	19.2		24.0	18.8	
48.0						17.4		20.7	16.3	26.9	18.5		23.8	18.0	
50.0						16.7		20.3	15.6	26.7	17.8	14.7	23.7	17.2	
52.0									15.1	17.4	14.1	14.1	23.6	16.6	
54.0									14.5	17.0	13.4	13.4	23.4	16.1	12.9
56.0									14.2	16.7	12.9			15.8	12.4
58.0									13.9	16.5	12.4			15.5	11.8
60.0											12.1			15.2	11.3
62.0											11.7			14.9	10.9
64.0															10.6
66.0															10.3
68.0															10.1
70.0															9.8
(°)	15~62	18~50	21~42	13~70	16~57	28~48	12~70	24~57	17~48	11~70	14~57	24~50	20~71	21~59	15~50
架数	4	3	2	3	3	2	3	2	2	3	2	2	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	31043	31043	31043	31044	31044	31044	31045	31045	31045	31046	31046	31046	31047	31047	31047

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフイングジブ)

カウンタウエイト 140t  
アウトリガ 12.2 × 12.0m

主ジブ長さ+アダプタ長さ 50.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0				29.9											
20.0	35.0			29.7			24.1/21m								
22.0	34.2			29.2			24.1			21.1/23m					
24.0	33.9			28.7			24.1			21.1			18.6		
26.0	33.6			28.6			24.1			21.1			18.6		
28.0	33.3			28.5			24.1			21.1			18.6		
30.0	32.7			28.4			24.1			21.1			18.6		
32.0	32.2			28.2			24.0			21.0			18.6		
34.0		25.0		28.0	22.5/35m		23.9			20.9			18.6		
36.0		23.8		27.8	22.0		23.8			20.8			18.5		
38.0		22.7		27.5	20.9		23.8	19.2		20.7			18.4		
40.0		22.0			20.1		23.7	18.3		20.6	16.9/41m		18.3		
42.0		21.2			19.2		23.6	17.4		20.5	16.4		18.2		
44.0			17.3		18.7		23.5	16.8		20.4	15.7		18.1	14.9	
46.0			16.5		18.1	15.0		16.1		20.3	14.9		18.0	14.3	
48.0			15.8		17.8	14.3		15.7		20.1	14.4		17.9	13.7	
50.0					13.6		15.2	12.4		20.0	13.8		17.8	13.1	
52.0					13.1		15.0	11.9		13.3	10.7/53m	17.7	17.7	12.5	
54.0					12.7		14.8	11.3		12.9	10.4	17.6	17.6	11.9	
56.0								11.0		12.6	10.0		11.7	9.1/57m	
58.0								10.6		12.4	9.5		11.5	8.9	
60.0											9.2		11.3	8.5	
62.0											8.8		11.0	8.1	
64.0											8.6		10.8	7.8	
66.0											8.4		10.6	7.5	
68.0														7.3	
70.0															7.1
(°)	20~61	13~49	21~39	18~69	12~55	19~46	16~69	11~56	26~47	15~69	20~57	16~49	22~71	9~57	22~49
架数	3	2	2	3	2	2	2	2	2	2	2	2	2	2	2
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73
DSコード	31043	31043	31043	31044	31044	31044	31045	31045	31045	31046	31046	31046	31047	31047	31047

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフイングジブ)

カウンタウエイト 140t  
アウトリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
20.0	28.0/21m			22.5											
22.0	26.0			22.6			18.1								
24.0	27.8			22.6			18.1			16.6			14.7/25m		
26.0	27.2			22.5			18.1			16.6			14.7		
28.0	26.6			22.3			18.1			16.6			14.7		
30.0	26.1			22.1			18.1			16.6			14.7		
32.0	25.6			21.9			18.1			16.4			14.7		
34.0				21.7			18.1			16.3			14.7		
36.0		19.2		21.6	17.1/37m		18.1			16.1			14.6		
38.0		18.2		21.4	16.7		18.1			16.0			14.5		
40.0		17.6			16.0		18.1	14.9		15.8			14.3		
42.0		16.9			15.4		18.1	14.2		15.7	12.8/43m		14.2		
44.0					14.9		18.1	13.6		15.6	12.5		14.1		
46.0			12.9/47m		14.4			13.1		15.5	11.9		13.9	11.1	
48.0			12.7		14.0	11.3/49m		12.7		15.4	11.4		13.8	10.6	
50.0			12.2			11.1		12.2		15.4	10.9		13.7	10.2	
52.0						10.6		12.0	9.4/53m		10.5		13.7	9.7	
54.0						10.2		11.7	9.2		10.1		13.6	9.3	
56.0									8.8		9.8	7.8		8.9	
58.0									8.5		9.6	7.4		8.6	
60.0									8.2			7.1		8.4	6.3
62.0									7.9			6.7		8.2	6.0
64.0												6.5		8.1	5.7
66.0												6.2		7.9	5.4
68.0															5.2
70.0															5.0
74.0															4.7
(°)	24~60	24~47	22~36	21~68	22~54	29~44	19~69	20~55	18~45	18~69	25~56	24~47	24~70	17~56	16~47
架数	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83
DSコード	31043	31043	31043	31044	31044	31044	31045	31045	31045	31046	31046	31046	31047	31047	31047





TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 120t  
アウドガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 25.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	24.0			27.0			30.0			33.0			36.0			39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
14.0	111.0			101.0			92.5			83.6			76.0/15m						
16.0	106.0			99.0			91.5			83.0			76.0					67.5	
18.0	99.5			95.0			89.0			82.3			76.0					67.5	
20.0	91.5			89.9			86.0			81.3			76.0					67.5	
22.0	83.0	76.0		84.2			82.0			79.1			75.5					67.5	
24.0	76.5	71.0		78.3	69.4		78.0	68.0		76.4	64.5/25m		74.0					66.4	
26.0		67.0		72.1	65.3		72.0	64.0		71.2	62.7		71.5	61.5				65.2	
28.0		60.5	54.0/29m	65.3	60.0		65.0	59.5		64.6	59.2		64.5	58.0				64.1	57.2
30.0		55.0	51.5	62.4/29m	54.6	48.7/31m	59.0	54.0	48.5/31m	58.7	53.7		58.5	54.0				58.5	53.5
32.0			47.0	49.9	46.5		49.5	46.0		53.7	49.1	43.8/33m	53.5	49.5				53.5	48.8
34.0			43.5	46.0	42.8		45.5	42.5		49.4	45.1	41.9	49.5	45.5	42.0			49.2	44.9
36.0					39.6		42.0	39.5	45.2/35m	41.7	38.7	46.0	46.0	42.0	39.0	45.5	41.4	38.4	38.4
38.0					36.9			36.5		38.8	35.9		39.0	36.0	42.3	38.4	35.6	35.6	35.6
40.0								34.0		36.2	33.5		36.5	33.5	39.5	35.8	33.1	33.1	33.1
42.0												31.4	34.0	31.5	36.1/41m	33.5	30.9	30.9	30.9
44.0												29.5		29.8		31.5	29.0	29.0	29.0
46.0														28.1		29.7	27.3	27.3	27.3
48.0																	25.7	25.7	25.7
50.0																		25.7	25.7
(°)	32~66	27~57	26~47	19~68	19~56	17~47	29~71	24~60	23~52	17~73	17~61	16~52	26~72	22~62	20~54	16~72	16~61	20~53	20~53
係数	9	6	5	8	6	4	8	6	4	7	5	4	6	4	6	5	3	6	3
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03
DSコード	32030	32030	32030	32043	32043	32043	32031	32031	32031	32044	32044	32044	32032	32032	32032	32045	32045	32045	32045

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)				
	42.0			45.0			48.0			51.0			54.0			60.0				
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)				
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65		
16.0	60.5/17m			54.2/17m			49.0			45.0/19m										
18.0	60.5			54.2			49.0			45.0			41.0					36.0/21m		
20.0	60.5			54.2			49.0			45.0			41.0					36.0		
22.0	60.5			54.2			49.0			45.0			41.0					36.0		
24.0	60.0			54.2			49.0			45.0			41.0					36.0		
26.0	59.5			54.0			49.0			45.0			41.0					36.0		
28.0	59.0	54.0/29m		53.8			49.0			44.9			41.0					36.0		
30.0	58.0	53.0		53.6	51.5		49.0			44.8			41.0					36.0		
32.0	53.0	48.5		52.8	48.1		49.0	48.0		44.6	44.7/33m		41.0					36.0		
34.0	49.0	44.5		48.5	44.1		48.5	44.0		44.4	43.4		41.0	40.5				36.0		
36.0	45.0	41.5		44.8	40.7		44.5	40.5		44.2	40.0		41.0	40.0				36.0	34.5/37m	
38.0	42.0	38.5	35.5	41.6	37.7	33.6/39m	41.5	37.5		40.9	37.0		41.0	37.0				36.0	34.5	
40.0	39.0	35.5	33.0	38.8	35.1	32.3	38.5	35.0	31.5/41m	38.1	34.3		38.0	34.5				36.0	34.0	
42.0	36.5	33.5	31.0	36.2	32.8	30.2	36.0	33.0	30.0	35.6	32.0	28.4/43m	35.5	32.0				36.0	32.5	
44.0		31.5	29.1	34.0	30.7	28.2	34.0	30.5	28.5	33.3	29.9	27.4	33.5	30.0	27.0/45m			33.5	30.5	
46.0		29.7	27.4	32.0	28.8	26.5	32.0	29.1	26.8	31.3	28.1	25.7	31.5	28.5	26.2			31.5	28.7	
48.0		28.0	25.8	27.2	24.9	23.0	30.0	27.4	25.2	29.5	26.4	24.1	29.8	26.8	24.6			29.9	27.0	24.7
50.0			24.4	25.7	23.5	21.5	25.9	23.8	21.9	27.9	24.9	22.7	28.2	25.3	23.2			28.3	25.4	23.3
54.0					21.1	19.4	23.4	21.4	19.4	25.9/52m	22.3	20.2	24.2	22.7	20.7			25.4	22.8	20.8
58.0										20.7/57m	18.2	20.2	24.2	22.7	20.7			23.0	20.6	18.7
62.0											17.0/61m				17.0			18.7	16.9	16.9
66.0																		17.1	15.5	15.5
70.0																				14.2
(°)	24~72	20~62	26~53	19~73	23~62	22~54	22~73	18~61	18~54	18~73	18~62	17~54	21~73	24~62	23~53	25~74	16~62	16~54	16~54	
係数	5	5	3	5	4	3	4	4	3	4	4	3	4	4	2	3	3	2	2	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	
DSコード	32033	32033	32033	32046	32046	32046	32034	32034	32034	32047	32047	32047	32035	32035	32035	32036	32036	32036	32036	

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)				
	66.0			72.0			78.0*			84.0*			90.0#			96.0#				
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)				
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65		
22.0	28.0/23m																			
24.0	28.0			24.0/25m																
26.0	28.0			24.0			21.0													
28.0	28.0			24.0			21.0			17.0										
30.0	28.0			24.0			21.0			16.9			13.5							
32.0	28.0			24.0			21.0			16.9			13.3					10.4		
34.0	28.0			24.0			21.0			16.8			13.1					10.3		
36.0	27.9			24.0			21.0			16.7			12.9					10.1		
38.0	27.9			24.0			21.0			16.6			12.7					9.9		
40.0	27.8	29.5		24.0			20.8			16.6			12.5					9.7		
42.0	27.7	29.3		24.0	23.5		20.7			16.5			12.3					9.5		
44.0	27.7	29.2		24.0	23.5		20.5	20.9/45m		16.2			12.1					9.3		
46.0	27.6	27.9		24.0	23.5		20.2	20.8		15.9			11.9					9.1		
48.0	27.3	26.2		24.0	23.5		20.0	20.6		15.6	16.4		11.7					9.0		
50.0	27.0	24.7	21.2/52m	24.0	23.5		19.7	20.4		15.3	16.1		11.5	12.0				8.8	9.0/53m	
54.0	24.7	22.0	20.0	23.6	21.5	18.9/55m	19.2	19.9		14.7	15.4		11.1	11.6				8.4	8.9	
58.0	22.3	19.8	17.9	21.7	19.2	17.3	18.7	19.4	17.1/59m	14.1	14.8		10.7	11.1				8.0	8.5	
62.0	20.2	17.9	16.1	19.7	17.3	15.4	18.2	17.5	15.7	13.6	14.3	15.0	10.3	10.7	11.0/65m			7.6	8.1	
66.0	15.7	16.3	14.5	17.9	15.7	13.8	17.7	15.9	14.0	13.2	13.8	13.9	9.9	10.4	10.9	10.4		7.2	7.7	7.9/69m
70.0		14.9	13.2	14.4	14.3	12.4	16.3	14.4	12.6	12.7	13.3	12.5	9.5	10.0	10.4	10.4		6.9	7.3	7.8
74.0			12.0		13.0	11.3	13.2	13.1	11.4	12.3	12.9	11.2	9.1	9.6	10.0	10.0		6.5	7.0	7.4
78.0					12.2/77m	10.2	9.9	12.0	10.3	11.9	11.8	10.1	8.8	9.3	9.6	9.6		6.2	6.7	7.0
82.0						9.6/81m		11.0	9.4	9.3	10.8	9.2	8.5	9.0	9.3	9.3		5.9	6.3	6.6
86.0									8.6		9.9	8.3	8.2	8.6	8.5	8.5		5.6	6.0	6.3
90.0											9.3/89m	7.6	6.6/89m	8.3	7.7	7.7		5.3	5.7	6.0
94.0												7.3/92m		8.0	7.0	7.0		5.1	5	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 120t  
アウドリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 30.5m+4.0m

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)						
	24.0			27.0			30.0			33.0			36.0			39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
14.0	96.5/15m			88.4/15m			80.5/15m			70.5/15m									
16.0	93.0			87.0			80.5			70.2			62.0					55.5/17m	
18.0	87.0			83.5			78.5			69.6			62.0					55.5	
20.0	81.5			79.3			76.0			69.1			62.0					55.5	
22.0	77.0			74.9			72.5			67.1			61.5					55.5	
24.0	73.5	62.0		70.6			68.5	58.0/25m		64.8			60.5					55.1	
26.0	71.0	58.0		66.9	57.4		65.0	56.5		62.5	52.4/27m		59.0					54.2	
28.0		55.0		64.2	54.5		62.0	53.5		60.2	51.0		57.5	49.0				53.4	
30.0		52.5	46.5/31m	58.8	51.9		58.5	51.5		57.9	48.6		55.5	46.5				52.5	45.7
32.0		49.0	45.0		48.6	42.9/33m	53.5	48.0	42.5/33m	53.0	46.7		53.0	44.0				50.9	43.9
34.0			41.5		44.7	41.1		44.5	41.0	48.8	43.9	38.6/35m	49.0	42.0				48.6	42.1
36.0			38.5		41.5	38.0		41.0	37.5	44.4	40.5	37.0	45.5	40.5	36.0/37m			44.9	40.2
38.0						35.3		38.0	35.0		37.6	34.3	42.0	38.0	34.5	41.7	37.3	32.8/39m	
40.0						33.0			32.5		35.1	32.0		35.5	32.5	38.9	34.8	31.6	
42.0									30.5		32.9	29.9		33.0	30.0	35.7	32.5	29.5	
44.0											28.1			31.0	28.5		30.5	27.6	
46.0											26.4				26.8		28.7	26.0	
48.0															25.3		27.1	24.5	
50.0																		23.1	
(°)	25~64	24~56	26~47	16~68	15~55	18~47	22~70	21~61	23~53	15~72	13~60	16~52	20~72	19~61	21~52	13~72	12~60	24~52	
索数	8	5	4	7	5	4	7	5	4	6	4	3	5	4	3	5	4	3	
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	32030	32030	32030	32043	32043	32043	32031	32031	32031	32044	32044	32044	32032	32032	32032	32045	32045	32045	32045

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)						
	42.0			45.0			48.0			51.0			54.0			60.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
18.0	50.0			44.6			40.0/19m												
20.0	50.0			44.6			40.0			36.9			33.5/21m						
22.0	50.0			44.6			40.0			36.9			33.5					30.0	
24.0	50.0			44.6			40.0			36.9			33.5					30.0	
26.0	49.5			44.6			40.0			36.9			33.5					30.0	
28.0	49.0			44.4			40.0			36.9			33.5					30.0	
30.0	49.0	43.5/31m		44.3			40.0			36.9			33.5					30.0	
32.0	48.5	42.5		44.1	41.4		40.0			36.9			33.5					30.0	
34.0	48.0	40.5		43.9	39.6		40.0	38.5		36.9	36.2/35m		33.5					30.0	
36.0	44.5	39.0		42.9	38.0		40.0	37.0		36.9	35.7		33.5	33.5				30.0	
38.0	41.5	37.0		41.1	36.4		40.0	35.5		36.9	34.6		33.5	32.5				28.1/39m	
40.0	38.5	34.5	31.5	38.2	34.0		38.0	34.0		36.2	33.2		33.5	31.5				30.0	27.9
42.0	36.0	32.5	29.7	35.7	31.7	28.7	35.5	32.0		35.1	31.0		33.5	31.0				30.0	27.7
44.0	33.5	30.5	27.8	33.5	29.7	26.8	33.5	30.0	27.2	32.8	28.9	25.2/45m	32.5	29.4				29.9	27.3
46.0		28.7	26.1	31.6	27.9	25.2	31.5	28.1	25.5	30.8	27.1	24.3	31.0	27.6	24.1/47m			29.9	27.0
48.0		27.1	24.6	30.7/47m	26.3	23.6	29.9	26.5	24.0	29.0	25.5	22.8	29.4	25.9	23.3	21.1		29.1	26.1
50.0		25.7	23.2		24.8	22.3	26.9	25.0	22.6	27.4	24.0	21.4	27.8	24.4	22.0	20.7		27.9	24.6
54.0			20.9		23.0/53m	19.9		22.5	20.2	24.9/53m	21.4	19.1	25.0	21.9	19.6	18.2		25.0	22.0
58.0						18.1				18.3		17.0		19.8	17.6	16.7		19.8	17.7
62.0												15.4		18.0	15.9	14.5		18.0	15.9
66.0																			14.4
70.0																			13.2
(°)	18~72	17~61	19~53	18~73	17~61	14~53	17~73	24~61	25~53	16~73	20~61	21~54	23~73	15~62	17~53	19~73	21~62	22~54	
索数	4	4	3	4	4	3	3	3	3	3	3	2	3	3	2	3	3	2	
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	32033	32033	32033	32046	32046	32046	32034	32034	32034	32047	32047	32047	32035	32035	32035	32036	32036	32036	32036

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)							
	66.0			72.0*			78.0*			84.0*			90.0#			96.0#				
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)				
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65		
24.0	23.3																			
26.0	23.3						17.6/27m													
28.0	23.3						17.6													
30.0	23.3						17.6			14.2/29m										
32.0	23.3						17.6			14.2			11.6					9.0/33m		
34.0	23.3						17.6			14.2			11.4					8.9		
36.0	23.3						17.6			14.1			11.3					8.8		
38.0	23.2						17.6			14.1			11.2					8.6		
40.0	23.2						17.5			14.1			11.1					8.5		
42.0	23.2	25.7					17.5			14.0			10.9					8.3		
44.0	23.1	25.2					17.4			13.9			10.8					8.2		
46.0	23.1	24.8					17.3	17.2/47m		13.8			10.7					8.0		
48.0	23.0	24.3					17.2	17.2		13.7			10.5					7.9		
50.0	23.0	23.8					17.1	17.1		13.6	13.7		10.4	10.6/53m				7.7		
54.0	22.3	21.2	18.8				16.8	16.9		13.3	13.4		10.1	10.6				7.4	7.8/55m	
58.0	21.6	19.0	16.7				16.6	16.7	15.0/61m	13.0	13.1		9.8	10.3				7.1	7.6	
62.0	19.9	17.2	15.0				16.3	16.4	14.5	12.7	12.9		9.5	10.0				6.8	7.2	
66.0	16.5	15.6	13.4				16.0	15.2	13.0	12.4	12.6	12.1	9.3	9.7	9.7/68m			6.5	6.9	
70.0		14.2	12.1				15.7	13.7	11.6	12.1	12.4	11.4	9.0	9.4	9.5	6.2	6.6	6.6	7.0/72m	
74.0		13.4/73m	11.0				13.6	12.4	10.4	11.8	12.2	10.2	8.7	9.1	9.1	5.9	6.3	6.8		
78.0			10.1				11.2	9.3	10.4	11.3	9.4	11.4	9.2	8.4	8.9	8.7	5.6	6.0	6.5	
82.0								8.4		10.3	8.5	9.7	10.1	8.3	8.1	8.6	8.3	5.4	5.8	6.2
86.0										9.7/85m	7.7	8.2	9.7	7.9	7.9	8.3	7.7	5.1	5.5	5.9
90.0											7.2/89m		9.3	7.5	6.3	8.0	6.9	5.0	5.3	5.6
94.0													8.5	6.8		7.8	6.2	4.8	5.1	5.3
96.0																7.5	5.9	4.5	5.0	5.2
98.0																	5.6		4.9	5.1
102.0																			4.8	4.8
106.0																5.2/101m				4.3
(°)	20~73	17~61	15~54																	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 120t  
アウドリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 35.5m+4.0m

作業半径 (m)	補ジブ長さ(m) 24.0			補ジブ長さ(m) 27.0			補ジブ長さ(m) 30.0			補ジブ長さ(m) 33.0			補ジブ長さ(m) 36.0			補ジブ長さ(m) 39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	81.5			73.2/17m			67.5			60.2			54.5/17m					
18.0	77.0			72.1			66.5			59.9			54.5				49.3	
20.0	72.5			69.2			65.0			59.5			54.5				49.3	
22.0	68.0			66.0			62.5			58.8			54.5				49.3	
24.0	64.5			62.7			60.0			56.8			53.5				49.3	
26.0	62.0	50.5		59.7			57.5	46.5/27m		55.1			52.5				48.7	
28.0		48.0		57.4	46.6		55.5	45.5		53.7	43.4/29m		51.0				48.0	
30.0		45.5		56.0	44.3		54.0	43.0		52.5	42.2		50.0	41.5			47.4	
32.0		44.0		42.5			52.5	41.0		51.6	40.3		49.5	39.5			46.7	39.1
34.0			36.5	40.8			39.5			48.2	38.3		48.5	37.5			46.1	37.5
36.0			35.0	39.6	33.8		38.0	32.5		44.6	37.0		44.5	36.0			44.4	35.9
38.0			33.0	37.5	32.4		37.0	31.5		35.7	30.9		41.5	34.5	30.0/39m		41.2	34.3
40.0					31.3			30.0		34.0	29.7		33.5	29.3			38.4	33.4
42.0					29.5			29.3		31.8	28.4		32.0	27.9			36.0	31.5
44.0								27.6		30.0	26.7		30.0	26.9			29.5	26.1
46.0											25.1			25.6			27.7	24.7
48.0											23.7			24.1			26.2	23.2
50.0														22.8			24.8	21.9
52.0																		20.8
54.0																		19.7
(°)	28~63	32~54	27~44	21~64	8~53	19~45	25~69	28~60	24~50	19~71	7~59	17~50	23~71	26~60	22~52	17~71	6~59	16~52
索数	7	4	3	6	4	3	6	4	3	5	4	3	5	4	3	4	3	3
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	32030	32030	32030	32043	32043	32043	32031	32031	32031	32044	32044	32044	32032	32032	32032	32045	32045	32045

作業半径 (m)	補ジブ長さ(m) 42.0			補ジブ長さ(m) 45.0			補ジブ長さ(m) 48.0			補ジブ長さ(m) 51.0			補ジブ長さ(m) 54.0			補ジブ長さ(m) 60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	45.0/19m			39.8/19m														
20.0	45.0			39.8			35.5			32.8/21m								
22.0	45.0			39.8			35.5			32.8			30.0				27.0/23m	
24.0	45.0			39.8			35.5			32.8			30.0				27.0	
26.0	45.0			39.8			35.5			32.8			30.0				27.0	
28.0	44.5			39.8			35.5			32.8			30.0				27.0	
30.0	44.5			39.7			35.5			32.8			30.0				27.0	
32.0	44.0	37.5/33m		39.6			35.5			32.8			30.0				27.0	
34.0	43.5	36.5		39.5	35.7		35.5			32.8			30.0				27.0	
36.0	43.0	35.0		39.2	34.2		35.5	33.0		32.8	31.7/37m		30.0				27.0	
38.0	41.0	33.5		38.9	32.7		35.5	32.0		32.8	31.2		30.0	30.0			27.0	
40.0	38.0	32.0		37.7	31.5		35.0	30.5		32.7	30.2		30.0	28.9			27.0	24.9/41m
42.0	36.0	31.0	26.2/43m	35.3	30.3		35.0	29.7		32.6	29.2		30.0	27.9			27.0	24.6
44.0	33.5	29.6	25.6	33.1	28.7	24.4/45m	33.0	28.8		32.3	27.9		29.9	27.1			27.0	24.0
46.0		27.8	24.4	31.1	26.9	23.8	31.0	27.2	23.5	30.4	26.1		29.8	26.2			27.0	23.5
48.0		26.2	23.4	29.4	25.4	22.4	29.5	25.6	22.4	28.6	24.5	21.5	28.9	25.0			26.9	23.0
50.0		24.8	22.1		23.9	21.1	27.9	24.2	21.4	27.0	23.1	20.1	27.3	23.6	20.5		26.7	22.5
54.0			19.8		21.5	18.8		21.7	19.1	24.3	20.6	17.7	24.6	21.1	18.4		24.7	21.2
58.0						16.8			17.2	18.6	15.8		19.0	16.4			22.3	19.1
62.0									15.6			14.1		17.3	14.7		18.7	17.3
66.0												12.8		13.4			15.8	13.4
70.0																		12.1
74.0																		11.1
(°)	21~71	23~60	27~52	16~72	19~61	23~51	19~71	28~60	18~53	15~72	24~61	13~52	24~72	21~61	24~52	17~73	25~61	16~53
索数	4	3	2	3	3	2	3	3	2	3	3	2	3	3	2	2	2	2
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	32033	32033	32033	32046	32046	32046	32034	32034	32034	32047	32047	32047	32035	32035	32035	32036	32036	32036

作業半径 (m)	補ジブ長さ(m) 66.0			補ジブ長さ(m) 72.0 *			補ジブ長さ(m) 78.0 *			補ジブ長さ(m) 84.0 #			補ジブ長さ(m) 90.0 #			補ジブ長さ(m) 96.0 #		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
24.0	21.0/25m																	
26.0	21.0			18.5/27m														
28.0	21.0			18.5			16.0											
30.0	21.0			18.5			16.0			13.0								
32.0	21.0			18.5			16.0			13.0			11.0					
34.0	21.0			18.5			16.0			13.0			10.9				8.5	
36.0	21.0			18.5			16.0			13.0			10.9				8.4	
38.0	21.0			18.5			16.0			13.0			10.8				8.3	
40.0	21.0			18.5			16.0			13.0			10.8				8.1	
42.0	21.0			18.5			16.0			13.0			10.7				8.0	
44.0	21.0	24.6		18.5			16.0			13.0			10.6				7.9	
46.0	21.0	23.7		18.5	18.0		16.0			13.0			10.5				7.8	
48.0	21.0	22.9		18.5	18.0		16.0	15.3/49m		13.0			10.5				7.6	
50.0	21.0	22.1		18.5	17.9		16.0	15.3		13.0	12.5/52m		10.4				7.5	
54.0	21.0	20.4	16.0/57m	18.5	17.8		16.0	15.3		13.0	12.5		10.2	10.5/55m			7.2	7.5/57m
58.0	21.0	18.3	15.5	18.5	17.6	13.5/61m	16.0	15.3		13.0	12.5		10.0	10.3			6.9	7.4
62.0	19.5	16.5	13.8	18.5	15.8	13.1	16.0	15.3	12.6/64m	13.0	12.5		9.8	10.1			6.6	7.1
66.0	17.2	14.9	12.3	17.2	14.2	11.6	15.9	14.5	11.9	12.8	12.5	10.9/68m	9.6	9.9			6.3	6.8
70.0		13.5	11.1	15.4	12.8	10.4	15.9	13.0	10.6	12.5	12.5	10.4	9.3	9.7	9.5/71m		6.1	6.5
74.0		12.3	10.0	11.3	11.6	9.3	14.0	11.8	9.5	12.1	11.6	9.3	9.1	9.5	9.2	5.8	6.2	6.7/75m
78.0			9.1		10.5	8.3	10.8	10.6	8.5	11.8	10.5	8.3	8.9	9.3	8.8	5.6	6.0	6.5
82.0						7.5		9.7	7.6	9.9	9.5	7.4	8.6	9.1	8.3	5.4	5.8	6.3
86.0						6.9		8.9	6.8	7.8/85m	8.6	6.6	8.4	8.8	7.9	5.2	5.6	6.0
90.0									6.2		7.9	5.9	6.5	8.6	7.5	5.1	5.4	5.8
94.0												5.3		8.3	7.1	5.0	5.3	5.2
98.0												4.9		8.1	6.6	4.1/97m	5.2	4.6
102.0															6.2		5.1	4.1
106.0																		3.6
110.0																		3.3/109m
(°)	22~73	18~61	21~52	16~72	22~62	15~52	20~73	17~62	20~53	17~73	21~62	14~53	19~73	16~61	18~53	16~73	19~62	15~53
索数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	32037	32037	32037	32038	32038	32038	32											



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 120t  
アウドリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 40.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	24.0			27.0			30.0			33.0			36.0			39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	65.5/17m			60.4/17m			56.0/17m			48.8/17m								
18.0	65.5			60.3			56.0			48.8			43.0					38.9/19m
20.0	63.0			60.1			56.0			48.8			43.0					38.9
22.0	60.0			56.9			55.0			48.8			43.0					38.9
24.0	56.5			54.2			52.0			47.7			43.0					38.9
26.0	53.5			51.9			49.5			46.1			42.0					38.8
28.0		41.5		50.1			47.5	40.0/29m		44.7			41.0					38.4
30.0		39.0		48.8	38.8		46.0	38.5		43.6	35.5/31m		40.5					38.0
32.0		37.5			36.9		45.5	36.5		42.8	34.6		40.0	32.5				37.7
34.0		35.5			35.0			34.5		42.1	32.7		39.5	31.0				37.3
36.0			29.9		33.9			33.0		41.8	31.3		39.0	29.7				36.9
38.0			27.8		32.7	27.0/39m		31.5	26.9/39m		29.9		38.5	28.3				36.5
40.0			26.7			26.4		31.0	26.3		29.1	24.9		27.5				36.1
42.0						25.1			25.0		28.3	23.7		26.6	22.7			35.6
44.0						24.3			24.0		28.1	22.7		26.2	21.7			25.5
46.0									23.0			21.8		25.9	20.7			25.1
48.0												21.2			20.1			24.7
50.0												20.6			19.4			24.1
52.0																		18.2
54.0																		17.7
(°)	31~62	29~52	28~45	24~66	22~52	20~42	28~68	26~59	24~48	22~70	19~58	18~50	25~70	23~59	30~50	20~70	18~58	25~50
索数	5	4	3	5	3	2	5	3	2	4	3	2	4	3	2	3	3	2
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	32030	32030	32030	32043	32043	32043	32031	32031	32031	32044	32044	32044	32032	32032	32032	32045	32045	32045

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	42.0			45.0			48.0			51.0			54.0			60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
20.0	35.5			32.1			29.2/21m											
22.0	35.5			32.1			29.2			27.2			25.2/23m					
24.0	35.5			32.1			29.2			27.2			25.2					21.9
26.0	35.5			32.1			29.2			27.2			25.2					21.9
28.0	35.5			32.1			29.2			27.2			25.2					21.9
30.0	35.5			32.1			29.2			27.2			25.2					21.9
32.0	35.0			32.0			29.2			27.2			25.2					21.9
34.0	35.0	29.4/35m		32.0			29.2			27.1			25.2					21.9
36.0	34.5	28.7		31.8	27.3/37m		29.2			27.1			25.1					21.9
38.0	34.5	27.4		31.7	26.7		29.1	26.2		27.1	24.9/39m		25.1					21.9
40.0	34.0	26.3		31.4	25.6		29.0	25.1		27.1	24.5		25.1	23.3/41m				21.9
42.0	33.5	25.2		31.2	24.5		28.8	24.0		27.0	23.6		25.1	22.8				21.9
44.0	33.0	24.4		30.9	23.6		28.7	23.1		26.9	22.7		25.0	22.0				21.9
46.0		23.6	19.8	30.6	22.7		28.5	22.2		26.7	21.9		25.0	21.1				21.9
48.0		23.1	19.0	29.0	22.1	18.4	28.2	21.5	17.6/49m	26.5	21.1		24.9	20.4				21.9
50.0		22.7	18.2		21.5	17.5	27.6	20.8	17.2	26.3	20.3	16.5/51m	24.7	19.7	15.5/53m			21.8
54.0			17.0		20.8	16.2		19.9	15.7	23.9	19.7	15.5	24.2	18.6	15.2	21.6	17.2	14.1/56m
58.0			16.4			15.3		19.0	14.6		17.9	14.2		17.8	13.9	21.4	16.5	13.6
62.0						14.3			13.9		16.2	13.1		16.7	12.9	19.6	15.9	12.6
66.0												11.8			12.2		15.2	11.8
70.0															11.3		13.9	11.1
74.0																		10.3
(°)	23~70	28~59	20~50	19~72	24~58	15~50	22~72	20~59	26~51	17~72	15~60	22~51	26~72	25~59	18~51	19~72	18~60	23~52
索数	3	3	2	3	3	2	3	2	2	3	2	2	2	2	2	2	2	2
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	32033	32033	32033	32046	32046	32046	32034	32034	32034	32047	32047	32047	32035	32035	32035	32036	32036	32036

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	66.0 *			72.0 *			78.0 #			84.0 #			90.0 #			96.0 #		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
26.0	17.0																	
28.0	17.0			14.3			12.6/29m											
30.0	17.0			14.3			12.6			10.0/31m								
32.0	17.0			14.3			12.6			10.0			8.3/33m					
34.0	17.0			14.3			12.5			10.0			8.3				6.4/35m	
36.0	17.0			14.3			12.5			10.0			8.3				6.3	
38.0	17.0			14.3			12.4			10.0			8.2				6.2	
40.0	17.0			14.3			12.4			10.0			8.2				6.1	
42.0	17.0			14.3			12.4			10.0			8.2				5.9	
44.0	17.0			14.3			12.4			10.0			8.1				5.8	
46.0	17.0	19.1		14.3			12.4			10.0			8.1				5.7	
48.0	17.0	18.5		14.3	13.7/49m		12.4			10.0			8.1				5.6	
50.0	17.0	17.9		14.3	13.7		12.4	12.6/52m		10.0			8.0				5.5	
54.0	17.0	16.8		14.3	13.5		12.4	12.5		10.0	9.5		8.0				5.3	
58.0	17.0	15.6	12.7/60m	14.3	13.3		12.4	12.2		10.0	9.5		7.9	7.8/59m			5.1	5.4/60m
62.0	17.0	14.8	12.2	14.3	13.1	11.2/63m	12.3	12.0		10.0	9.5		7.8	7.8			4.9	5.3
66.0	17.0	14.2	11.1	14.3	12.8	10.4	12.3	11.7	8.9/67m	9.9	9.5		7.7	7.7			4.7	5.1
70.0		12.9	10.1	14.3	12.1	9.5	12.3	11.4	8.4	9.8	9.5	7.7	7.6	7.6			4.6	4.9
74.0		11.7	9.2	11.9	11.0	8.4	12.3	11.1	7.7	9.6	9.5	7.1	7.4	7.5	6.9		4.4	4.8
78.0			8.3		9.9	7.5	11.1	10.1	7.2	9.5	9.3	6.6	7.3	7.3	6.3		4.3	4.6
82.0			7.6		9.1	6.7		9.2	6.8	9.3	9.0	6.1	7.2	7.2	5.9		4.2	4.5
86.0						6.1		8.3	6.1	7.3	8.1	5.6	7.1	7.0	5.4		4.1	4.3
90.0									5.5		7.4	5.3	6.7	6.8	5.0		4.0	4.2
94.0									5.0		6.8	4.7		6.6	4.7		3.9	4.1
98.0												4.2		6.2	4.3		3.8	4.0
102.0															3.8		3.9	3.9
106.0															3.4		3.8	3.8
(°)	23~72	22~60	16~52	17~72	16~60	21~52	21~73	20~60	15~52	16~73	15~61	19~53	20~72	19~60	14~52	15~72	14~61	
索数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	32037	32037	32037	32038	32038	32038	32039	32039	32039	32040	32040	32040	32041	32041	32041	32042	32042	32042

単位:t

補ジブ起伏角度(最小-最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* :最大風速7.0m/s # :

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 120t  
アウドガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 45.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	24.0			27.0			30.0			33.0			36.0			39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	52.0/15m			48.4/19m			45.0/19m			40.1								
20.0	51.5			48.3			45.0			40.1			36.0					32.7
22.0	49.5			47.2			45.0			40.1			36.0					32.7
24.0	47.0			45.1			43.5			39.9			36.0					32.7
26.0	44.5			43.3			41.5			38.9			35.5					32.7
28.0	42.5			41.9			40.0			38.0			35.0					32.6
30.0				40.8			39.0			37.2			35.0					32.4
32.0		32.5		40.1	31.3		38.5	30.5		36.6	28.8/33m		34.5					32.3
34.0		30.5			29.7			29.0		36.1	28.1		34.0	27.5				32.1
36.0		29.6			28.5			27.7		35.7	26.8		34.0	26.1				32.0
38.0					27.3			26.5		35.4	25.5		33.5	24.8				31.8
40.0			22.9/19m		26.6	21.2/41m		25.7	20.9/41m		24.6		33.5	23.8				31.6
42.0			21.1			20.7		24.9	20.4		23.7	19.2/43m		22.9				31.5
44.0						19.9			19.6		23.3	18.8		22.3	17.8/45m			31.3
46.0						19.1			18.8		22.8	18.0		21.8	17.4			21.0
48.0									18.2			17.4		21.6	16.7			20.7
50.0												16.7			16.0			20.3
54.0															15.2			14.5
56.0																		14.2
58.0																		13.9
(°)	24~58	26~44	28~41	15~62	18~50	21~42	21~65	23~55	25~48	13~70	16~57	28~48	19~68	21~58	23~48	12~70	24~57	17~48
索数	4	3	2	4	3	2	4	3	2	3	3	2	3	3	2	3	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	32030	32030	32030	32043	32043	32043	32031	32031	32031	32044	32044	32044	32032	32032	32032	32045	32045	32045

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	42.0			45.0			48.0			51.0			54.0			60.0*		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
20.0	30.0/21m																	
22.0	30.0			27.8			26.0			24.5/23m								
24.0	30.0			27.8			26.0			24.5			23.0					
26.0	30.0			27.8			26.0			24.5			23.0			19.0		
28.0	30.0			27.8			26.0			24.5			23.0			19.0		
30.0	30.0			27.8			26.0			24.5			23.0			19.0		
32.0	30.0			27.8			25.9			24.5			23.0			19.0		
34.0	30.0			27.7			25.9			24.4			23.0			19.0		
36.0	30.0	24.4/37m		27.7			25.8			24.4			23.0			19.0		
38.0	30.0	23.8		27.6	22.6/39m		25.7			24.3			22.9			19.0		
40.0	29.8	22.7		27.5	22.1		25.6	21.7		24.3	20.8/41m		22.9			19.0		
42.0	29.7	21.6		27.4	21.0		25.5	20.6		24.2	20.4		22.9	19.5/43m		19.0		
44.0	29.5	20.8		27.2	20.1		25.3	19.7		24.1	19.6		22.8	19.1		19.0		
46.0	29.4	19.9		27.1	19.2		25.2	18.8		24.0	18.8		22.8	18.2		19.0	16.8	
48.0		19.4	15.7/49m	26.9	18.5		25.0	18.0		23.8	18.0		22.7	17.5		19.0	16.3	
50.0		18.8	15.3	26.7	17.8	14.7	24.9	17.3	13.7/52m	23.7	17.2		22.6	16.7		19.0	15.8	
54.0		18.1	14.2		17.0	13.4		16.2	13.0	23.4	16.1	12.9	22.3	15.5	12.2/56m	19.0	14.9	
58.0			13.3		16.5	12.4		15.5	11.9		15.5	11.8	20.8	14.6	11.6	19.0	14.1	11.0/59m
62.0						11.7			11.0		14.9	10.9		13.9	10.6	19.0	13.4	10.3
66.0									10.4			10.3		13.6	9.9		12.8	9.4
70.0												9.8			9.3		12.4	8.7
74.0																		8.2
78.0																		7.7
(°)	17~70	19~58	28~48	11~70	14~57	24~50	24~71	25~58	19~50	20~71	21~59	15~50	15~71	17~59	24~50	21~71	22~59	17~51
索数	3	2	2	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	32033	32033	32033	32046	32046	32046	32034	32034	32034	32047	32047	32047	32035	32035	32035	32036	32036	32036

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	66.0*			72.0#			78.0#			84.0#			90.0#			96.0#		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
26.0	14.7/27m																	
28.0	14.7			11.5/29m														
30.0	14.7			11.5			10.6											
32.0	14.7			11.5			10.5			8.0/33m								
34.0	14.7			11.5			10.4			8.0			6.5/35m					
36.0	14.7			11.5			10.3			8.0			6.5					
38.0	14.7			11.5			10.2			8.0			6.5			4.9		
40.0	14.7			11.5			10.2			8.0			6.5			4.8		
42.0	14.7			11.5			10.1			8.0			6.5			4.6		
44.0	14.7			11.5			10.0			8.0			6.5			4.5		
46.0	14.7			11.5			10.0			8.0			6.5			4.4		
48.0	14.7			11.5			10.0			8.0			6.5			4.3		
50.0	14.7	15.2/49m		11.5			10.0			8.0			6.5			4.2		
54.0	14.7	14.9		11.5	11/51m		10.0			8.0			6.5			4.1		
58.0	14.7	13.8		11.5	10.8		10.0	11.3		8.0	7.5/56m		6.5			3.9		
62.0	14.7	12.9		11.5	10.6		10.0	10.7		8.0	7.5		6.5			3.8		
66.0	14.7	12.1	9.3/63m	11.5	10.3		10.0	10.1		8.0	7.5		6.5	6.0		3.7	4.0	
66.0	14.7	11.4	8.6	11.5	10.0	7.9	10.0	9.5	5.5/69m	8.0	7.5		6.5	6.0		3.6	3.9	
70.0	13.1	10.8	7.7	11.5	9.7	6.9	10.0	9.0	5.4	8.0	7.5	5.3/73m	6.5	6.0		3.5	3.8	
74.0		10.4	7.1	11.5	9.4	6.1	10.0	8.5	4.8	8.0	7.5	5.1	6.5	6.0	5.0/77m	3.5	3.7	
78.0		10.1	6.6		9.0	5.5	10.0	8.1	4.3	8.0	7.3	4.5	6.5	5.9	4.8	3.4	3.6	
82.0			6.2		8.5	5.0	7.8	7.7	3.9	8.0	7.0	3.9	6.5	5.8	4.1	3.4	3.5	
86.0						4.7		7.4	3.7	7.6	6.8	3.5	6.5	5.7	3.6	3.3	3.4	
90.0						4.5		7.1	3.4		6.5	3.2	6.5	5.6	3.1	3.3	3.4	
94.0									3.3		6.2	2.9	4.2	5.5	2.7	3.2	3.3	
98.0												2.8		5.4	2.4	3.0	3.2	
102.0												2.8						
106.0														5.2/101m	2.2		3.1	
(°)	14~72	15~59	22~51	19~72	20~60	16~51	13~72	14~60	20~52	12~72	16~58	14~52	20~72	16~58	19~52	16~72	17~61	
索数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	32037	32037	32037	32038	32038	32038	32039	32039	32039	32040	32040	32040	32041	32041	32041	32042	32042	

補ジブ起伏角度(最小-最大) LKコードジブ伸縮コード DSコード作業設定コード \* :最大風速7.0m/s # :最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 120t  
アウドガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 50.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)				
	24.0			27.0			30.0			33.0			36.0			39.0				
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)				
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65		
18.0	38.0/19m						33/19m			29.9/19m										
20.0	36.0			35.0			32.5			29.7			26.6					24.1/21m		
22.0	37.5			34.2			31.5			29.2			26.6					24.1		
24.0	36.5			33.9			31.0			28.7			26.6					24.1		
26.0	36.0			33.6			31.0			28.6			26.6					24.1		
28.0	35.0			33.3			31.0			28.5			26.4					24.1		
30.0				32.7			31.0			28.4			26.2					24.1		
32.0		26.9		32.2			30.5			28.2			26.1					24.0		
34.0		25.5		25.0			30.0	24.6		28.0	22.5/35m		25.9					23.9		
36.0		24.4		23.8				23.5		27.8	22.0		25.8	20.2/37m				23.8		
38.0		23.4		22.7				22.4		27.5	20.9		25.7	19.7				23.8	19.2	
40.0				22.0				21.5			20.1		25.6	18.9				23.7	18.3	
42.0				21.2				20.6			19.2			18.1				23.6	17.4	
44.0					17.3			20.0	17.0		18.7			17.5				23.5	16.8	
46.0					16.5				16.0		18.1	15.0		16.9					16.1	
48.0					15.8				15.3		17.8	14.3		16.6	13.4				15.7	
50.0									14.5			13.6		16.3	12.8				15.2	12.4
54.0												12.7			11.9				14.8	11.3
56.0																				11.0
58.0																				10.6
(°)	27~60	23~49		20~61	13~49	21~39	24~67	20~54	25~46	18~69	12~55	19~46	22~69	18~55	31~46	16~69	11~56	26~47		
索数	3	2		3	2	2	3	2	2	3	2	2	2	2	2	2	2	2	2	2
LKコード	73	73		73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73
DSコード	32030	32030		32043	32043	32043	32031	32031	32031	32044	32044	32044	32032	32032	32032	32045	32045	32045		

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	42.0			45.0			48.0			51.0			54.0 *			60.0 *					
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)					
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65			
22.0	22.1			21.1/23m																	
24.0	22.1			21.1			20.2			18.6			17.1/25m								
26.0	22.1			21.1			20.2			18.6			17.1						13.5		
28.0	22.1			21.1			20.2			18.6			17.1						13.5		
30.0	22.1			21.1			20.2			18.6			17.1						13.5		
32.0	22.1			21.0			20.1			18.6			17.1						13.5		
34.0	22.1			20.9			20.0			18.6			17.1						13.5		
36.0	22.1			20.8			19.8			18.5			17.0						13.5		
38.0	22.1			20.7			19.6			18.4			17.0						13.5		
40.0	22.1	17.9		20.6	16.9/41m		19.5			18.3			17.0						13.5		
42.0	22.0	17.0		20.5	16.4		19.3	16.1		18.2			17.0						13.5		
44.0	21.9	16.3		20.4	15.7		19.1	15.3		18.1	14.9		17.0	14.2/45m					13.5		
46.0	21.9	15.6		20.3	14.9		19.0	14.5		18.0	14.3		17.0	13.9					13.5		
48.0		15.1		20.1	14.4		18.8	13.9		17.9	13.7		16.9	13.3					13.5	12.1	
50.0		14.5	11.5/52m	20.0	13.8	10.7/53m	18.7	13.2		17.8	13.1		16.8	12.7					13.5	11.7	
54.0		13.9	11.0		12.9	10.4		12.1	9.8	17.6	11.9	9.1/57m	16.6	11.7					13.5	10.9	
58.0			10.2		12.4	9.5		11.6	9.1		11.5	8.9	16.5	10.9	8.5/59m				13.5	10.1	
62.0			9.6			8.8		11.2	8.3		11.0	8.1		10.3	7.9				13.5	9.5	7.4
66.0						8.4			7.7		10.6	7.5		9.9	7.2					9.1	6.7
70.0												7.1			6.6					8.7	6.1
74.0															6.3					8.4	5.6
78.0																					5.3
(°)	20~69	25~56	21~47	15~69	20~57	16~49	25~69	15~58	26~49	22~71	9~57	22~49	18~71	22~58	19~48	23~72	14~58	23~50			
索数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	32033	32033	32033	32046	32046	32046	32034	32034	32034	32047	32047	32047	32035	32035	32035	32036	32036	32036	32036		

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	66.0 #			72.0 #			78.0 #			84.0 #		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65
28.0	10.3											
30.0	10.3			7.8								
32.0	10.3			7.8					6.6			
34.0	10.3			7.8					6.5			4.8
36.0	10.3			7.8					6.5			4.8
38.0	10.3			7.8					6.5			4.8
40.0	10.3			7.8					6.4			4.8
42.0	10.3			7.8					6.4			4.8
44.0	10.3			7.8					6.3			4.8
46.0	10.3			7.8					6.3			4.8
48.0	10.3			7.8					6.3			4.8
50.0	10.3	10.3/51m		7.8	7.5/53m				6.3			4.8
54.0	10.3	9.8		7.8	7.5				6.3			4.8
58.0	10.3	9.0		7.8	7.2				6.3			4.8
62.0	10.3	8.3		7.8	7.0				6.3			4.8
66.0	10.3	7.7		7.8	6.7				6.3			4.8
70.0	10.3	7.3		7.8	6.4				6.3			4.8
74.0		6.9		7.8	6.2				6.3			4.8
78.0		6.6			5.9				6.3			4.8
82.0					5.7				6.3			4.8
86.0					5.4							4.8
(°)	16~72	20~58		21~71	12~59		15~71			19~71		
索数	2	2		2	2		2			2		
LKコード	73	73		73	73		73			73		
DSコード	32037	32037		32038	32038		32039			32040		

補ジブ起伏角度(最小-最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* :最大風速7.0m/s # :最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフイングジブ)

カウンタウエイト 120t  
アウトリガ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	27.0			33.0			39.0			45.0			51.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
20.0	28.0/21m			22.5											
22.0	26.0			22.6			18.1								
24.0	27.8			22.6			18.1			16.6			14.7/25m		
26.0	27.2			22.5			18.1			16.6			14.7		
28.0	26.6			22.3			18.1			16.6			14.7		
30.0	26.1			22.1			18.1			16.6			14.7		
32.0	25.6			21.9			18.1			16.4			14.7		
34.0				21.7			18.1			16.3			14.7		
36.0		19.2		21.6	17.1/37m		18.1			16.1			14.6		
38.0		18.2		21.4	16.7		18.1			16.0			14.5		
40.0		17.6			16.0		18.1	14.9		15.8			14.3		
42.0		16.9			15.4		18.1	14.2		15.7	12.8/43m		14.2		
44.0					14.9		18.1	13.6		15.6	12.5		14.1		
46.0			12.9/47m		14.4			13.1		15.5	11.9		13.9	11.1	
48.0			12.7		14.0	11.3/49m		12.7		15.4	11.4		13.8	10.6	
50.0			12.2			11.1		12.2		15.4	10.9		13.7	10.2	
52.0						10.6		12.0	9.4/53m		10.5		13.7	9.7	
54.0						10.2		11.7	9.2		10.1		13.6	9.3	
56.0									8.8		9.8	7.8		8.9	
58.0									8.5		9.6	7.4		8.6	
60.0									8.2			7.1		8.4	6.3
62.0									7.9			6.7		8.2	6.0
64.0												6.5		8.1	5.7
66.0												6.2		7.9	5.4
68.0															5.2
70.0															5.0
72.0															4.7
74.0															
(°)	24~60	24~47	22~36	21~68	22~54	29~44	19~69	20~55	18~45	18~69	25~56	24~47	24~70	17~56	16~47
索数	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83
DSコード	32043	32043	32043	32044	32044	32044	32045	32045	32045	32046	32046	32046	32047	32047	32047



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 100t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 20.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	24.0			27.0			30.0			33.0			36.0			39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
12.0	116.0/13m			109/13m			100.0/13m			89.9/13m								
14.0	114.0			107.0			98.5			89.2			78.5			71.0/15m		
16.0	110.0			104.0			96.0			87.9			77.5			70.9		
18.0	103.0			100.0			94.0			86.5			77.0			70.6		
20.0	92.5	87.5		91.3			92.0			84.8			77.0			70.3		
22.0	81.5	76.0		81.5	75.9		81.0	75.5		80.9	70.5/23m		76.5			69.7		
24.0	72.0	67.0		71.7	66.7		71.0	66.5		71.1	65.9		71.0	66.0		68.9		
26.0		59.5	56.5	63.9	59.4		63.5	59.0		63.3	58.6		63.5	59.0		63.1	58.4	
28.0		54.0	51.0	57.6	53.5	50.3	57.0	53.0	50.0	56.9	52.7		57.0	53.0		56.7	52.4	
30.0			46.0	48.5	45.7		52.0	48.0	45.5	51.6	47.7	44.8	51.5	48.0		51.4	47.5	
32.0			42.0		44.4	41.7		44.0	41.5	47.2	43.6	40.9	47.5	43.5	41.0	47.0	43.3	38.9/33m
34.0						38.4		40.5	38.0	43.5	40.1	37.5	43.5	40.0	37.5	43.2	39.8	37.2
36.0						35.6			35.0		37.0	34.6	40.0	37.0	35.0	39.9	36.7	34.3
38.0									32.5		34.4	32.1		34.5	32.5	37.0	34.0	31.8
40.0												29.9		32.0	30.0	34.6	31.7	29.5
42.0												29.0/41m			28.3		29.6	27.6
44.0															26.6		27.8	25.8
46.0																		24.3
48.0																		23.6/47m
(°)	29~67	30~59	25~50	22~69	23~58	16~50	26~71	26~61	22~55	20~73	20~62	21~54	23~73	24~63	20~53	18~73	19~62	19~55
条数	9	7	5	9	6	4	8	6	4	7	6	4	6	5	3	6	5	3
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02
DSコード	33030	33030	33030	33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045	33045

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	42.0			45.0			48.0			51.0			54.0			60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	63.5			57.8			52.0/17m											
18.0	63.5			57.8			52.0			48.1			44.0/19m					
20.0	63.0			57.7			52.0			48.1			44.0			37.0		
22.0	63.0			57.6			52.0			48.1			44.0			37.0		
24.0	62.5			57.5			52.0			48.1			44.0			37.0		
26.0	62.0	55.0/27m		57.0			51.5			48.1			44.0			37.0		
28.0	56.5	52.0		56.2	51.7		51.0			47.5			44.0			37.0		
30.0	51.0	47.5		50.8	46.8		50.5	47.0		46.8	44.0/31m		44.0			37.0		
32.0	46.5	43.0		46.4	42.6		46.5	42.5		45.8	41.9		43.5	42.0		37.0		
34.0	43.0	39.5	35.5/35m	42.5	39.1		42.5	39.0		41.9	38.4		42.0	38.5		37.0	35.0/35m	
36.0	39.5	36.5	34.0	39.2	36.0	32.3/37m	39.0	36.0		38.6	35.3		38.5	35.5		37.0	35.0	
38.0	37.0	34.0	31.5	36.4	33.3	31.0	36.5	33.5	30.0/39m	35.7	32.6		36.0	33.0		36.0	33.0	
40.0	34.5	31.5	29.6	33.8	31.0	28.8	34.0	31.0	29.1	33.2	30.2	28.0	33.5	30.5		33.5	30.5	
42.0	32.0	29.7	27.7	31.6	28.9	26.8	31.5	29.1	27.1	30.9	28.1	26.0	31.0	28.6	26.5	31.0	28.7	
44.0		27.8	25.9	29.6	27.0	25.1	29.8	27.2	25.3	28.9	26.3	24.3	29.3	26.7	24.8	29.4	26.8	24.1/45m
46.0		26.2	24.4	28.8/45m	25.4	23.5	28.0	25.6	23.8	27.2	24.6	22.7	27.5	25.0	23.2	27.6	25.2	23.3
48.0			23.0		23.9	22.1	26.5	24.1	22.4	25.6	23.1	21.3	25.9	23.5	21.8	26.0	23.6	21.9
50.0			21.7		23.2/49m	20.8		22.8	21.1	24.1	21.8	20.0	24.4	22.2	20.5	24.5	22.3	20.6
54.0						19.2/53m			18.9		19.5	17.8	22.0	19.9	18.3	22.0	19.9	18.3
58.0												16.0		18.0	16.5	19.9	17.9	16.4
62.0															15.3/61m		16.2	14.9
66.0																		13.5
(°)	22~73	22~62	18~54	21~74	21~63	18~54	20~74	27~62	24~54	23~73	23~63	20~55	19~73	19~63	19~54	23~74	24~63	22~55
条数	5	5	3	5	4	3	4	4	3	4	4	3	4	4	2	3	3	2
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036	33036

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	66.0			72.0			78.0*			84.0*			90.0*			96.0#		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
22.0	30.0																	
24.0	30.0			25.9														
26.0	29.9			25.8			21.7			17.6/27m								
28.0	29.7			25.7			21.5			17.5			14.0/29m					
30.0	29.5			25.7			21.3			17.4			13.8			11.1/31m		
32.0	29.2			25.6			21.2			17.2			13.6			10.9		
34.0	29.0			25.6			21.0			17.0			13.3			10.6		
36.0	28.7			25.6			20.8			16.8			13.1			10.4		
38.0	28.5	29.6		25.6			20.6			16.6			12.8			10.1		
40.0	28.2	29.3		25.5	25.2		20.3			16.3			12.6			9.8		
42.0	28.0	28.0		25.4	25.2		20.1		20.5/43m	16.0			12.3			9.6		
44.0	27.7	26.1		25.3	25.2		19.9	20.3		15.7			12.1			9.3		
46.0	26.9	24.4		25.2	23.9		19.6	20.1		15.4	16.0		11.9			9.1		
48.0	25.3	22.9	20.4/49m	24.8	22.4		19.3	19.8		15.1	15.7		11.6	12.0/49m		8.9		
50.0	23.8	21.5	19.8	23.3	21.0	18.1/52m	19.1	19.6		14.8	15.4		11.4	11.9		8.7	9.0/51m	
54.0	21.2	19.1	17.5	20.7	18.6	17.0	18.5	18.8	16.2/56m	14.2	14.7		11.0	11.4		8.3	8.7	
58.0	19.1	17.1	15.6	18.6	17.6	16.0	17.9	16.8	15.3	13.6	14.1	14.6/59m	10.5	11.0		7.9	8.4	
62.0	17.3	15.4	14.0	16.7	14.9	13.3	16.9	15.1	13.6	12.9	13.6	13.4	10.1	10.6	11.1/63m	7.6	8.0	
66.0	15.9/65m	14.0	12.6	15.2	13.4	11.9	15.3	13.6	12.1	12.4	13.0	11.9	9.8	10.2	10.8	7.3	7.6	8.1
70.0		12.8	11.4	13.6	12.1	10.7	13.9	12.3	10.8	11.9	12.1	10.7	9.4	9.8	10.3	7.0	7.3	7.6
74.0			10.6/73m		11.0	9.6	12.6	11.1	9.7	11.5	10.9	9.5	9.1	9.4	9.8	6.7	7.0	7.1
78.0					8.7	10.1/77m		10.0	8.7	11.1	9.9	8.5	8.8	9.1	8.8	6.4	6.7	6.7
82.0							9.4/81m		7.9	8.8	9.0	7.7	8.5	8.8	7.9	6.1	6.4	6.3
84.0								7.5			8.6	7.3	8.2	8.6	7.5	6.0	6.3	6.2
86.0											8.2	6.9	7.9	8.3	7.1	5.8	6.1	6.0
90.0												6.3	6.8/88m	7.5	6.3	5.6	5.8	5.8
92.0														7.1	6.0	5.3	5.6	5.6
94.0															5.7	5.0	5.5	5.4
96.0															5.4		5.4	5.1
98.0			</															

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 100t  
アウトドラ 12.2 x 12.0m

主ジブ長さ+アダプタ長さ 25.5m+4.0m

単位:t

作業半径 (m)	補ジブ長さ(m) 24.0			補ジブ長さ(m) 27.0			補ジブ長さ(m) 30.0			補ジブ長さ(m) 33.0			補ジブ長さ(m) 36.0			補ジブ長さ(m) 39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
14.0	111.0			101.0			92.5			83.6			76.0/15m					
16.0	106.0			99.0			91.5			83.0			76.0				67.5	
18.0	99.5			95.0			89.0			82.3			76.0				67.5	
20.0	91.5			89.9			86.0			81.3			76.0				67.5	
22.0	80.5	73.5		80.3			80.0			79.1			75.5				67.5	
24.0	70.5	64.5		70.6	64.2		70.0	64.0		69.9	59.8/25m		70.0				66.4	
26.0		57.5		62.9	57.1		62.5	57.0		62.2	56.3		62.5	56.5			62.1	
28.0		52.0	45.5/29m	56.7	51.4		56.0	51.0		55.9	50.5		56.0	51.0			55.8 50.3	
30.0		47.0	43.5	54.1/29m	46.6	41.1/31m	51.0	46.5	41.0/39m	50.7	45.8		51.0	46.0			50.6 45.5	
32.0			40.0	42.6	39.2		42.5	39.0	46.4	41.8		36.7/33m	46.5	42.0			46.1 41.5	
34.0			36.5	39.2	36.0		39.0	35.5	42.7	38.3	35.1		42.5	38.5	35.5		42.4 38.1	
36.0					33.3		36.0	33.0	41.1/35m	35.4	32.4		39.5	35.5	32.5		39.1 35.1 32.0	
38.0						31.0			30.5		32.9	30.0		33.0	30.0		36.3 32.5 29.6	
40.0									28.8		30.6	27.9		31.0	28.3		33.9 30.2 27.5	
42.0												26.1		29.0	26.5	32.8/41m	28.2 25.7	
44.0												24.5			24.8		26.5 24.0	
46.0															23.4		24.9 22.5	
48.0																	21.2	
50.0																	20.7/49m	
(°)	32~66	27~57	26~47	19~68	19~56	17~47	29~71	24~60	23~52	17~73	17~61	16~52	26~72	22~62	20~54	16~72	16~61 20~53	
素数	9	6	4	8	5	4	8	5	4	7	5	3	6	5	3	6	4 3	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03 03	
DSコード	33030	33030	33030	33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045 33045	

単位:t

作業半径 (m)	補ジブ長さ(m) 42.0			補ジブ長さ(m) 45.0			補ジブ長さ(m) 48.0			補ジブ長さ(m) 51.0			補ジブ長さ(m) 54.0			補ジブ長さ(m) 60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	60.5/17m			54.2/17m			49.0			45.0/19m								
18.0	60.5			54.2			49.0			45.0			41.0				36.0/21m	
20.0	60.5			54.2			49.0			45.0			41.0				36.0	
22.0	60.5			54.2			49.0			45.0			41.0				36.0	
24.0	60.0			54.2			49.0			45.0			41.0				36.0	
26.0	59.5			54.0			49.0			45.0			41.0				36.0	
28.0	55.5	48.0/29m		53.8			49.0			44.9			41.0				36.0	
30.0	50.5	45.5		49.9	44.8		49.0			44.8			41.0				36.0	
32.0	46.0	41.5		45.5	40.8		45.5	41.0		44.6	38.3/33m		41.0				36.0	
34.0	42.0	38.0		41.7	37.3		41.5	37.5		41.1	36.6		41.0	37.0			36.0	
36.0	39.0	35.0		38.5	34.4		38.5	34.5		37.9	33.6		38.0	34.0			36.0 33.0/37m	
38.0	36.0	32.5	29.8	35.7	31.8	27.8/39m	35.5	32.0		35.0	31.0		35.0	31.5			35.5 31.5	
40.0	33.5	30.0	27.7	33.2	29.5	26.7	33.0	29.8		32.5	28.8		32.5	29.2			33.0 29.4	
42.0	31.5	28.3	25.8	31.0	27.5	24.9	31.0	27.7	25.2	30.3	26.7	23.2/43m	30.5	27.2			30.5 27.4	
44.0		26.5	24.1	29.0	25.7	23.2	29.2	25.9	23.5	28.3	24.9	22.4	28.7	25.4	22.2/45m		28.8 25.6	
46.0		25.0	22.7	27.3	24.1	21.7	27.4	24.3	22.0	26.6	23.3	20.9	26.9	23.8	21.4		27.1 23.9	
48.0		23.5	21.3	22.7	20.4	18.2	22.9	20.7	18.5	22.4	19.5	17.3	22.7	19.9	17.8		22.8 20.0 17.9	
50.0			20.1	21.4	19.2	17.2	21.6	19.5	17.4	22.4	20.6	18.4	23.9	21.0	18.9		24.0 21.1 19.0	
52.0							20.5	18.5	16.4	22.4	20.6	18.4	23.9	21.0	18.9		24.0 21.1 19.0	
54.0							19.4	17.4	15.7	22.4	20.6	18.4	23.9	21.0	18.9		24.0 21.1 19.0	
58.0									15.7			17.0/57m	14.5		16.9	15.0	19.4 16.9 15.1	
62.0												13.4/61m			13.5		15.3 13.5	
66.0																	14.0 12.2	
70.0																	11.1	
(°)	24~72	20~62	26~53	19~73	23~62	22~54	22~73	18~61	18~54	18~73	18~62	17~54	21~73	24~62	23~53	25~74	16~62 16~54	
素数	5	4	3	5	4	3	4	4	2	4	3	2	4	3	2	3	3 2	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03 03	
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036 33036	

単位:t

作業半径 (m)	補ジブ長さ(m) 66.0			補ジブ長さ(m) 72.0			補ジブ長さ(m) 78.0			補ジブ長さ(m) 84.0 #			補ジブ長さ(m) 90.0 #			補ジブ長さ(m) 96.0 #		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
22.0	28.0/23m																	
24.0	28.0			24.0/25m														
26.0	28.0			24.0			21.0											
28.0	28.0			24.0			21.0			17.0								
30.0	28.0			24.0			21.0			16.9			13.5					
32.0	28.0			24.0			21.0			16.9			13.3				10.4	
34.0	28.0			24.0			21.0			16.8			13.1				10.3	
36.0	27.9			24.0			21.0			16.7			12.9				10.1	
38.0	27.9			24.0			21.0			16.6			12.7				9.9	
40.0	27.8	28.6		24.0			20.8			16.6			12.5				9.7	
42.0	27.7	26.6		24.0	23.5		20.7			16.5			12.3				9.5	
44.0	27.7	24.8		24.0	23.5		20.5	20.9/45m		16.2			12.1				9.3	
46.0	26.4	23.2		24.0	22.6		20.2	20.8		15.9			11.9				9.1	
48.0	24.7	21.7		24.0	21.2		20.0	20.6		15.6	16.4		11.7				9.0	
50.0	23.3	20.4	17.1/52m	22.8	19.8		19.7	20.1		15.3	16.1		11.5	12.0			8.8 9.0/53m	
54.0	20.8	18.1	16.0	20.2	17.5	14.8/55m	19.2	17.8		14.7	15.4		11.1	11.6			8.4 8.9	
58.0	18.6	16.1	14.1	18.1	15.6	13.4	18.4	15.8	13.3/59m	14.1	14.8		10.7	11.1			8.0 8.5	
62.0	16.8	14.5	12.5	16.3	13.9	11.8	16.5	14.2	12.1	13.6	14.0	11.9	10.3	10.7	11.0/65m		7.6 8.1	
66.0	15.4	13.1	11.2	14.8	12.4	10.5	14.9	12.6	10.7	13.2	12.5	10.5	9.9	10.4	10.8		7.2 7.7 7.9/69m	
70.0		11.9	10.0	13.4	11.2	9.3	13.6	11.3	9.5	12.7	11.2	9.3	9.5	10.0	9.6		6.9 7.3 7.8	
74.0			9.1		10.1	8.3	12.4	10.2	8.4	12.3	10.0	8.3	9.1	9.6	8.5		6.5 7.0 7.4	
78.0					9.4/77m	7.5	9.9	9.2	7.5	11.2	9.0	7.3	8.8	9.3	7.6		6.2 6.7 7.0	
82.0						7.0/81m		8.3	6.7	9.3	8.1	6.5	8.5	8.3	6.7		5.9 6.3 6.5	
86.0									6.1		7.4	5.8	8.2	7.5	6.0		5.6 6.0 5.7	
90.0											6.9/89m	5.2	6.6/89m	6.8	5.3		5.3 5.7 5.0	
92.0												5.0		6.5	5.0		5.2 5.6 4.7	
94.0														6.1	4.7		5.4 4.4	
98.0															4.2		5.2 3.9	
100.0																	5.0 3.7	
102.0																	3.4	
104.0																	3.2	
(°)	19~73	21~62	21~53	23~73	18~63	17~54	19~73	20~63	19~54	21~73	16~62	18~54	18~73	18~63	18~54	20~73	18~63 17~54	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 100t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 30.5m+4.0m

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	24.0			27.0			30.0			33.0			36.0			39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
14.0	96.5/15m			88.4/15m			80.5/15m			70.5/15m								
16.0	93.0			87.0			80.5			70.2			62.0					55.5/17m
18.0	87.0			83.5			78.5			69.6			62.0					55.5
20.0	81.5			79.3			76.0			69.1			62.0					55.5
22.0	77.0			74.9			72.5			67.1			61.5					55.5
24.0	70.0	62.0		69.8			68.5	58.0/25m		64.8			60.5					55.1
26.0	62.5	56.0		62.1	55.4		61.5	55.0		61.4	51.8/27m		59.0					54.2
28.0		50.5		55.9	49.8		55.5	49.5		55.2	49.0		55.5	49.0				53.4
30.0		45.5	40.0/31m	50.8	45.2		50.5	45.0		50.1	44.3		50.0	44.5				49.9
32.0		41.5	38.0	41.3	38.0	35.8/33m	46.0	41.0	35.5/33m	45.7	40.4		46.0	40.5				45.5
34.0			35.0	37.9	34.3		37.5	34.0		42.0	37.1	32.0/35m	42.0	37.5				41.8
36.0			32.5	35.1	31.6		34.5	31.5		38.9	34.2	30.7	39.0	34.5	30.0/37m			38.6
38.0					29.4		32.5	29.3		31.7	28.4	36.0	32.0	28.9	35.8	31.4	27.0	37.0/39m
40.0					27.4			27.3		29.5	26.4		29.9	26.9	33.4	29.2	26.0	
42.0								25.5		27.6	24.6		28.0	25.1	31.2	27.2	24.2	
44.0											23.1		26.3	23.5		25.5	22.6	
46.0											21.7			22.1		23.9	21.2	
48.0														20.8		22.6	20.0	
50.0																	18.8	
(°)	25~64	24~56	26~47	16~68	15~55	18~47	22~70	21~61	23~53	15~72	13~60	16~52	20~72	19~61	21~52	13~72	12~60	24~52
索数	8	5	3	7	5	3	7	5	3	6	4	3	5	4	3	5	4	2
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	33030	33030	33030	33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045	33045

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	42.0			45.0			48.0			51.0			54.0			60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	50.0			44.6			40.0/19m			36.9			33.5/21m					
20.0	50.0			44.6			40.0			36.9			33.5			30.0		
22.0	50.0			44.6			40.0			36.9			33.5			30.0		
24.0	50.0			44.6			40.0			36.9			33.5			30.0		
26.0	49.5			44.6			40.0			36.9			33.5			30.0		
28.0	49.0			44.4			40.0			36.9			33.5			30.0		
30.0	49.0	42.0/31m		44.3			40.0			36.9			33.5			30.0		
32.0	45.5	40.0		44.1	39.4		40.0			36.9			33.5			30.0		
34.0	41.5	36.5		41.2	36.0		40.0	36.0		36.9	33.8/35m		33.5			30.0		
36.0	38.5	34.0		37.9	33.2		38.0	33.0		36.9	32.4		33.5	32.5		30.0		
38.0	35.5	31.5		35.1	30.6		35.0	30.5		34.5	29.9		33.5	30.0		30.0	28.1/39m	
40.0	33.0	29.3	26.2	32.7	28.4		32.5	28.7		32.0	27.6		32.0	28.1		30.0	27.9	
42.0	31.0	27.3	24.4	30.5	26.5	23.4	30.5	26.7		29.8	25.7		30.0	26.2		30.0	26.3	
44.0	29.3	25.6	22.8	28.5	24.7	21.8	28.7	25.0	22.2	27.8	23.9	20.3/45m	28.2	24.4		28.4	24.6	
46.0		24.0	21.4	26.8	23.2	20.4	27.0	23.4	20.8	26.1	22.4	19.5	26.4	22.8	19.5/47m	26.6	23.0	
48.0		22.6	20.1	26.1/47m	21.8	19.1	25.4	22.0	19.5	24.5	21.0	18.2	24.9	21.4	18.8	25.0	21.6	
50.0		21.4	19.0		20.5	18.0	24.1	20.8	18.3	23.1	19.7	17.0	23.5	20.2	17.6	23.6	20.3	17.8
54.0			17.0		18.9/53m	15.9		18.6	16.3	21.4/53m	17.5	14.9	21.1	18.0	15.5	21.1	18.1	15.6
58.0					14.3				14.6		15.7	13.2		16.1	13.8	19.0	16.2	13.9
62.0											11.8			14.7	12.3	17.7/61m	14.6	12.4
66.0															11.2		13.3	11.1
70.0																		10.0
(°)	18~72	17~61	19~53	18~73	17~61	14~53	17~73	16~61	12~53	16~73	15~61	12~54	23~73	15~62	17~53	19~73	16~62	12~54
索数	4	4	2	4	3	2	3	3	2	3	3	2	3	3	2	3	3	2
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036	33036

単位:t

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)					
	66.0			72.0*			78.0*			84.0*			90.0#			96.0#		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
24.0	23.3																	
26.0	23.3			20.2			17.6/27m											
28.0	23.3			20.2			17.6			14.2/29m								
30.0	23.3			20.2			17.6						11.6/31m					
32.0	23.3			20.2			17.6			14.2			11.6					9.0
34.0	23.3			20.2			17.6			14.2			11.4					8.9
36.0	23.3			20.2			17.6			14.1			11.3					8.8
38.0	23.2			20.2			17.6			14.1			11.2					8.6
40.0	23.2			20.2			17.5			14.1			11.1					8.5
42.0	23.2	25.6		20.2			17.5			14.0			10.9					8.3
44.0	23.1	23.8		20.2	19.7		17.4			13.9			10.8					8.2
46.0	23.1	22.2		20.2	19.7		17.3	17.2/47m		13.8			10.7					8.0
48.0	23.0	20.8		20.2	19.6		17.2	17.2		13.7			10.5					7.9
50.0	22.9	19.5		20.2	19.0		17.1	17.1		13.6	13.7		10.4	10.6/53m				7.7
54.0	20.4	17.3	14.7	19.9	16.7		16.8	16.9		13.3	13.4		10.1	10.6			7.4	7.8/55m
58.0	18.3	15.4	12.9	17.7	14.8	12.2	16.6	15.1	11.3/61m	13.0	13.1		9.8	10.3			7.1	7.6
62.0	16.5	13.7	11.4	15.9	13.1	10.7	16.2	13.4	10.9	12.7	12.9	9.8/65m	9.5	10.0			6.8	7.2
66.0	15.0	12.3	10.1	14.4	11.6	9.4	14.6	11.9	9.6	12.4	11.7	9.4	9.3	9.7	9.2/68m		6.5	6.9
70.0		11.1	9.0	13.1	10.4	8.3	13.3	10.6	8.5	12.1	10.5	8.3	9.0	9.4	8.6	6.2	6.6	7.0/72m
74.0		10.4/73m	8.1	11.8/73m	9.3	7.3	12.1	9.5	7.5	11.8	9.3	7.3	8.7	9.1	7.6	5.9	6.3	6.8
78.0			7.3		8.5	6.5	10.4	8.5	6.6	10.9	8.4	6.4	8.4	8.6	6.7	5.6	6.0	6.4
82.0					5.8			7.7	5.8	9.7	7.5	5.6	8.1	7.7	5.9	5.4	5.8	5.6
86.0								7.2/85m	5.2	8.2/84m	6.7	5.0	7.9	6.9	5.2	5.1	5.5	4.9
90.0									4.8		6.1	4.4	6.3	6.2	4.5	5.0	5.3	4.2
94.0												3.9		5.6	4.0	4.8	5.1	3.7
96.0														5.3	3.7	4.5	4.9	3.5
98.0															3.4	4.7	3.2	3.2
102.0															3.1	4.2	2.7	2.7
106.0																		2.3
(°)	20~73	17~61	15~54	17~73	19~62	20~53	19~73	16~62	17~54	18~73	18~62	19~53	17~73	17~62	16~54	17~73	16~62	17~53
索数	2	2</																



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 35.5m+4.0m

作業半径 (m)	補ジブ長さ(m) 24.0			補ジブ長さ(m) 27.0			補ジブ長さ(m) 30.0			補ジブ長さ(m) 33.0			補ジブ長さ(m) 36.0			補ジブ長さ(m) 39.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
16.0	81.5			73.2/17m			67.5			60.2			54.5/17m					
18.0	77.0			72.1			66.5			59.9			54.5				49.3	
20.0	72.5			69.2			65.0			59.5			54.5				49.3	
22.0	68.0			66.0			62.5			58.8			54.5				49.3	
24.0	64.5			62.7			60.0			56.8			53.5				49.3	
26.0	61.5	50.5		59.7			57.5	46.5/27m		55.1			52.5				48.7	
28.0		48.0		55.2	46.6		55.0	45.5		53.7	43.4/29m		51.0				48.0	
30.0		44.5		50.1	43.8		49.5	43.0		49.4	42.2		49.5	41.5			47.4	
32.0		40.5		39.9			45.5	39.5		45.1	39.1		45.0	39.5			44.9	38.8
34.0			33.0	36.7			36.5			41.4	35.8		41.5	36.0			41.2	35.5
36.0			30.5	33.9	30.0		33.5	30.0		38.3	33.0		38.5	33.5			38.0	32.7
38.0			28.7	31.5	27.8		31.0	27.8		30.5	26.8		35.5	31.0	26.4/39m		35.3	30.3
40.0					25.9			25.8		28.4	24.9		28.9	25.5			32.8	28.1
42.0					24.2			24.1		26.6	23.2		27.0	23.7			30.7	26.2
44.0								22.6		25.0	21.7		25.3	22.2			24.5	21.3
46.0											20.3			20.8			23.0	19.9
48.0											19.2			19.6			21.7	18.7
50.0														18.5			20.5	17.5
52.0																		16.6
54.0																		15.6
(°)	28~63	32~54	27~44	21~64	8~53	19~45	25~69	28~60	24~50	19~71	7~59	17~50	23~71	26~60	22~52	17~71	6~59	16~52
索数	7	4	3	6	4	3	6	4	3	5	4	2	5	4	2	4	3	2
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	33030	33030	33030	33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045	33045

作業半径 (m)	補ジブ長さ(m) 42.0			補ジブ長さ(m) 45.0			補ジブ長さ(m) 48.0			補ジブ長さ(m) 51.0			補ジブ長さ(m) 54.0			補ジブ長さ(m) 60.0		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
18.0	45.0/19m			39.8/19m			35.5			32.8/21m								
20.0	45.0			39.8			35.5			32.8			30.0				27.0/23m	
22.0	45.0			39.8			35.5			32.8			30.0				27.0	
24.0	45.0			39.8			35.5			32.8			30.0				27.0	
26.0	45.0			39.8			35.5			32.8			30.0				27.0	
28.0	44.5			39.8			35.5			32.8			30.0				27.0	
30.0	44.5			39.7			35.5			32.8			30.0				27.0	
32.0	44.0	37.0/33m		39.6			35.5			32.8			30.0				27.0	
34.0	41.0	35.5		39.5	34.8		35.5			32.8			30.0				27.0	
36.0	38.0	32.5		37.4	31.9		35.5	32.0		32.8	29.9/37m		30.0				27.0	
38.0	35.0	30.0		34.6	29.5		34.5	29.8		32.8	28.7		30.0	29.2			27.0	
40.0	32.5	28.2		32.1	27.3		32.0	27.6		31.5	26.5		30.0	27.0			27.0	24.9/41m
42.0	30.5	26.3	22.3/43m	30.0	25.4		30.0	25.7		29.3	24.6		29.7	25.1			27.0	24.6
44.0	28.8	24.6	21.5	28.1	23.7	19.7/45m	28.2	24.0		27.4	22.9		27.7	23.4			27.0	23.6
46.0		23.1	20.1	26.4	22.2	19.0	26.5	22.5	19.4	25.6	21.4		26.0	21.9			26.2	22.1
48.0		21.8	18.9	24.9	20.8	17.7	25.0	21.1	18.1	24.1	20.0	16.7	24.4	20.5			24.6	20.7
50.0		20.5	17.7		19.6	16.5	23.6	19.9	17.0	22.7	18.8	15.5	23.0	19.3	16.2		23.2	19.5
54.0			15.8		17.5	14.6		17.8	15.0	20.3	16.7	13.5	20.6	17.1	14.2		20.7	17.3
58.0					13.0			13.3	12.0	14.9	11.9		15.4	12.5	10.0		18.7	15.4
62.0									12.0			10.5	13.9	11.2	17.0		13.9	11.2
66.0												9.5		10.0			12.5	10.0
70.0																		9.0
74.0																		8.1
(°)	21~71	23~60	27~52	16~72	19~61	23~51	19~72	28~60	18~53	15~72	24~61	13~52	24~72	21~61	24~52	17~73	25~61	16~53
索数	4	3	2	3	3	2	3	3	2	3	3	2	3	3	2	2	2	2
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036	33036

作業半径 (m)	補ジブ長さ(m) 66.0			補ジブ長さ(m) 72.0 *			補ジブ長さ(m) 78.0 *			補ジブ長さ(m) 84.0 #			補ジブ長さ(m) 90.0 #			補ジブ長さ(m) 96.0 #		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65
24.0	21.0/25m																	
26.0	21.0			18.5/27m														
28.0	21.0			18.5			16.0											
30.0	21.0			18.5			16.0			13.0								
32.0	21.0			18.5			16.0			13.0			11.0					
34.0	21.0			18.5			16.0			13.0			10.9				8.5	
36.0	21.0			18.5			16.0			13.0			10.9				8.4	
38.0	21.0			18.5			16.0			13.0			10.8				8.3	
40.0	21.0			18.5			16.0			13.0			10.8				8.1	
42.0	21.0			18.5			16.0			13.0			10.7				8.0	
44.0	21.0	22.8		18.5			16.0			13.0			10.6				7.9	
46.0	21.0	21.3		18.5	18.0		16.0			13.0			10.5				7.8	
48.0	21.0	19.9		18.5	18.0		16.0	15.3/49m		13.0			10.5				7.6	
50.0	21.0	18.6		18.5	17.9		16.0	15.3		13.0	12.5/52m		10.4				7.5	
54.0	20.0	16.5	12.1/57m	18.5	15.8		16.0	15.3		13.0	12.5		10.2	10.5/55m			7.2	7.5/57m
58.0	17.9	14.5	11.7	17.4	13.9	9.9/61m	16.0	14.2		13.0	12.5		10.0	10.3			6.9	7.4
62.0	16.2	12.9	10.2	15.6	12.2	9.5	15.9	12.5	9.2/64m	13.0	12.5		9.8	10.1			6.6	7.1
66.0	14.7	11.5	9.0	14.1	10.8	8.3	14.3	11.1	8.5	12.8	11.0	7.8/68m	9.6	9.9			6.3	6.8
70.0		10.4	8.0	12.8	9.6	7.2	13.0	9.9	7.5	12.5	9.7	7.3	9.3	9.7	7.4/71m		6.1	6.5
74.0		9.4	7.1	11.3	8.6	6.3	11.8	8.8	6.5	11.7	8.6	6.3	9.1	9.0	6.6	5.8	6.2	6.1/75m
78.0			6.3		7.7	5.5	10.8	7.9	5.7	10.6	7.7	5.5	8.9	8.0	5.8	5.6	6.0	5.5
82.0					4.9			7.1	5.0	9.7	6.9	4.8	8.6	7.1	5.0	5.4	5.8	4.7
86.0					4.4			6.4	4.3	7.8/85m	6.1	4.1	8.4	6.4	4.4	5.2	5.6	4.1
90.0									3.8		5.5	3.6	6.5	5.7	3.7	5.1	5.4	3.5
94.0												3.1		5.0	3.2	5.0	4.8	2.9
98.0												2.7		4.5	2.7	4.1/97m	4.2	2.4
102.0															2.3		3.7	2.0
(°)	22~73	18~61	21~53	16~72	22~62	15~52	20~73	17~62	20~53	17~73	21~62	14~53	19~73	16~61	18~53	16~73	19~62	27~53
索数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23
DSコード	33037	33037	33037	33038	33038	33038	33039	33039	33039	33040	33040	33040	33041	33041	33041	33042	33042	33042

補ジブ起伏角度(最小-最大) LKコードジブ伸

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 40.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	24.0			27.0			30.0			33.0			36.0			39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
16.0	65.5/17m			60.4/17m			56.0/17m			48.8/17m									
18.0	65.5			60.3			56.0			48.8			43.0					38.9/19m	
20.0	63.0			60.1			56.0			48.8			43.0					38.9	
22.0	60.0			56.9			55.0			48.8			43.0					38.9	
24.0	56.5			54.2			52.0			47.7			43.0					38.9	
26.0	53.5			51.9			49.5			46.1			42.0					38.8	
28.0		41.5		50.1			47.5	40.0/29m		44.7			41.0					38.4	
30.0		39.0		48.8	38.8		46.0	38.5		43.6	35.5/31m		40.5					38.0	
32.0		37.5			36.9			36.5		42.8	34.6		40.0	32.5				37.7	
34.0		35.5			35.0			34.5		40.9	32.7		39.5	31.0				37.3	30.7
36.0			29.6		33.0			32.5		37.8	31.3		38.0	29.7				36.9	29.5
38.0			27.5		30.6	25.6/39m		30.5	25.6/39m	29.6			35.5	28.3				34.8	28.2
40.0			25.6			24.7		28.4	24.7		23.7			27.5				32.4	27.0
42.0						23.1			23.0		25.7	22.0		26.2	22.7			30.3	25.4
44.0						21.6			21.6		24.1	20.5		24.6	21.2			27.7	23.7
46.0									20.3			19.2		23.1	19.8			25.4	22.2
48.0												18.0			18.6			23.7	20.9
50.0												16.9			17.5			22.2	19.8
52.0																		21.0	18.4
54.0																		20.1	17.5
(°)	31~62	29~52	28~45	24~66	22~52	20~42	28~68	26~59	24~48	22~70	19~58	18~50	25~70	23~59	30~50	20~70	18~58	25~50	25~50
条数	5	4	3	5	3	2	5	3	2	4	3	2	4	3	2	3	3	3	3
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	33030	33030	33030	33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045	33045	33045

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	42.0			45.0			48.0			51.0			54.0			60.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
20.0	35.5			32.1			29.2/21m												
22.0	35.5			32.1			29.2			27.2			25.2/23m						
24.0	35.5			32.1			29.2			27.2			25.2					21.9	
26.0	35.5			32.1			29.2			27.2			25.2					21.9	
28.0	35.5			32.1			29.2			27.2			25.2					21.9	
30.0	35.5			32.1			29.2			27.2			25.2					21.9	
32.0	35.0			32.0			29.2			27.2			25.2					21.9	
34.0	35.0	29.4/35m		32.0			29.2			27.1			25.2					21.9	
36.0	34.5	28.7		31.8	27.3/37m		29.2			27.1			25.1					21.9	
38.0	34.5	27.4		31.7	26.7		29.1	26.2		27.1	24.9/39m		25.1					21.9	
40.0	32.5	26.3		31.4	25.6		29.0	25.1		27.1	24.5		25.1	23.3/41m				21.9	
42.0	30.0	25.2		29.6	24.5		28.8	24.0		27.0	23.6		25.1					21.9	19.9/43m
44.0	28.5	23.9		27.7	22.9		27.9	23.1		26.9	22.1		25.0	22.0				21.9	19.6
46.0		22.4	19.0	26.0	21.4		26.2	21.8		25.2	20.6		25.0	21.1				21.9	19.1
48.0		21.0	17.8	24.5	20.1	16.5	24.6	20.4	16.4/49m	23.7	19.3		24.1	19.8				21.9	18.6
50.0		19.8	16.6		18.9	15.4	23.3	19.2	15.9	22.3	18.1	13.9/51m	22.7	18.6	13.6/53m			21.8	18.1
54.0			14.7		16.8	13.5		17.1	13.9	20.0	15.9	12.4	20.3	16.5	13.1			20.4	16.6
56.0			14.0			12.7		16.3	13.1		15.0	11.6		15.6	12.3			19.4	15.7
58.0			13.2			11.9		15.4	12.3		14.1	10.9		14.6	11.5			18.4	14.8
60.0						11.3			11.7		13.4	10.2		13.9	10.9			17.6	14.0
62.0						10.7			11.0		12.6	9.5		13.1	10.2			16.7	13.2
66.0												8.5			9.1			11.9	9.1
70.0															8.2			10.8	8.1
74.0																		7.3	7.3
(°)	23~70	28~59	20~50	19~72	24~58	15~50	22~72	20~59	26~51	17~72	15~60	22~51	26~72	25~59	18~51	19~72	18~60	23~52	23~52
条数	3	3	2	3	3	2	3	2	2	3	2	2	2	2	2	2	2	2	2
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036	33036	33036

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	66.0 #			72.0 #			78.0 #			84.0 #			90.0 #			96.0 #			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
26.0	17.0																		
28.0	17.0			14.3			12.6/29m												
30.0	17.0			14.3			12.6			10.0/31m									
32.0	17.0			14.3			12.6			10.0			8.3/33m						
34.0	17.0			14.3			12.5			10.0			8.3					6.4/35m	
36.0	17.0			14.3			12.5			10.0			8.3					6.3	
38.0	17.0			14.3			12.4			10.0			8.2					6.2	
40.0	17.0			14.3			12.4			10.0			8.2					6.1	
42.0	17.0			14.3			12.4			10.0			8.2					5.9	
44.0	17.0			14.3			12.4			10.0			8.1					5.8	
46.0	17.0	19.1		14.3			12.4			10.0			8.1					5.7	
48.0	17.0	18.5		14.3	13.7/49m		12.4			10.0			8.1					5.6	
50.0	17.0	17.9		14.3	13.7		12.4	12.6/52m		10.0			8.0					5.5	
54.0	17.0	15.7		14.3	13.5		12.4	12.5		10.0	9.5		8.0					5.3	
58.0	17.0	13.8		14.3	13.1		12.4	12.2		10.0	9.5		7.9	7.8/59m				5.1	
60.0	16.5	13.0	10.0	14.3	12.3		12.4	12.1		10.0	9.5		7.9	7.8				5.0	5.4
62.0	15.9	12.2	9.3	14.3	11.5	8.3/63m	12.3	11.9		10.0	9.5		7.8	7.8					

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 100t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 45.5m+4.0m

作業半径 (m)	補ジブ長さ(m) 24.0			補ジブ長さ(m) 27.0			補ジブ長さ(m) 30.0			補ジブ長さ(m) 33.0			補ジブ長さ(m) 36.0			補ジブ長さ(m) 39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
18.0	52.0/19m			48.4/19m			45.0/19m			40.1									
20.0	51.5			48.3			45.0			40.1			36.0				32.7		
22.0	49.5			47.2			45.0			40.1			36.0				32.7		
24.0	47.0			45.1			43.5			39.9			36.0				32.7		
26.0	44.5			43.3			41.5			38.9			35.5				32.7		
28.0	42.5			41.9			40.0			38.0			35.0				32.6		
30.0				40.8			39.0			37.2			35.0				32.4		
32.0		32.5		40.1	31.3		38.5	30.5		36.6	28.8/33m		34.5				32.3		
34.0		30.5		29.7			37.5	29.0		36.1	28.1		34.0	27.5			32.1		
36.0		29.6		28.5				27.7		35.7	26.8		34.0	26.1			32.0	25.5	
38.0				27.3				26.5		34.7	25.5		33.5	24.8			31.8	24.5	
40.0			22.9/39m	26.6				25.7	20.9/41m		24.6		32.5	23.8			31.6	23.4	
42.0			21.1					24.9	20.4		23.7	19.2/43m		22.9			29.9	22.3	
44.0								19.9			19.6		22.3	18.8		22.3	17.8/45m	28.1	21.7
46.0								19.1			18.8	21.9	17.9		21.8	17.4		21.0	16.6/47m
48.0											18.0		16.8		21.1	16.7		20.2	16.3
50.0													15.7			16.0		19.0	15.3
52.0																15.3			14.4
54.0																14.6			13.4
56.0																			12.7
58.0																			12.0
(°)	24~58	26~44	28~41	15~62	18~50	21~42	21~65	23~55	25~48	13~70	16~57	28~48	19~68	21~58	23~48	12~70	24~57	17~48	
索数	4	3	2	4	3	2	4	3	2	3	3	2	3	3	2	3	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	33030	33030	33030	33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045	33045	33045

作業半径 (m)	補ジブ長さ(m) 42.0			補ジブ長さ(m) 45.0			補ジブ長さ(m) 48.0			補ジブ長さ(m) 51.0			補ジブ長さ(m) 54.0			補ジブ長さ(m) 60.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
20.0	30.0/21m																		
22.0	30.0			27.8			26.0			24.5/23m									
24.0	30.0			27.8			26.0			24.5			23.0						
26.0	30.0			27.8			26.0			24.5			23.0				19.0		
28.0	30.0			27.8			26.0			24.5			23.0				19.0		
30.0	30.0			27.8			26.0			24.5			23.0				19.0		
32.0	30.0			27.8			25.9			24.5			23.0				19.0		
34.0	30.0			27.7			25.9			24.4			23.0				19.0		
36.0	30.0	24.4/37m		27.7			25.8			24.4			23.0				19.0		
38.0	30.0	23.8		27.6	22.6/39m		25.7			24.3			22.9				19.0		
40.0	29.8	22.7		27.5	22.1		25.6	21.7		24.3	20.8/41m		22.9				19.0		
42.0	29.7	21.6		27.4	21.0		25.5	20.6		24.2	20.4		22.9	19.5/43m			19.0		
44.0	28.1	20.8		27.2	20.1		25.3	19.7		24.1	19.6		22.8	19.1			19.0		
46.0	26.4	19.9		25.6	19.2		25.2	18.8		24.0	18.8		22.8	18.2			19.0	16.8	
48.0		19.4	15.7/49m	24.1	18.5		24.3	18.0		23.3	18.0		22.7	17.5			19.0	16.3	
50.0		18.8	15.3	22.8	17.8	14.2	22.9	17.3	13.7/52m	22.0	17.2		22.4	16.7			19.0	15.8	
54.0		17.2	13.7		16.1	12.4		16.2	12.9	19.6	15.1	11.3	20.0	15.5			19.0	14.9	
58.0			12.2		14.4	10.9		14.7	11.3	13.3	9.8	18.1	13.9	10.5			16.4	14.1	10.4/59m
62.0						9.7			10.1	11.9	8.5		12.4	9.3			12.5	9.4	
66.0									9.1		7.5		11.2	8.2			11.2	8.3	
70.0											6.7			7.3			10.1	7.3	
74.0																		6.5	
78.0																			5.9
(°)	17~70	19~58	28~48	11~70	14~57	24~50	24~71	25~58	19~50	20~71	21~59	15~50	15~71	17~59	24~50	21~71	22~59	17~51	
索数	3	2	2	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036	33036	33036

作業半径 (m)	補ジブ長さ(m) 66.0 #			補ジブ長さ(m) 72.0 #			補ジブ長さ(m) 78.0 #			補ジブ長さ(m) 84.0 #			補ジブ長さ(m) 90.0 #			補ジブ長さ(m) 96.0 #			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
26.0	14.7/27m																		
28.0	14.7			11.5/29m															
30.0	14.7			11.5			10.6												
32.0	14.7			11.5			10.5			8.0/33m									
34.0	14.7			11.5			10.4			8.0			6.5/35m						
36.0	14.7			11.5			10.3			8.0			6.5				4.9		
38.0	14.7			11.5			10.2			8.0			6.5				4.8		
40.0	14.7			11.5			10.2			8.0			6.5				4.6		
42.0	14.7			11.5			10.1			8.0			6.5				4.5		
44.0	14.7			11.5			10.0			8.0			6.5				4.4		
46.0	14.7			11.5			10.0			8.0			6.5				4.3		
48.0	14.7			11.5			10.0			8.0			6.5				4.2		
50.0	14.7	15.2/49m		11.5			10.0			8.0			6.5				4.2		
54.0	14.7	14.9		11.5	11.0/51m		10.0			8.0			6.5				4.1		
58.0	14.7	13.8		11.5	10.8		10.0	11.3		8.0	7.5/56m		6.5				3.9		
62.0	14.7	12.9		11.5	10.6		10.0	10.7		8.0	7.5		6.5				3.8		
66.0	14.7	11.6	8.1/63m	11.5	10.3		10.0	10.1		8.0	7.5		6.5	6.0			3.7	4.0	
70.0	14.1	10.2	7.2	11.5	9.5	6.5	10.0	9.5	5.5/69m	8.0	7.5		6.5	6.0			3.6	3.9	
74.0	12.9	9.1	6.3	11.5	8.4	5.5	10.0	8.7	5.4	8.0	7.5		6.5	6.0			3.5	3.8	
78.0		8.2	5.4	11.1	7.4	4.7	10.0	7.7	4.8	8.0	7.5	4.7	6.5	6.0	4.5/77m		3.5	3.7	
82.0		7.4	4.7		6.6	4.0	10.0	6.8	4.2	8.0	6.6	4.0	6.5	5.9	4.3		3.4	3.6	
86.0			4.1		5.9	3.3	7.8	6.0	3.5	8.0	5.8	3.3	6.5	5.8	3.6		3.4	3.5	
90.0						2.8		5.3	2.9	7.6	5.1	2.7	6.5	5.4	3.0		3.3	3.4	
94.0						2.4		4.8	2.4		4.5	2.2	6.5	4.8	2.5		3.3	3.4	
98.0									2.0		4.0		4.2	4.2	2.0		3.2	3.3	
102.0														3.6			3.0	3.2	
106.0															3.3/101m			2.9	
(°)	14~72	15~59	22~51	19~72	20~60	16~51	13~72	14~60	20~52	17~72	18~61	35~52	12~72	15~58	36~52	16~72	17~61		
索数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	33037	33037	33037	33038	33038	33038	33039	33039	33039	33040	33040	33040	33041	33041	33041	33041	33042		

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 100t  
アウドリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 50.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	24.0			27.0			30.0			33.0			36.0			39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
18.0	38.0/19m						33.0/19m			29.9/19m									
20.0	36.0			35.0			32.5			29.7			26.6					24.1/21m	
22.0	37.5			34.2			31.5			29.2			26.6					24.1	
24.0	36.5			33.9			31.0			28.7			26.6					24.1	
26.0	36.0			33.6			31.0			28.6			26.6					24.1	
28.0	35.0			33.3			31.0			28.5			26.4					24.1	
30.0				32.7			31.0			28.4			26.2					24.1	
32.0		26.9		32.2			30.5			28.2			26.1					24.0	
34.0		25.5			25.0		30.0	24.6		28.0	22.5/35m		25.9					23.9	
36.0		24.4			23.8			23.5		27.8	22.0		25.8	20.2/37m				23.8	
38.0		23.4			22.7			22.4		27.5	20.9		25.7	19.7				23.8	19.2
40.0					22.0			21.5			20.1		25.6	18.9				23.7	18.3
42.0					21.2			20.6			19.2			18.1				23.6	17.4
44.0						17.3		20.0	17.0		18.7			17.5				23.5	16.8
46.0					16.5				16.0	18.1	15.0			16.9					16.1
48.0					15.8				15.3	17.8	14.3			16.6	13.4				15.7
50.0									14.5		13.6			16.3	12.8				15.2
52.0											13.1				12.3				15.0
54.0											12.7				11.9				14.8
56.0																			11.0
58.0																			10.6
(°)	27~60	23~49		20~61	13~49	21~39	24~67	20~54	25~46	18~69	12~55	19~46	22~69	18~55	31~46	16~69	11~56	26~47	
索数	3	2		3	2	2	3	2	2	3	2	2	2	2	2	2	2	2	2
LKコード	73	73		73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73
DSコード	33030	33030		33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045	33045	

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			
	42.0			45.0			48.0			51.0			54.0*			60.0*			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
22.0	22.1			21.1/23m			20.2			18.6									
24.0	22.1			21.1			20.2			18.6			17.1/25m						
26.0	22.1			21.1			20.2			18.6			17.1					13.5	
28.0	22.1			21.1			20.2			18.6			17.1					13.5	
30.0	22.1			21.1			20.2			18.6			17.1					13.5	
32.0	22.1			21.0			20.1			18.6			17.1					13.5	
34.0	22.1			20.9			20.0			18.6			17.1					13.5	
36.0	22.1			20.8			19.8			18.5			17.0					13.5	
38.0	22.1			20.7			19.6			18.4			17.0					13.5	
40.0	22.1	17.9		20.6	16.9/41m		19.5			18.3			17.0					13.5	
42.0	22.0	17.0		20.5	16.4		19.3	16.1		18.2			17.0					13.5	
44.0	21.9	16.3		20.4	15.7		19.1	15.3		18.1	14.9		17.0	14.2/45m				13.5	
46.0	21.9	15.6		20.3	14.9		19.0	14.5		18.0	14.3		17.0	13.9				13.5	
48.0		15.1		20.1	14.4		18.8	13.9		17.9	13.7		16.9	13.3				13.5	12.1
50.0		14.5	11.5/52m	20.0	13.8	10.7/53m	18.7	13.2		17.8	13.1		16.8	12.7				13.5	11.7
54.0		13.9	11.0		12.9	10.4		12.3	9.8/55m	17.6	11.9	9.1/57m	16.6	11.7				13.5	10.9
58.0			10.2		12.4	9.5		11.6	9.1		11.5	8.9	16.5	10.9	8.5/59m			13.5	10.1
62.0			9.6			8.8		11.2	8.3		11.0	7.8		10.3	7.9			13.5	9.5
66.0						7.9			7.7		10.2	6.7		9.9	7.2				9.1
70.0												5.9			6.6				8.7
74.0															5.9				8.4
78.0																			5.2
(°)	20~69	25~56	21~47	15~69	20~57	16~49	25~69	15~58	26~49	22~71	9~57	22~49	18~71	22~58	19~48	23~72	14~58	23~50	
索数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036	33036	

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)		
	66.0 #			72.0 #			78.0 #			84.0 #		
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)		
	83	73	65	83	73	65	83	73	65	83	73	65
28.0	10.3											
30.0	10.3			7.8								
32.0	10.3			7.8			6.6					
34.0	10.3			7.8			6.5			4.8		
36.0	10.3			7.8			6.5			4.8		
38.0	10.3			7.8			6.5			4.8		
40.0	10.3			7.8			6.4			4.8		
42.0	10.3			7.8			6.4			4.8		
44.0	10.3			7.8			6.3			4.8		
46.0	10.3			7.8			6.3			4.8		
48.0	10.3			7.8			6.3			4.8		
50.0	10.3	10.3/51m		7.8	7.5/53m		6.3			4.8		
54.0	10.3	9.8		7.8	7.5		6.3			4.8		
58.0	10.3	9.0		7.8	7.2		6.3			4.8		
62.0	10.3	8.3		7.8	7.0		6.3			4.8		
66.0	10.3	7.7		7.8	6.7		6.3			4.8		
70.0	10.3	7.3		7.8	6.4		6.3			4.8		
74.0		6.9		7.8	6.2		6.3			4.8		
78.0		6.6			5.9		6.3			4.8		
82.0					5.4		6.3			4.8		
86.0					4.9					4.8		
(°)	16~72	20~58		21~71	12~59		15~71			19~71		
索数	2	2		2	2		2			2		
LKコード	73	73		73	73		73			73		
DSコード	33037	33037		33038	33038		33039			33040		

補ジブ起伏角度(最小-最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* :最大風速7.0m/s # :最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラッピングジブ)

カウンタウエイト 100t  
アウトリガ 12.2×12.0m

主ジブ長さ+アダプタ長さ 55.5m+4.0m

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			単位:t
	24.0			27.0			30.0			33.0			36.0			39.0			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
20.0	31.0/21m			28.0/21m			25.5/21m			22.5/21m			20.0			18.1			
22.0	31.0			28.0			25.5			22.6			20.0			18.1			
24.0	30.0			27.8			25.5			22.6			20.0			18.1			
26.0	29.5			27.2			25.2			22.5			20.0			18.1			
28.0	28.8			26.6			24.7			22.3			20.0			18.1			
30.0				26.1			24.3			22.1			20.0			18.1			
32.0				25.6			23.9			21.9			20.0			18.1			
34.0		20.8/35m					23.5			21.7			20.0			18.1			
36.0		20.3			19.2			18.3		21.6	17.1/37m		20.0			18.1			
38.0		19.3			18.2			17.4		21.4	16.7		20.0	15.8/39m		18.1			
40.0					17.6			16.7		21.4	16.0		20.0	15.5		18.1	14.9		
42.0					16.9			16.0		21.4	15.4		20.0	14.8		18.1	14.2		
44.0								15.5		21.4	14.9		20.0	14.3		18.1	13.6		
46.0						12.9/47m			12.5/47m	21.4	14.4		20.0	13.8		18.1	13.1		
48.0						12.7			12.2	21.4	14.0	11.3/49m	20.0	13.5		18.1	12.7		
50.0						12.2			11.6	21.4	13.1	11.1	20.0	13.1		18.1	12.2		
52.0										21.4	10.6		20.0	10.0		18.1	12.0	9.4/53m	
54.0										21.4	10.2		20.0	9.8		18.1	11.7	9.2	
56.0										21.4	9.4		20.0	9.4		18.1	11.7	8.8	
58.0										21.4	9.1		20.0	9.1		18.1	11.7	8.5	
60.0										21.4	8.2		20.0	8.2		18.1	11.7	8.2	
62.0										21.4	7.9		20.0	7.9		18.1	11.7	7.9	
(°)	31~56	31~44		24~60	24~47	22~36	27~64	27~52	34~44	21~68	22~54	29~44	25~67	25~54	24~42	19~69	20~55	18~45	
条数	3	2		3	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83		83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	33030	33030		33043	33043	33043	33031	33031	33031	33044	33044	33044	33032	33032	33032	33045	33045	33045	

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			単位:t
	42.0			45.0			48.0*			51.0			54.0*			60.0#			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	83	73	65	
24.0	16.6			16.6						14.7/25m									
26.0	16.6			16.6			16.5			14.7			12.9/27m						
28.0	16.6			16.6			16.5			14.7			12.9				9.5		
30.0	16.6			16.6			16.5			14.7			12.9				9.5		
32.0	16.6			16.4			16.4			14.7			12.9				9.5		
34.0	16.6			16.3			16.3			14.7			12.9				9.5		
36.0	16.6			16.1			16.0			14.6			12.9				9.5		
38.0	16.6			16.0			15.7			14.5			12.9				9.5		
40.0	16.6			15.8			15.5			14.3			12.9				9.5		
42.0	16.6	13.8		15.7	12.8/43m		15.2			14.2			12.9				9.5		
44.0	16.6	13.2		15.6	12.5		15.0	11.7/45m		14.1			12.9				9.5		
46.0	16.6	12.6		15.5	11.9		14.8	11.4		13.9	11.1		12.9	10.4/47m			9.5		
48.0		12.1		15.4	11.4		14.6	10.9		13.8	10.6		12.9	10.2			9.5		
50.0		11.7		15.4	10.9		14.5	10.3		13.7	10.2		12.8	9.7			9.5	8.8	
54.0		11.0	8.3/56m		10.1	7.8/56m		9.5		13.6	9.3		12.7	8.8			9.5	8.0	
58.0			8.0		9.6	7.4		8.8	6.4/59m		8.6	6.3/60m	12.6	8.1			9.5	7.4	
62.0			7.4			6.7		8.4	6.2		8.2	6.0		7.6	5.7		9.5	6.8	4.7/65m
66.0						6.2			5.7		7.9	5.4		7.2	5.1			6.3	4.6
70.0									5.3			5.0			4.6			6.0	4.0
74.0												4.5			4.2			5.7	3.6
78.0																		5.3	3.3
82.0																		5.0	3.0
(°)	23~67	29~55	28~43	18~69	25~56	24~47	27~68	21~55	20~45	24~70	17~56	16~47	20~69	26~57	25~47	24~70	19~57	18~49	
条数	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	33033	33033	33033	33046	33046	33046	33034	33034	33034	33047	33047	33047	33035	33035	33035	33036	33036	33036	

作業半径 (m)	補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			補ジブ長さ(m)			単位:t
	66.0 #			72.0 #			78.0 #			84.0 #			
	主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			主ジブ角(°)			
	83	73	65	83	73	65	83	73	65	83	73	65	
28.0	7.0/29m												
30.0	7.0												
32.0	7.0			5.0			3.3/33m						
34.0	7.0			5.0			3.3			2.0/35m			
36.0	7.0			5.0			3.3			2.0			
38.0	7.0			5.0			3.3			2.0			
40.0	7.0			5.0			3.3			2.0			
42.0	7.0			5.0			3.3			2.0			
44.0	7.0			5.0			3.3			2.0			
46.0	7.0			5.0			3.3			2.0			
48.0	7.0			5.0			3.3			2.0			
50.0	7.0	6.4/53m		5.0			3.3			2.0			
54.0	7.0	6.2		5.0	4.8/56m		3.3			2.0			
58.0	7.0	5.6		5.0	4.7		3.3			2.0			
62.0	7.0	5.1		5.0	4.3		3.3			2.0			
66.0	7.0	4.6		5.0	4.0		3.3			2.0			
70.0	7.0	4.1		5.0	3.8		3.3			2.0			
74.0		3.7		5.0	3.5		3.3			2.0			
78.0		3.4			3.3		3.3			2.0			
82.0					3.1		3.3			2.0			
86.0					3.0					2.0			
(°)	18~71	23~58		22~70	17~58		16~71			20~71			
条数	2	2		2	2		2			2			
LKコード	83	83		83	83		83			83			
DSコード	33037	33037		33038	33038		33039			33040			

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 12.2 × 12.0m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 15.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																			単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	90.0*	96.0#		
12.0	123.0	114.0/13m	105.0/13m	98.8/13m																
14.0	118.0	112.0	103.0	97.7	89.0	81.4	73.0/15m													
16.0	111.0	107.0	101.0	95.7	88.0	80.8	73.0	67.0	60.5/17m	56.3/17m										
18.0	98.0	97.0	97.5	93.7	87.0	80.2	73.0	66.8	60.5	56.3	52.0									
20.0	83.0	82.9	82.5	82.3	82.0	79.6	72.5	66.7	60.5	56.3	52.0	42.0								
22.0	71.5	71.6	71.0	71.0	71.0	70.9	70.5	66.6	60.5	56.3	52.0	42.0	35.5	30.5/23m						
24.0	67.5/23m	63.0	62.5	62.4	62.5	62.2	62.0	61.7	60.5	56.3	52.0	42.0	35.0	30.0	24.5/25m					
26.0		56.1	55.5	55.4	55.5	55.3	55.0	54.7	54.5	54.2	52.0	42.0	34.5	30.0	24.3	19.9/27m				
28.0		53.3/27m	50.0	49.8	50.0	49.6	49.5	49.1	49.0	48.5	48.5	42.0	34.0	30.0	23.9	19.7	16.0			
30.0			45.5	45.2	45.0	44.9	44.5	44.4	44.5	43.8	44.0	42.0	33.5	30.0	23.5	19.3	15.6	13.0		
32.0				41.3	41.5	41.0	41.0	40.4	40.5	39.8	40.0	40.0	33.0	30.0	23.1	19.0	15.3	12.5		
34.0				39.6/33m	38.0	37.6	37.5	37.0	37.0	36.4	36.5	36.5	32.5	29.9	22.8	18.6	14.9	12.0		
36.0					35.0	34.7	34.5	34.1	34.0	33.5	33.5	34.0	32.5	29.7	22.4	18.3	14.6	11.6		
38.0						32.2	32.0	31.5	31.5	30.9	31.0	31.0	30.5	29.4	22.1	17.9	14.3	11.2		
40.0						31.1/39m	30.0	29.3	29.5	28.7	29.0	29.2	28.5	28.0	21.8	17.5	14.0	10.9		
42.0							28.1	27.4	27.5	26.7	27.0	27.2	26.5	26.0	21.5	17.2	13.7	10.6		
44.0								25.6	25.8	24.9	25.3	25.4	24.7	24.2	21.2	16.8	13.4	10.3		
46.0								24.9/45m	24.2	23.3	23.7	23.8	23.1	22.6	20.9	16.4	13.1	10.0		
48.0									23.5/47m	21.9	22.3	22.3	21.7	21.2	20.5	16.1	12.8	9.7		
50.0										20.7	21.0	21.0	20.3	19.9	20.1	15.7	12.5	9.5		
54.0											19.4/53m	18.8	18.1	17.6	17.8	15.0	12.0	9.0		
58.0												16.9	16.2	15.7	15.9	14.3	11.5	8.7		
62.0													14.6	14.0	14.2	13.7	11.1	8.4		
66.0													13.6/65m	12.7	12.8	12.7	10.7	8.1		
70.0														11.5	11.6	11.5	10.3	7.8		
74.0															10.5	10.4	10.0	7.5		
76.0															10.1	9.9	9.8	7.4		
78.0																9.4	9.6	7.3		
82.0																8.2	8.7	7.0		
86.0																	7.4	6.7		
88.0																	6.2	6.5		
90.0																		6.4		
94.0																			5.1/93m	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	20~74	19~74	18~73	18~74	19~74		
条数	10	9	9	8	7	7	6	6	5	5	4	4	3	3	2	2	2	2		
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00		
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040	34041	34042		

**主ジブ長さ+アダプタ長さ 20.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																			単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0*	96.0#		
12.0	116.0/13m	109.0/13m	100.0/13m	89.9/13m																
14.0	114.0	107.0	98.5	89.2	78.5	71.0/15m														
16.0	110.0	104.0	96.0	87.9	77.5	70.9	63.5	57.8	52.0/17m											
18.0	96.0	95.8	94.0	86.5	77.0	70.6	63.5	57.8	52.0	48.1	44.0/19m									
20.0	81.5	81.4	81.0	80.8	77.0	70.3	63.0	57.7	52.0	48.1	44.0	37.0								
22.0	70.5	70.3	70.0	69.7	69.5	69.6	63.0	57.6	52.0	48.1	44.0	37.0	30.0							
24.0	62.0	61.8	61.5	61.2	61.0	61.0	60.5	57.5	52.0	48.1	44.0	37.0	30.0	25.9						
26.0		55.0	54.5	54.3	54.5	54.2	54.0	53.6	51.5	48.1	44.0	37.0	29.9	25.8	21.7	17.6/27m				
28.0		49.5	49.0	48.8	49.0	48.6	48.5	48.1	48.0	47.5	44.0	37.0	29.7	25.7	21.5	17.5	14/29m			
30.0			44.5	44.2	44.5	44.0	44.0	43.4	43.5	42.8	43.0	37.0	29.5	25.7	21.3	17.4	13.8	11.1/31m		
32.0				40.4	40.5	40.1	40.0	39.5	39.5	38.9	39.0	37.0	29.2	25.6	21.2	17.2	13.6	10.9		
34.0				37.1	37.0	36.8	36.5	36.2	36.0	35.6	35.5	36.0	29.0	25.6	21.0	17.0	13.3	10.6		
36.0					34.5	34.0	34.0	33.3	33.5	32.7	33.0	33.0	28.7	25.6	20.8	16.8	13.1	10.4		
38.0						31.5	31.5	30.8	31.0	30.2	30.5	30.5	28.5	25.6	20.6	16.6	12.8	10.1		
40.0						29.3	29.3	28.6	28.8	28.0	28.3	28.5	27.8	25.5	20.3	16.3	12.6	9.8		
42.0							27.4	26.7	26.8	26.0	26.4	26.5	25.8	25.4	20.1	16.0	12.3	9.6		
44.0								25.0	25.1	24.3	24.6	24.8	24.1	23.6	19.9	15.7	12.1	9.3		
46.0								24.2/45m	23.6	22.7	23.1	23.2	22.5	22.0	19.6	15.4	11.9	9.1		
48.0									22.3	21.3	21.7	21.8	21.1	20.6	19.3	15.1	11.6	8.9		
50.0										20.1	20.4	20.5	19.8	19.3	19.1	14.8	11.4	8.7		
54.0											18.3	18.3	17.6	17.1	17.3	14.2	11.0	8.3		
58.0												16.5	15.7	15.2	15.4	13.6	10.5	7.9		
62.0													14.1	13.6	13.8	12.9	10.1	7.6		
66.0													13.2/65m	12.2	12.4	12.3	9.8	7.3		
70.0														11.1	11.2	11.1	9.4	7.0		
74.0															10.1	10.0	9.1	6.7		
78.0															9.5/77m	9.0	8.8	6.4		
82.0																8.2	8.3	6.1		
86.0																	7.5	5.8		
88.0																	6.8	5.7		
90.0																		5.6		
94.0																			5.0	
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	21~73	18~73	20~74	19~74	18~74		
条数	9	9	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2		
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02		
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040	34041	34042		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 12.2 × 12.0m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 25.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0#	96.0#	
14.0	111.0	101.0	92.5	83.6	76.0/15m														
16.0	106.0	99.0	91.5	83.0	76.0	67.5	60.5/17m	54.2/17m											
18.0	94.5	94.5	89.0	82.3	76.0	67.5	60.5	54.2	49.0	45.0/19m									
20.0	80.0	79.9	79.5	79.3	76.0	67.5	60.5	54.2	49.0	45.0	41.0	36.0/21m							
22.0	69.0	69.1	68.5	68.4	68.5	67.5	60.5	54.2	49.0	45.0	41.0	36.0	28/23m						
24.0	61.0	60.7	60.0	60.0	60.0	59.9	59.5	54.2	49.0	45.0	41.0	36.0	28.0	24.0/25m					
26.0		54.0	53.5	53.3	53.5	53.2	53.0	52.6	49.0	45.0	41.0	36.0	28.0	24.0	21.0				
28.0		48.5	48.0	47.8	48.0	47.7	47.5	47.1	47.0	44.9	41.0	36.0	28.0	24.0	21.0	17.0			
30.0		46.3/29m	43.5	43.3	43.5	43.1	43.0	42.5	42.5	41.9	41.0	36.0	28.0	24.0	21.0	16.9	13.5		
32.0				39.5	39.5	39.3	39.0	38.7	38.5	38.1	38.0	36.0	28.0	24.0	21.0	16.9	13.3	10.4	
34.0				36.3	36.5	36.0	36.0	35.4	35.5	34.8	35.0	35.0	28.0	24.0	21.0	16.8	13.1	10.3	
36.0				34.9/35m	33.5	33.2	33.0	32.6	32.5	31.9	32.0	32.5	27.9	24.0	21.0	16.7	12.9	10.1	
38.0						30.8	30.5	30.1	30.0	29.5	29.8	30.0	27.9	24.0	21.0	16.6	12.7	9.9	
40.0						28.7	28.6	27.9	28.1	27.3	27.6	27.8	27.2	24.0	20.8	16.6	12.5	9.7	
42.0						27.7/41m	26.8	26.0	26.2	25.4	25.7	25.9	25.2	24.0	20.7	16.5	12.3	9.5	
44.0								24.4	24.5	23.7	24.0	24.2	23.5	23.0	20.5	16.2	12.1	9.3	
46.0								22.9	23.0	22.1	22.5	22.6	21.9	21.4	20.2	15.9	11.9	9.1	
48.0								21.7	20.8	21.1	21.2	20.5	20.0	20.0	15.6	11.7	9.0		
50.0									19.5	19.9	20.0	19.3	18.8	19.1	15.3	11.5	8.8		
54.0									18.5/52m	17.8	17.8	17.1	16.6	16.9	14.7	11.1	8.4		
58.0											16.0	15.2	14.7	15.0	14.1	10.7	8.0		
62.0												13.7	13.1	13.4	13.3	10.3	7.6		
66.0												12.4	11.8	12.0	11.9	9.9	7.2		
70.0													10.7	10.8	10.7	9.5	6.9		
74.0														9.8	9.6	9.1	6.5		
78.0															8.8	8.7	8.8	6.2	
82.0																7.8	8.0	5.9	
86.0																	7.2	5.6	
90.0																	6.6/89m	5.3	
94.0																		5.1	
(°)	32~66	19~68	29~71	17~73	26~72	16~72	24~72	19~73	22~73	18~73	21~73	25~74	19~73	23~73	17~74	21~73	18~73	20~73	
係数	9	8	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040	34041	34042	

主ジブ長さ+アダプタ長さ 30.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0*	90.0#	96.0#	
14.0	96.5/15m	88.4/15m	80.5/15m	70.5/15m															
16.0	93.0	87.0	80.5	70.2	62.0	55.5/17m													
18.0	87.0	83.5	78.5	69.6	62.0	55.5	50.0	44.6	40/19m										
20.0	79.0	78.9	76.0	69.1	62.0	55.5	50.0	44.6	40.0	36.9	33.5/21m								
22.0	68.5	68.1	67.5	67.1	61.5	55.5	50.0	44.6	40.0	36.9	33.5	30.0							
24.0	60.0	59.8	59.5	59.1	59.5	55.1	50.0	44.6	40.0	36.9	33.5	30.0	23.3						
26.0	53.5	53.2	53.0	52.5	52.5	52.4	49.5	44.6	40.0	36.9	33.5	30.0	23.3	20.2	17.6/27m				
28.0		47.8	47.5	47.1	47.5	47.0	46.5	44.4	40.0	36.9	33.5	30.0	23.3	20.2	17.6	14.2/29m			
30.0		43.4	43.0	42.6	43.0	42.5	42.5	41.8	40.0	36.9	33.5	30.0	23.3	20.2	17.6	14.2	11.6/31m		
32.0			39.5	38.9	39.0	38.7	38.5	38.0	38.0	36.9	33.5	30.0	23.3	20.2	17.6	14.2	11.6	9.0/33m	
34.0				35.7	36.0	35.4	35.5	34.8	35.0	34.2	33.5	30.0	23.3	20.2	17.6	14.2	11.4	8.9	
36.0				33.0	33.0	32.7	32.5	32.0	32.0	31.4	31.5	30.0	23.3	20.2	17.6	14.1	11.3	8.8	
38.0					30.5	30.2	30.0	29.6	29.7	28.9	29.3	29.5	23.2	20.2	17.6	14.1	11.2	8.6	
40.0						28.1	28.1	27.4	27.6	26.8	27.1	27.4	23.2	20.2	17.5	14.1	11.1	8.5	
42.0						26.3	26.3	25.5	25.7	24.9	25.2	25.4	23.2	20.2	17.5	14.0	10.9	8.3	
44.0							24.6	23.9	24.1	23.2	23.5	23.7	23.0	20.2	17.4	13.9	10.8	8.2	
46.0								22.4	22.6	21.7	22.0	22.2	21.5	20.2	17.3	13.8	10.7	8.0	
48.0								21.8/47m	21.2	20.3	20.7	20.8	20.1	19.6	17.2	13.7	10.5	7.9	
50.0									20.1	19.1	19.5	19.6	18.9	18.4	17.1	13.6	10.4	7.7	
54.0									17.6/53m	17.4	17.4	16.7	16.2	16.5	13.3	10.1	7.4		
58.0												15.6	14.9	14.3	14.6	13.0	9.8	7.1	
62.0												14.5/61m	13.4	12.8	13.1	12.7	9.5	6.8	
66.0													12.1	11.5	11.7	11.6	9.3	6.5	
70.0														10.3	10.5	10.4	9.0	6.2	
74.0														9.6/73m	9.4	9.3	8.7	5.9	
78.0															8.5	8.3	8.4	5.6	
82.0																7.5	7.7	5.4	
84.0																7.2	7.3	5.3	
86.0																	6.9	5.1	
90.0																	6.2	5.0	
94.0																		4.8	
96.0																		4.5	
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	19~73	20~73	17~73	19~73	18~73	17~73	17~73	
係数	8	7	7	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2	
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040	34041	34042	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 12.2×12.0m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																			単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0#	90.0#	96.0#		
16.0	81.5	73.2/17m	67.5	60.2	54.5/17m															
18.0	77.0	72.1	66.5	59.9	54.5	49.3	45.0/19m	39.8/19m												
20.0	72.5	69.2	65.0	59.5	54.5	49.3	45.0	39.8	35.5	32.8/21m										
22.0	67.5	66.0	62.5	58.8	54.5	49.3	45.0	39.8	35.5	32.8	30.0	27.0/23m								
24.0	59.0	59.0	58.5	56.8	53.5	49.3	45.0	39.8	35.5	32.8	30.0	27.0	21.0/25m							
26.0	52.5	52.4	52.0	51.7	52.0	48.7	45.0	39.8	35.5	32.8	30.0	27.0	21.0	18.5/27m						
28.0		47.1	46.5	46.4	46.5	46.2	44.5	39.8	35.5	32.8	30.0	27.0	21.0	18.5	16.0					
30.0		42.7	42.5	41.9	42.0	41.8	41.5	39.7	35.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0				
32.0			38.5	38.2	38.5	38.1	38.0	37.4	35.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0	11.0			
34.0				35.1	35.0	34.9	34.5	34.2	34.0	32.8	30.0	27.0	21.0	18.5	16.0	13.0	10.9	8.5		
36.0				32.4	32.5	32.1	32.0	31.4	31.5	30.8	30.0	27.0	21.0	18.5	16.0	13.0	10.9	8.4		
38.0					30.0	29.7	29.7	29.0	29.2	28.4	28.7	27.0	21.0	18.5	16.0	13.0	10.8	8.3		
40.0						27.6	27.6	26.9	27.1	26.2	26.6	26.9	21.0	18.5	16.0	13.0	10.8	8.1		
42.0						25.8	25.8	25.1	25.2	24.4	24.7	25.0	21.0	18.5	16.0	13.0	10.7	8.0		
44.0							24.2	23.4	23.6	22.7	23.1	23.3	21.0	18.5	16.0	13.0	10.6	7.9		
46.0								21.9	22.1	21.2	21.6	21.8	21.0	18.5	16.0	13.0	10.5	7.8		
48.0								20.7	20.8	19.9	20.2	20.4	19.7	18.5	16.0	13.0	10.5	7.6		
50.0									19.6	18.7	19.0	19.2	18.5	18.0	16.0	13.0	10.4	7.5		
54.0										16.6	17.0	17.1	16.3	15.8	16.0	13.0	10.2	7.2		
58.0													15.3	14.5	14.0	14.3	13.0	10.0	6.9	
62.0													13.8	13.0	12.5	12.7	12.7	9.8	6.6	
66.0														11.8	11.1	11.4	11.3	9.6	6.3	
70.0															10.0	10.2	10.1	9.3	6.1	
74.0															9.0	9.1	9.0	9.1	5.8	
78.0																8.2	8.0	8.3	5.6	
82.0																	7.2	7.4	5.4	
86.0																	6.7/85m	6.7	5.2	
90.0																		6.0	5.1	
94.0																			5.0	
98.0																			4.1/97m	
(°)	28~63	21~64	25~69	19~71	23~71	17~71	21~71	16~72	29~72	15~72	24~72	17~73	22~73	16~72	20~73	17~73	19~73	16~73		
条数	7	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2	2		
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23		
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040	34041	34042		

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																			単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	78.0#	84.0#	90.0#	96.0#		
16.0	65.5/17m	60.4/17m	56.0/17m	48.8/17m																
18.0	65.5	60.3	56.0	48.8	43.0	38.9/19m														
20.0	63.0	60.1	56.0	48.8	43.0	38.9	35.5	32.1	29.2/21m											
22.0	60.0	56.9	55.0	48.8	43.0	38.9	35.5	32.1	29.2	27.2	25.2/23m									
24.0	56.5	54.2	52.0	47.7	43.0	38.9	35.5	32.1	29.2	27.2	25.2	21.9								
26.0	52.0	51.8	49.5	46.1	42.0	38.8	35.5	32.1	29.2	27.2	25.2	21.9	17.0							
28.0		46.6	46.0	44.7	41.0	38.4	35.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6/29m					
30.0		42.2	42.0	41.4	40.5	38.0	35.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0/31m				
32.0			38.0	37.7	38.0	37.6	35.0	32.0	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0	8.3/33m			
34.0				34.6	35.0	34.4	34.0	32.0	29.2	27.1	25.2	21.9	17.0	14.3	12.5	10.0	8.3	6.4/35m		
36.0				31.9	32.0	31.7	31.5	31.0	29.2	27.1	25.1	21.9	17.0	14.3	12.5	10.0	8.3	6.3		
38.0					29.9	29.3	29.3	28.6	28.8	27.1	25.1	21.9	17.0	14.3	12.4	10.0	8.2	6.2		
40.0						27.2	27.3	26.5	26.7	25.8	25.1	21.9	17.0	14.3	12.4	10.0	8.2	6.1		
42.0						25.4	25.4	24.7	24.9	24.0	24.4	21.9	17.0	14.3	12.4	10.0	8.2	5.9		
44.0							23.8	23.0	23.2	22.3	22.7	21.9	17.0	14.3	12.4	10.0	8.1	5.8		
46.0								21.6	21.8	20.8	21.2	21.4	17.0	14.3	12.4	10.0	8.1	5.7		
48.0								20.3	20.4	19.5	19.9	20.1	17.0	14.3	12.4	10.0	8.1	5.6		
50.0									19.3	18.3	18.7	18.9	17.0	14.3	12.4	10.0	8.0	5.5		
54.0										16.3	16.6	16.8	16.0	14.3	12.4	10.0	8.0	5.3		
58.0												15.0	14.2	13.7	12.4	10.0	7.9	5.1		
62.0												13.6	12.7	12.2	12.3	10.0	7.8	4.9		
66.0													11.5	10.8	11.1	9.9	7.7	4.7		
70.0														9.6	9.9	9.8	7.6	4.6		
74.0															8.7	8.8	7.4	4.4		
78.0																7.9	7.8	7.3	4.3	
82.0																	7.0	7.2	4.2	
86.0																	6.3	6.5	4.1	
90.0																		5.8	4.0	
94.0																			3.9	
98.0																			3.8	
(°)	31~62	24~66	28~68	22~70	25~72	20~70	23~70	19~72	22~72	17~72	26~72	19~72	23~72	17~72	21~73	16~73	20~72	15~72		
条数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2		
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43		
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040	34041	34042		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s



TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 12.2 x 12.0m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 45.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																			単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0#	78.0#	84.0#	90.0#	96.0#		
18.0	52.0/19m	48.4/19m	45.0/19m	40.1																
20.0	51.5	48.3	45.0	40.1	36.0	32.7	30.0/21m													
22.0	49.5	47.2	45.0	40.1	36.0	32.7	30.0	27.8	26.0	24.5/23m										
24.0	47.0	45.1	43.5	39.9	36.0	32.7	30.0	27.8	26.0	24.5	23.0									
26.0	44.5	43.3	41.5	38.9	35.5	32.7	30.0	27.8	26.0	24.5	23.0	19.0	14.7/27m							
28.0	42.5	41.9	40.0	38.0	35.0	32.6	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5/29m						
30.0		40.8	39.0	37.2	35.0	32.4	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5	10.6					
32.0		38.0	37.5	36.6	34.5	32.3	30.0	27.8	25.9	24.5	23.0	19.0	14.7	11.5	10.5	8.0/33m				
34.0			34.5	34.1	34.0	32.1	30.0	27.7	25.9	24.4	23.0	19.0	14.7	11.5	10.4	8.0	6.5/35m			
36.0				31.4	31.5	31.2	30.0	27.7	25.8	24.4	23.0	19.0	14.7	11.5	10.3	8.0	6.5	4.9		
38.0				29.2	29.5	28.9	28.9	27.6	25.7	24.3	22.9	19.0	14.7	11.5	10.2	8.0	6.5	4.8		
40.0					27.5	26.8	26.9	26.1	25.6	24.3	22.9	19.0	14.7	11.5	10.2	8.0	6.5	4.6		
42.0						25.0	25.0	24.3	24.5	23.5	22.9	19.0	14.7	11.5	10.1	8.0	6.5	4.5		
44.0							23.4	23.4	22.6	22.8	21.9	22.3	19.0	14.7	11.5	10.0	8.0	6.5	4.4	
46.0								22.0	21.2	21.4	20.4	20.9	19.0	14.7	11.5	10.0	8.0	6.5	4.3	
48.0									19.9	20.1	19.1	19.5	19.0	14.7	11.5	10.0	8.0	6.5	4.2	
50.0									18.8	18.9	17.9	18.3	18.6	14.7	11.5	10.0	8.0	6.5	4.1	
54.0										15.9	16.3	16.5	14.7	11.5	10.0	8.0	6.5	3.9		
58.0											14.7	14.7	13.9	11.5	10.0	8.0	6.5	3.8		
62.0												13.3	12.5	11.5	10.0	8.0	6.5	3.7		
66.0													11.2	10.5	10.0	8.0	6.5	3.6		
70.0													10.1	9.3	9.6	8.0	6.5	3.5		
74.0														8.4	8.6	8.0	6.5	3.5		
78.0															7.7	7.5	6.5	3.4		
82.0															6.9	6.7	6.5	3.4		
86.0																6.0	6.2	3.3		
90.0																	5.6	3.3		
94.0																		4.2	3.2	
98.0																			3.0	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~70	19~72	13~72	18~72	12~72	16~72		
条数	4	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040	34041	34042		

**主ジブ長さ+アダプタ長さ 50.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																単位:t		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	78.0#	84.0#			
18.0	38.0/19m		33.0/19m	29.9/19m															
20.0	38.0	35.0	32.5	29.7	26.6	24.1/21m													
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m											
24.0	36.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m								
26.0	36.0	33.6	31.0	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5							
28.0	35.0	33.3	31.0	28.5	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3						
30.0		32.7	31.0	28.4	26.2	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8					
32.0		32.2	30.5	28.2	26.1	24.0	22.1	21.0	20.1	18.6	17.1	13.5	10.3	7.8	6.6				
34.0			30.0	28.0	25.9	23.9	22.1	20.9	20.0	18.6	17.1	13.5	10.3	7.8	6.5	4.8			
36.0				27.8	25.8	23.8	22.1	20.8	19.8	18.5	17.0	13.5	10.3	7.8	6.5	4.8			
38.0				27.5	25.7	23.8	22.1	20.7	19.6	18.4	17.0	13.5	10.3	7.8	6.5	4.8			
40.0					25.6	23.7	22.1	20.6	19.5	18.3	17.0	13.5	10.3	7.8	6.4	4.8			
42.0						23.6	22.0	20.5	19.3	18.2	17.0	13.5	10.3	7.8	6.4	4.8			
44.0							23.1	21.9	20.4	19.1	18.1	17.0	13.5	10.3	7.8	6.3	4.8		
46.0								21.7	20.3	19.0	18.0	17.0	13.5	10.3	7.8	6.3	4.8		
48.0									19.6	18.8	17.9	16.9	13.5	10.3	7.8	6.3	4.8		
50.0									18.5	18.6	17.6	16.8	13.5	10.3	7.8	6.3	4.8		
54.0										15.6	16.0	13.5	10.3	7.8	6.3	4.8			
58.0											14.4	13.5	10.3	7.8	6.3	4.8			
62.0												13.0	10.3	7.8	6.3	4.8			
66.0													10.3	7.8	6.3	4.8			
70.0														9.8	7.8	6.3	4.8		
74.0															7.8	6.3	4.8		
78.0																6.3	4.8		
82.0																	6.3	4.8	
86.0																		4.8	
(°)	27~60	20~61	24~67	18~69	22~69	16~69	20~69	15~69	25~69	22~71	18~71	23~72	16~72	21~71	15~71	19~71			
条数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039	34040			

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフイングジブ)

カウンタウエイト 80t  
アウトリガ 12.2 × 12.0m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	78.0#		
20.0	31.0/21m	28.0/21m	25.5/21m	22.5													
22.0	31.0	28.0	25.5	22.6	20.0	18.1											
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m							
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m						
28.0	28.8	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m				
30.0		26.1	24.3	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0				
32.0		25.6	23.9	21.9	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0	3.3/33m		
34.0			23.5	21.7	20.0	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	3.3		
36.0				21.6	20.0	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	3.3		
38.0				21.4	20.0	18.1	16.6	16.0	15.7	14.5	12.9	9.5	7.0	5.0	3.3		
40.0					20.0	18.1	16.6	15.8	15.5	14.3	12.9	9.5	7.0	5.0	3.3		
42.0						18.1	16.6	15.7	15.2	14.2	12.9	9.5	7.0	5.0	3.3		
44.0						18.1	16.6	15.6	15.0	14.1	12.9	9.5	7.0	5.0	3.3		
46.0							16.6	15.5	14.8	13.9	12.9	9.5	7.0	5.0	3.3		
48.0								15.4	14.6	13.8	12.9	9.5	7.0	5.0	3.3		
50.0								15.4	14.5	13.7	12.8	9.5	7.0	5.0	3.3		
54.0										13.6	12.7	9.5	7.0	5.0	3.3		
58.0											12.6	9.5	7.0	5.0	3.3		
62.0												9.5	7.0	5.0	3.3		
66.0													7.0	5.0	3.3		
70.0													7.0	5.0	3.3		
74.0														5.0	3.3		
78.0															3.3		
82.0															3.3		
(°)	31~56	24~60	27~64	21~68	25~67	19~69	23~67	18~69	27~68	24~70	20~69	24~70	18~71	22~70	16~71		
条数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2		
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83		
DSコード	34030	34043	34031	34044	34032	34045	34033	34046	34034	34047	34035	34036	34037	34038	34039		

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 12.2×12.0m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 15.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																	単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	90.0*	
12.0	123.0	114.0/13m	105.0/13m	98.8/13m														
14.0	118.0	112.0	103.0	97.7	89.0	81.4	73.0/15m											
16.0	101.0	101.0	98.0	95.7	88.0	80.8	73.0	67.0	60.5/17m	56.3/17m								
18.0	83.0	82.9	82.5	82.3	81.5	80.2	73.0	66.8	60.5	56.3	52.0							
20.0	70.0	70.0	69.5	69.4	69.5	69.4	69.0	66.7	60.5	56.3	52.0	42.0						
22.0	60.5	60.4	60.0	59.8	60.0	59.7	59.5	59.2	59.0	56.3	52.0	42.0	35.5	30.5/23m				
24.0	57.0/23m	53.0	52.5	52.4	52.5	52.3	52.0	51.7	51.5	51.2	51.0	42.0	35.0	30.0	24.5/25m			
26.0		47.2	47.0	46.5	46.5	46.3	46.0	45.8	45.5	45.2	45.5	42.0	34.5	30.0	24.3	19.9/27m		
28.0		44.8/27m	42.0	41.7	42.0	41.5	41.5	41.0	41.0	40.4	40.5	34.0	30.0	23.9	19.7	16.0		
30.0			38.0	37.7	38.0	37.5	37.5	36.9	37.0	36.4	36.5	36.5	33.5	30.0	23.5	19.3	15.6	
32.0				34.4	34.5	34.1	34.0	33.5	33.5	33.0	33.0	33.5	32.5	30.0	23.1	19.0	15.3	
34.0				33.0/33m	31.5	31.3	31.0	30.7	30.5	30.0	30.0	30.5	29.9	29.5	22.8	18.6	14.9	
36.0					29.4	28.8	28.8	28.2	28.3	27.5	27.9	28.1	27.4	27.0	22.4	18.3	14.6	
38.0						26.7	26.7	26.0	26.2	25.4	25.7	25.9	25.2	24.8	22.1	17.9	14.3	
40.0						25.7/39m	24.8	24.1	24.3	23.4	23.8	24.0	23.3	22.8	21.8	17.5	14.0	
42.0							23.1	22.4	22.6	21.8	22.1	22.3	21.6	21.1	21.4	17.2	13.7	
44.0								21.0	21.1	20.3	20.6	20.7	20.1	19.6	19.9	16.8	13.4	
46.0								20.3/45m	19.8	18.9	19.3	19.4	18.7	18.2	18.5	16.4	13.1	
48.0									19.2/47m	17.7	18.1	18.1	17.5	17.0	17.3	16.1	12.8	
50.0										16.7	17.0	17.0	16.3	15.8	16.1	15.7	12.5	
54.0											15.6/53m	15.1	14.4	13.9	14.1	14.1	12.0	
58.0												13.6	12.8	12.3	12.5	12.4	11.5	
62.0													11.4	10.9	11.1	11.0	11.1	
66.0													10.6/65m	9.7	9.9	9.8	10.0	
70.0														8.7	8.8	8.7	8.9	
74.0															7.8	7.7	7.9	
76.0															7.4	7.3	7.5	
78.0																6.8	7.0	
82.0																6.1	6.2	
86.0																	5.5	
88.0																	5.2	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	20~74	19~74	18~73	18~74	
条数	10	9	9	8	7	7	6	6	5	5	4	4	3	3	2	2	2	
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	35041	

**主ジブ長さ+アダプタ長さ 20.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																	単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0*	
12.0	116.0/13m	109.0/13m	100.0/13m	89.9/13m														
14.0	114.0	107.0	98.5	89.2	78.5	71.0/15m												
16.0	97.0	96.5	92.5	87.9	77.5	70.9	63.5	57.8	52.0/17m									
18.0	81.0	81.2	80.5	80.2	77.0	70.6	63.5	57.8	52.0	48.1	44.0/19m							
20.0	68.5	68.5	68.0	67.9	68.0	67.9	63.0	57.7	52.0	48.1	44.0	37.0						
22.0	59.0	59.1	58.5	58.5	58.5	58.4	58.0	57.6	52.0	48.1	44.0	37.0	30.0					
24.0	52.0	51.9	51.5	51.2	51.5	51.1	51.0	50.5	50.5	48.1	44.0	37.0	30.0	25.9				
26.0		46.1	45.5	45.4	45.5	45.3	45.0	44.7	44.5	44.1	44.0	37.0	29.9	25.8	21.7	17.6/27m		
28.0		41.4	41.0	40.7	41.0	40.5	40.5	39.9	40.0	39.4	39.5	37.0	29.7	25.7	21.5	17.5	14.0/29m	
30.0			37.0	36.8	37.0	36.6	36.5	36.0	36.0	35.4	35.5	36.0	29.5	25.7	21.3	17.4	13.8	
32.0				33.5	33.5	33.3	33.0	32.7	32.5	32.1	32.0	32.5	29.2	25.6	21.2	17.2	13.6	
34.0				30.8	31.0	30.5	30.5	29.8	30.0	29.2	29.6	29.8	29.0	25.6	21.0	17.0	13.3	
36.0					28.6	28.0	28.1	27.4	27.6	26.8	27.1	27.3	26.7	25.6	20.8	16.8	13.1	
38.0						25.9	25.9	25.3	25.4	24.6	25.0	25.2	24.5	24.0	20.6	16.6	12.8	
40.0						24.1	24.1	23.4	23.6	22.7	23.1	23.3	22.6	22.1	20.3	16.3	12.6	
42.0							22.5	21.8	21.9	21.1	21.5	21.6	20.9	20.5	20.1	16.0	12.3	
44.0								20.3	20.5	19.6	20.0	20.1	19.4	19.0	19.3	15.7	12.1	
46.0								19.7/45m	19.2	18.3	18.7	18.8	18.1	17.6	17.9	15.4	11.9	
48.0									18.1	17.1	17.5	17.6	16.9	16.4	16.7	15.1	11.6	
50.0										16.1	16.4	16.5	15.8	15.3	15.6	14.8	11.4	
54.0											14.6	14.6	13.9	13.4	13.7	13.6	11.0	
58.0												13.1	12.3	11.8	12.0	12.0	10.5	
62.0													11.0	10.4	10.6	10.6	10.1	
66.0													10.2/65m	9.3	9.4	9.3	9.7	
70.0														8.2	8.3	8.2	8.5	
74.0															7.4	7.3	7.5	
78.0															6.8/77m	6.4	6.6	
82.0																5.7	5.9	
86.0																	5.2	
88.0																	4.9	
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	21~73	18~73	20~74	19~74	
条数	9	9	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	35041	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* :最大風速7.0m/s # :最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 12.2×12.0m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 25.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		90.0#
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0#		
14.0	107.0	101.0	92.5	83.6	76.0/15m														
16.0	91.5	91.2	87.5	83.0	76.0	67.5	60.5/17m	54.2/17m											
18.0	79.5	79.2	76.0	76.0	73.5	67.5	60.5	54.2	49.0	45/19m									
20.0	67.0	67.1	66.5	66.5	65.0	64.9	60.5	54.2	49.0	45.0	41.0	36.0/21m							
22.0	58.0	57.9	57.5	57.2	57.5	57.1	56.0	54.2	49.0	45.0	41.0	36.0	28.0/23m						
24.0	51.0	50.7	50.5	50.0	50.0	49.9	49.5	49.4	49.0	45.0	41.0	36.0	28.0	24.0/25m					
26.0		45.0	44.5	44.4	44.5	44.2	44.0	43.6	43.5	43.0	41.0	36.0	28.0	24.0	21.0				
28.0		40.4	40.0	39.7	40.0	39.6	39.5	39.0	39.0	38.4	38.5	36.0	28.0	24.0	21.0	17.0			
30.0		38.6/29m	36.0	35.9	36.0	35.7	35.5	35.1	35.0	34.5	34.5	35.0	28.0	24.0	21.0	16.9	13.5		
32.0				32.7	33.0	32.5	32.5	31.8	32.0	31.2	31.5	31.5	28.0	24.0	21.0	16.9	13.3		
34.0				29.9	30.0	29.7	29.7	29.0	29.2	28.4	28.8	29.0	28.0	24.0	21.0	16.8	13.1		
36.0				28.8/35m	27.9	27.3	27.3	26.6	26.8	26.0	26.4	26.6	25.9	24.0	21.0	16.7	12.9		
38.0						25.2	25.3	24.6	24.7	23.9	24.3	24.5	23.8	23.3	21.0	16.6	12.7		
40.0						23.4	23.4	22.7	22.9	22.1	22.4	22.6	22.0	21.5	20.8	16.6	12.5		
42.0						22.7/41m	21.9	21.1	21.3	20.4	20.8	21.0	20.3	19.8	20.2	16.5	12.3		
44.0								19.7	19.9	19.0	19.4	19.5	18.8	18.4	18.7	16.2	12.1		
46.0								18.4	18.6	17.7	18.1	18.2	17.5	17.0	17.4	15.9	11.9		
48.0									17.5	16.5	16.9	17.0	16.3	15.8	16.2	15.6	11.7		
50.0										15.5	15.9	16.0	15.3	14.8	15.1	15.0	11.5		
54.0										14.7/52m	14.1	14.1	13.4	12.9	13.2	13.1	11.1		
58.0												12.6	11.9	11.3	11.6	11.5	10.7		
62.0													10.6	10.0	10.2	10.2	10.3		
66.0													9.5	8.8	9.0	8.9	9.3		
70.0														7.8	7.9	7.8	8.1		
74.0															7.0	6.9	7.2		
78.0															6.2	6.1	6.3		
82.0																5.4	5.5		
86.0																	4.8		
90.0																		4.4/89m	
(°)	32~66	19~68	29~71	17~73	26~72	16~72	24~72	19~73	22~73	18~73	21~73	25~74	19~73	23~73	17~74	21~73	18~73		
索数	9	8	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2		
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03		
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	35041		

主ジブ長さ+アダプタ長さ 30.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		90.0#
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0*	90.0#		
14.0	94.5/15m	88.4/15m	80.5/15m	70.5/15m															
16.0	87.0	86.7	80.5	70.2	62.0	55.5/17m													
18.0	76.0	75.6	72.5	69.6	62.0	55.5	50.0	44.6	40/19m										
20.0	66.0	66.1	64.5	64.2	62.0	55.5	50.0	44.6	40.0	36.9	33.5/21m								
22.0	57.0	56.9	56.5	56.3	55.5	55.5	50.0	44.6	40.0	36.9	33.5	30.0							
24.0	50.0	49.9	49.5	49.2	49.5	49.1	48.5	44.6	40.0	36.9	33.5	30.0	23.3						
26.0	44.5	44.3	44.0	43.6	44.0	43.4	43.0	42.8	40.0	36.9	33.5	30.0	23.3	20.2	17.6/27m				
28.0		39.7	39.5	39.0	39.0	38.9	38.5	38.2	38.0	36.9	33.5	30.0	23.3	20.2	17.6	14.2/29m			
30.0		36.0	35.5	35.2	35.5	35.0	35.0	34.4	34.5	33.8	33.5	30.0	23.3	20.2	17.6	14.2	11.6/31m		
32.0			32.5	32.0	32.0	31.8	31.5	31.2	31.0	30.6	30.5	30.0	23.3	20.2	17.6	14.2	11.6		
34.0				29.3	29.7	29.1	29.1	28.5	28.6	27.8	28.2	28.4	23.3	20.2	17.6	14.2	11.4		
36.0				27.1	27.4	26.7	26.8	26.1	26.3	25.4	25.8	26.1	23.3	20.2	17.6	14.1	11.3		
38.0					25.3	24.7	24.7	24.0	24.2	23.4	23.7	24.0	23.2	20.2	17.6	14.1	11.2		
40.0						22.9	22.9	22.2	22.4	21.5	21.9	22.2	21.5	20.2	17.5	14.1	11.1		
42.0						21.4	21.4	20.6	20.8	19.9	20.3	20.5	19.8	19.3	17.5	14.0	10.9		
44.0							20.0	19.2	19.4	18.5	18.9	19.1	18.4	17.9	17.4	13.9	10.8		
46.0								18.0	18.2	17.2	17.6	17.8	17.1	16.6	17.0	13.8	10.7		
48.0								17.4/47m	17.0	16.1	16.5	16.6	15.9	15.4	15.8	13.7	10.5		
50.0									16.1	15.1	15.5	15.6	14.9	14.4	14.7	13.6	10.4		
54.0										13.8/53m	13.7	13.8	13.0	12.5	12.8	12.8	10.1		
58.0												12.3	11.5	11.0	11.3	11.2	9.8		
62.0												11.3/61m	10.2	9.6	9.9	9.8	9.5		
66.0													9.1	8.4	8.6	8.5	8.9		
70.0														7.4	7.6	7.5	7.8		
74.0														6.8/73m	6.7	6.5	6.9		
78.0															5.9	5.7	6.0		
82.0																5.1	5.3		
84.0																4.8	4.9		
86.0																	4.6		
90.0																		4.0	
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	19~73	20~73	17~73	19~73	18~73	17~73		
索数	8	7	7	6	5	5	4	4	3	3	3	3	2	2	2	2	2		
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08		
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	35041		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 12.2 × 12.0m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																		単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	90.0*		
16.0	81.5	73.2/17m	67.5	60.2	54.5/17m														
18.0	72.5	72.1	66.5	59.9	54.5	49.3	45.0/19m	39.8/19m											
20.0	64.0	63.9	61.5	59.5	54.5	49.3	45.0	39.8	35.5	32.8/21m									
22.0	56.0	56.0	55.0	55.0	53.5	49.3	45.0	39.8	35.5	32.8	30.0	27.0/23m							
24.0	49.5	49.0	48.5	48.3	48.5	48.1	45.0	39.8	35.5	32.8	30.0	27.0	21.0/25m						
26.0	44.0	43.5	43.0	42.8	43.0	42.7	42.5	39.8	35.5	32.8	30.0	27.0	21.0	18.5/27m					
28.0		39.0	38.5	38.3	38.5	38.1	38.0	37.5	35.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0			
30.0		35.3	35.0	34.5	35.0	34.4	34.0	33.7	33.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0			
32.0			32.0	31.4	31.5	31.2	31.0	30.6	30.5	29.9	30.0	27.0	21.0	18.5	16.0	13.0	11.0		
34.0				28.7	29.1	28.5	28.6	27.9	28.1	27.2	27.6	27.0	21.0	18.5	16.0	13.0	10.9		
36.0				26.5	26.8	26.2	26.2	25.5	25.7	24.9	25.2	25.5	21.0	18.5	16.0	13.0	10.9		
38.0				24.8	24.2	24.2	24.2	23.5	23.7	22.8	23.2	23.5	21.0	18.5	16.0	13.0	10.8		
40.0					22.4	22.4	22.4	21.7	21.9	21.0	21.4	21.7	21.0	18.5	16.0	13.0	10.8		
42.0						20.9	20.9	20.1	20.3	19.4	19.8	20.1	19.4	18.5	16.0	13.0	10.7		
44.0							19.5	18.7	18.9	18.0	18.4	18.6	17.9	17.4	16.0	13.0	10.6		
46.0								17.5	17.7	16.8	17.2	17.4	16.7	16.2	16.0	13.0	10.5		
48.0								16.4	16.6	15.6	16.0	16.2	15.5	15.0	15.4	13.0	10.5		
50.0									15.6	14.6	15.0	15.2	14.5	13.9	14.3	13.0	10.4		
54.0										13.0	13.3	13.4	12.6	12.1	12.5	12.4	10.2		
58.0												11.9	11.1	10.5	10.9	10.8	10.0		
62.0												10.7	9.8	9.2	9.5	9.4	9.8		
66.0													8.7	8.0	8.3	8.2	8.6		
70.0														7.0	7.2	7.1	7.5		
74.0														6.2	6.4	6.2	6.6		
78.0															5.6	5.4	5.7		
82.0																4.7	5.0		
86.0																4.3/85m	4.3		
90.0																	3.8		
(°)	28~63	21~64	25~69	19~71	23~71	17~71	21~71	16~72	29~72	15~72	24~72	17~73	22~73	16~72	20~73	17~73	19~73		
索数	7	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2		
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23		
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	35041		

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																		単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	78.0#	84.0#	90.0#		
16.0	65.5/17m	60.4/17m	56.0/17m	48.8/17m															
18.0	65.5	60.3	56.0	48.8	43.0	38.9/19m													
20.0	61.5	60.1	56.0	48.8	43.0	38.9	35.5	32.1	29.2/21m										
22.0	55.5	55.2	53.0	48.8	43.0	38.9	35.5	32.1	29.2	27.2	25.2/23m								
24.0	48.5	48.4	48.0	47.7	43.0	38.9	35.5	32.1	29.2	27.2	25.2	21.9							
26.0	43.0	42.9	42.5	42.2	42.0	38.8	35.5	32.1	29.2	27.2	25.2	21.9	17.0						
28.0		38.4	38.0	37.7	38.0	37.6	35.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6/29m				
30.0		34.8	34.5	34.0	34.5	33.9	33.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0/31m			
32.0			31.5	30.9	31.0	30.7	30.5	30.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0	8.3/33m		
34.0				28.2	28.7	28.0	28.1	27.4	27.6	26.7	25.2	21.9	17.0	14.3	12.5	10.0	8.3		
36.0				26.0	26.4	25.7	25.8	25.1	25.3	24.4	24.8	21.9	17.0	14.3	12.5	10.0	8.3		
38.0				24.4	23.7	23.8	23.1	23.3	22.4	22.8	21.9	17.0	14.3	12.4	10.0	8.2			
40.0						22.0	22.1	21.3	21.5	20.6	21.0	21.3	17.0	14.3	12.4	10.0	8.2		
42.0						20.5	20.5	19.7	20.0	19.0	19.4	19.7	17.0	14.3	12.4	10.0	8.2		
44.0							19.2	18.4	18.6	17.6	18.0	18.3	17.0	14.3	12.4	10.0	8.1		
46.0								17.1	17.3	16.4	16.8	17.0	16.3	14.3	12.4	10.0	8.1		
48.0								16.1	16.2	15.3	15.7	15.9	15.2	14.3	12.4	10.0	8.1		
50.0									15.3	14.3	14.7	14.9	14.1	13.6	12.4	10.0	8.0		
54.0										12.6	13.0	13.1	12.3	11.8	10.0	8.0			
58.0												11.6	10.8	10.2	10.6	10.0	7.9		
62.0												10.4	9.5	8.8	9.2	9.1	7.8		
66.0													8.4	7.7	8.0	7.9	7.7		
70.0														6.7	7.0	6.8	7.3		
74.0															5.9	6.1	6.3		
78.0																5.3	5.5		
82.0																	4.5		
86.0																	3.9		
90.0																	3.5		
(°)	31~62	24~66	28~68	22~70	25~72	20~70	23~70	19~72	22~72	17~72	26~72	19~72	23~72	17~72	21~73	16~73	20~72		
索数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	2	2	2		
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43		
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	35041		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 12.2 × 12.0m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 45.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																	
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0#	78.0#	84.0#	90.0#	
18.0	52.0/19m	48.4/19m	45.0/19m	40.1														
20.0	51.5	48.3	45.0	40.1	36.0	32.7	30.0/21m											
22.0	49.5	47.2	45.0	40.1	36.0	32.7	30.0	27.8	26.0	24.5/23m								
24.0	47.0	45.1	43.5	39.9	36.0	32.7	30.0	27.8	26.0	24.5	23.0							
26.0	42.5	42.3	41.5	38.9	35.5	32.7	30.0	27.8	26.0	24.5	23.0	19.0	14.7/27m					
28.0	38.5	37.9	37.5	37.1	35.0	32.6	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5/29m				
30.0		34.2	34.0	33.5	34.0	32.4	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5	10.6			
32.0		31.2	31.0	30.4	30.5	30.2	30.0	27.8	25.9	24.5	23.0	19.0	14.7	11.5	10.5	8.0/33m		
34.0			28.4	27.7	28.2	27.6	27.7	26.9	25.9	24.4	23.0	19.0	14.7	11.5	10.4	8.0	6.5/35m	
36.0				25.5	26.0	25.3	25.4	24.6	24.9	23.9	23.0	19.0	14.7	11.5	10.3	8.0	6.5	
38.0				23.6	24.0	23.3	23.4	22.6	22.9	21.9	22.4	19.0	14.7	11.5	10.2	8.0	6.5	
40.0					22.3	21.6	21.7	20.9	21.1	20.2	20.6	19.0	14.7	11.5	10.2	8.0	6.5	
42.0						20.1	20.1	19.3	19.6	18.6	19.1	19.0	14.7	11.5	10.1	8.0	6.5	
44.0						18.8	18.8	18.0	18.2	17.2	17.7	17.9	14.7	11.5	10.0	8.0	6.5	
46.0							17.6	16.8	17.0	16.0	16.4	16.7	14.7	11.5	10.0	8.0	6.5	
48.0								15.7	15.9	14.9	15.3	15.6	14.7	11.5	10.0	8.0	6.5	
50.0								14.8	14.9	13.9	14.3	14.5	13.8	11.5	10.0	8.0	6.5	
54.0										12.2	12.6	12.8	12.0	11.4	10.0	8.0	6.5	
58.0											11.3	11.3	10.5	9.8	10.0	8.0	6.5	
62.0												10.1	9.1	8.5	8.9	8.0	6.5	
66.0													8.0	7.4	7.7	7.6	6.5	
70.0														7.2	6.4	6.7	6.6	
74.0															5.6	5.8	5.7	
78.0																5.1	4.9	
82.0																4.5	4.2	
86.0																	3.7	
90.0																	3.3	
94.0																	2.9	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~70	19~72	13~72	18~72	12~72	
条数	4	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	35041	

**主ジブ長さ+アダプタ長さ 50.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	78.0#	84.0#	
18.0	38.0/19m		33.0/19m	29.9/19m													
20.0	38.0	35.0	32.5	29.7	26.6	24.1/21m											
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m									
24.0	36.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m						
26.0	36.0	33.6	31.0	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5					
28.0	35.0	33.3	31.0	28.5	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3				
30.0		32.7	31.0	28.4	26.2	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8			
32.0		30.8	30.5	28.2	26.1	24.0	22.1	21.0	20.1	18.6	17.1	13.5	10.3	7.8	6.6		
34.0			28.1	27.4	25.9	23.9	22.1	20.9	20.0	18.6	17.1	13.5	10.3	7.8	6.5	4.8	
36.0				25.1	25.6	23.8	22.1	20.8	19.8	18.5	17.0	13.5	10.3	7.8	6.5	4.8	
38.0				23.2	23.7	23.0	22.1	20.7	19.6	18.4	17.0	13.5	10.3	7.8	6.5	4.8	
40.0					22.0	21.3	21.3	20.6	19.5	18.3	17.0	13.5	10.3	7.8	6.4	4.8	
42.0						19.8	19.8	19.0	19.3	18.2	17.0	13.5	10.3	7.8	6.4	4.8	
44.0						18.4	18.5	17.7	17.9	16.9	17.0	13.5	10.3	7.8	6.3	4.8	
46.0							17.3	16.5	16.7	15.7	16.1	13.5	10.3	7.8	6.3	4.8	
48.0								15.4	15.6	14.6	15.0	13.5	10.3	7.8	6.3	4.8	
50.0								14.5	14.6	13.6	14.1	13.5	10.3	7.8	6.3	4.8	
54.0										11.9	12.4	12.5	10.3	7.8	6.3	4.8	
58.0											11.0	11.1	10.2	7.8	6.3	4.8	
62.0												9.8	8.9	7.8	6.3	4.8	
66.0													7.8	7.1	6.3	4.8	
70.0														6.9	6.1	4.8	
74.0															5.4	4.8	
78.0																4.8	
82.0																4.2	
86.0																3.5	
(°)	27~60	20~61	24~67	18~69	22~69	16~69	20~69	15~69	25~69	22~71	18~71	23~72	16~72	21~71	15~71	19~71	
条数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	35040	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

DZ-0072-6(5/5)

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 12.2×12.0m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)															
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	78.0#	
20.0	31.0/21m	28.0/21m	25.5/21m	22.5												
22.0	31.0	28.0	25.5	22.6	20.0	18.1										
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m						
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m					
28.0	28.8	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m			
30.0		26.1	24.3	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0			
32.0		25.6	23.9	21.9	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0	3.3/33m	
34.0			23.5	21.7	20.0	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	3.3	
36.0				21.6	20.0	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	3.3	
38.0				21.4	20.0	18.1	16.6	16.0	15.7	14.5	12.9	9.5	7.0	5.0	3.3	
40.0					20.0	18.1	16.6	15.8	15.5	14.3	12.9	9.5	7.0	5.0	3.3	
42.0						18.1	16.6	15.7	15.2	14.2	12.9	9.5	7.0	5.0	3.3	
44.0						18.1	16.6	15.6	15.0	14.1	12.9	9.5	7.0	5.0	3.3	
46.0							16.6	15.5	14.8	13.9	12.9	9.5	7.0	5.0	3.3	
48.0								15.1	14.6	13.8	12.9	9.5	7.0	5.0	3.3	
50.0								14.1	14.4	13.3	12.8	9.5	7.0	5.0	3.3	
54.0										11.6	12.1	9.5	7.0	5.0	3.3	
58.0											10.6	9.5	7.0	5.0	3.3	
62.0												9.5	7.0	5.0	3.3	
66.0													7.0	5.0	3.3	
70.0													6.6	5.0	3.3	
74.0														5.0	3.3	
78.0															3.3	
82.0															3.3	
(°)	31~56	24~60	27~64	21~68	25~67	19~69	23~67	18~69	27~68	24~70	20~69	24~70	18~71	22~70	16~71	
条数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	35030	35043	35031	35044	35032	35045	35033	35046	35034	35047	35035	35036	35037	35038	35039	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウェイト 120t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 15.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	90.0*	96.0#	
12.0	123.0	114.0/13m	105.0/13m	98.8/13m															
14.0	118.0	112.0	103.0	97.7	89.0	81.4	73.0/15m												
16.0	110.0	107.0	101.0	95.7	88.0	80.8	73.0	67.0	60.5/17m	56.3/17m									
18.0	92.5	92.9	92.5	92.4	87.0	80.2	73.0	66.8	60.5	56.3	52.0								
20.0	79.5	79.9	79.5	79.3	79.0	79.2	72.5	66.7	60.5	56.3	52.0	42.0							
22.0	70.0	69.9	69.5	69.4	69.0	69.2	68.5	66.6	60.5	56.3	52.0	42.0	35.5	30.5/23m					
24.0	66.0/23m	62.1	61.5	61.5	61.5	61.3	61.0	60.8	60.5	56.3	52.0	42.0	35.0	30.0	24.5/25m				
26.0		55.8	55.5	55.2	55.0	55.0	54.5	54.5	54.0	53.9	52.0	42.0	34.5	30.0	24.3	19.9/27m			
28.0		53.2/27m	50.0	49.9	50.0	49.7	49.0	49.2	48.5	48.7	48.5	42.0	34.0	30.0	23.9	19.7	16.0		
30.0			46.0	45.6	45.5	45.3	45.0	44.8	44.5	44.2	44.0	42.0	33.5	30.0	23.5	19.3	15.6	13.0	
32.0				41.9	41.5	41.6	41.0	41.0	40.5	40.5	40.0	40.5	33.0	30.0	23.1	19.0	15.3	12.5	
34.0				40.3/33m	38.5	38.4	38.0	37.8	37.5	37.2	37.0	37.0	32.5	29.9	22.8	18.6	14.9	12.0	
36.0					35.5	35.6	35.0	35.0	34.5	34.4	34.0	34.0	32.5	29.7	22.4	18.3	14.6	11.6	
38.0						33.2	32.5	32.6	32.0	32.0	31.5	31.5	31.0	29.4	22.1	17.9	14.3	11.2	
40.0						32.1/39m	30.5	30.4	30.0	29.8	29.7	29.8	29.1	28.6	21.8	17.5	14.0	10.9	
42.0							28.8	28.5	28.2	27.9	27.8	27.8	27.2	26.7	21.5	17.2	13.7	10.6	
44.0								26.8	26.5	26.1	26.0	26.1	25.5	24.9	21.2	16.8	13.4	10.3	
46.0								26.0/45m	25.0	24.6	24.5	24.5	23.9	23.3	20.9	16.4	13.1	10.0	
48.0									24.3/47m	23.2	23.1	23.1	22.5	21.9	20.5	16.1	12.8	9.7	
50.0										22.0	21.8	21.8	21.2	20.6	20.2	15.7	12.5	9.5	
54.0											20.2/53m	19.6	18.9	18.4	18.6	15.0	12.0	9.0	
58.0												17.7	17.0	16.5	16.6	14.3	11.5	8.7	
62.0													15.4	14.8	15.0	13.7	11.1	8.4	
66.0													14.4/65m	13.5	13.6	13.1	10.7	8.1	
70.0														12.3	12.3	12.2	10.3	7.8	
74.0															11.3	11.1	10.0	7.5	
76.0															10.3	10.7	9.8	7.4	
78.0																10.2	9.6	7.3	
82.0																8.4	9.4	7.0	
86.0																	7.6	6.7	
88.0																	6.5	6.5	
90.0																		6.4	
94.0																		5.3/93m	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	27~74	20~74	22~73	18~73	20~74	19~74	18~73	18~74	19~74	
条数	10	9	9	8	7	7	6	6	5	5	4	4	3	3	2	2	2	2	
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	72041	72042	

**主ジブ長さ+アダプタ長さ 20.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0*	96.0#	
12.0	116.0/13m	109.0/13m	100.0/13m	89.9/13m															
14.0	114.0	107.0	98.5	89.2	78.5	71.0/15m													
16.0	109.0	104.0	96.0	87.9	77.5	70.9	63.5	57.8	52.0/17m										
18.0	91.5	91.5	91.0	86.5	77.0	70.6	63.5	57.8	52.0	48.1	44.0/19m								
20.0	78.5	78.7	78.0	78.1	77.0	70.3	63.0	57.7	52.0	48.1	44.0	37.0							
22.0	69.0	68.8	68.5	68.2	68.0	68.1	63.0	57.6	52.0	48.1	44.0	37.0	30.0						
24.0	61.0	61.1	60.5	60.5	60.5	60.3	60.0	57.5	52.0	48.1	44.0	37.0	30.0	25.9					
26.0	55.0	54.9	54.5	54.2	54.0	54.1	53.5	53.5	51.5	48.1	44.0	37.0	29.9	25.8	21.7	17.6/27m			
28.0		49.7	49.5	49.1	49.0	48.9	48.5	48.3	48.0	47.5	44.0	37.0	29.7	25.7	21.5	17.5	14.0/29m		
30.0			45.0	44.8	44.5	44.5	44.0	44.0	43.5	43.4	43.0	37.0	29.5	25.7	21.3	17.4	13.8	11.1/31m	
32.0			43.0/31m	41.1	41.0	40.9	40.5	40.3	40.0	39.7	39.5	37.0	29.2	25.6	21.2	17.2	13.6	10.9	
34.0				38.0	38.0	37.7	37.0	37.1	36.5	36.5	36.0	36.5	29.0	25.6	21.0	17.0	13.3	10.6	
36.0					35.0	34.9	34.5	34.3	34.0	33.8	33.5	33.5	28.7	25.6	20.8	16.8	13.1	10.4	
38.0					34.0/37m	32.5	32.0	31.9	31.5	31.3	31.0	31.0	28.5	25.6	20.6	16.6	12.8	10.1	
40.0						30.4	30.0	29.8	29.5	29.2	29.1	29.2	28.2	25.5	20.3	16.3	12.6	9.8	
42.0							28.3	27.9	27.6	27.3	27.2	27.2	26.6	25.4	20.1	16.0	12.3	9.6	
44.0							27.4/43m	26.2	25.9	25.6	25.5	25.5	24.9	24.4	19.9	15.7	12.1	9.3	
46.0								25.5/45m	24.4	24.0	23.9	24.0	23.4	22.8	19.6	15.4	11.9	9.1	
48.0									23.1	22.7	22.6	22.6	22.0	21.4	19.3	15.1	11.6	8.9	
50.0										21.4	21.3	21.3	20.7	20.1	19.1	14.8	11.4	8.7	
54.0											19.2	19.1	18.5	17.9	18.1	14.2	11.0	8.3	
58.0												17.3	16.6	16.0	16.2	13.6	10.5	7.9	
62.0												16.5/60m	15.0	14.4	14.6	12.9	10.1	7.6	
66.0													14.0/65m	13.1	13.2	12.4	9.8	7.3	
70.0														11.9	12.0	11.9	9.4	7.0	
74.0														11.7/71m	10.9	10.8	9.1	6.7	
78.0															10.2/77m	9.9	8.8	6.4	
82.0																9.0	8.5	6.1	
86.0																8.2/83m	8.2	5.8	
88.0																	7.0	5.7	
90.0																		5.6	
94.0																		5.3	
(°)	15~67	22~69	21~71	20~73	19~73	18~73	17~73	21~74	20~74	23~73	19~73	18~74	20~74	19~73	18~73	17~74	19~74	18~73	
条数	9	9	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2	
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	72041	72042	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s



TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 120t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 25.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0#	96.0#	
14.0	111.0	101.0	92.5	83.6	76.0/15m	67.5	60.5/17m	54.2/17m											
16.0	106.0	99.0	91.5	83.0	76.0	67.5	60.5	54.2	49.0	45.0/19m									
18.0	90.0	90.2	89.0	82.3	76.0	67.5	60.5	54.2	49.0	45.0	41.0	36/21m							
20.0	77.5	77.5	77.0	76.9	76.0	67.5	60.5	54.2	49.0	45.0	41.0	36.0	28.0/23m						
22.0	67.5	67.8	67.0	67.2	67.0	67.0	60.5	54.2	49.0	45.0	41.0	36.0	28.0	24.0/25m					
24.0	60.0	60.1	59.5	59.5	59.5	59.4	59.0	54.2	49.0	45.0	41.0	36.0	28.0	24.0	21.0				
26.0	54.0	54.0	53.5	53.3	53.0	53.2	52.5	52.6	49.0	45.0	41.0	36.0	28.0	24.0	21.0	17.0			
28.0		48.9	48.5	48.2	48.0	48.1	47.5	47.5	47.0	44.9	41.0	36.0	28.0	24.0	21.0	17.0			
30.0		46.8/29m	44.0	44.0	44.0	43.8	43.5	43.2	42.5	42.6	41.0	36.0	28.0	24.0	21.0	16.9	13.5		
32.0			40.5	40.4	40.0	40.1	39.5	39.6	39.0	39.0	38.5	36.0	28.0	24.0	21.0	16.9	13.3	10.4	
34.0				37.3	37.0	37.0	36.5	36.4	36.0	35.8	35.5	35.5	28.0	24.0	21.0	16.8	13.1	10.3	
36.0				36.0/35m	34.5	34.3	34.0	33.7	33.0	33.1	33.0	33.0	27.9	24.0	21.0	16.7	12.9	10.1	
38.0					32.0	31.9	31.5	31.3	31.0	30.7	30.5	30.5	27.9	24.0	21.0	16.6	12.7	9.9	
40.0						29.8	29.5	29.2	28.9	28.6	28.5	28.6	27.8	24.0	20.8	16.6	12.5	9.7	
42.0						28.9/41m	27.7	27.3	27.1	26.7	26.6	26.7	26.1	24.0	20.7	16.5	12.3	9.5	
44.0							26.9/43m	25.7	25.4	25.0	24.9	25.0	24.4	23.8	20.5	16.2	12.1	9.3	
46.0								24.2	23.9	23.5	23.4	23.5	22.8	22.3	20.2	15.9	11.9	9.1	
48.0									22.6	22.2	22.1	22.1	21.5	20.9	20.0	15.6	11.7	9.0	
50.0									22.0/49m	21.0	20.8	20.9	20.2	19.7	19.7	15.3	11.5	8.8	
54.0										19.9/52m	18.7	18.7	18.0	17.5	17.7	14.7	11.1	8.4	
58.0												16.9	16.2	15.6	15.8	14.1	10.7	8.0	
62.0													15.8/61m	14.6	14.0	14.2	13.6	10.3	7.6
66.0														13.3	12.7	12.8	12.8	9.9	7.2
70.0															11.5	11.6	11.5	9.5	6.9
72.0															11.1	11.1	11.0	9.3	6.7
74.0																10.6	10.5	9.1	6.5
78.0																9.7	9.6	8.8	6.2
82.0																	8.8	8.5	5.9
86.0																	8.6/83m	8.1	5.6
90.0																		6.8/89m	5.3
94.0																			5.1
96.0																			5/95m
(°)	21~66	19~68	18~71	17~73	16~72	16~72	20~72	19~73	19~73	18~73	21~73	16~73	19~73	18~73	17~74	19~73	18~73	20~73	
条数	9	8	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	72041	72042	

主ジブ長さ+アダプタ長さ 30.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)																				
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0*	90.0#	96.0#			
14.0	96.5/15m	88.4/15m	80.5/15m	70.5/15m																	
16.0	93.0	87.0	80.5	70.2	62.0	55.5/17m															
18.0	87.0	83.5	78.5	69.6	62.0	55.5	50.0	44.6	40.0/19m												
20.0	76.5	76.6	76.0	69.1	62.0	55.5	50.0	44.6	40.0	36.9	33.5/21m										
22.0	67.0	67.0	66.5	66.4	61.5	55.5	50.0	44.6	40.0	36.9	33.5	30.0									
24.0	59.5	59.4	59.0	58.8	58.5	55.1	50.0	44.6	40.0	36.9	33.5	30.0	23.3								
26.0	53.5	53.3	53.0	52.7	52.5	52.5	49.5	44.6	40.0	36.9	33.5	30.0	23.3	20.2	17.6/27m						
28.0		48.3	48.0	47.6	47.5	47.5	47.0	44.4	40.0	36.9	33.5	30.0	23.3	20.2	17.6	14.2/29m					
30.0		44.1	43.5	43.4	43.5	43.2	42.5	42.6	40.0	36.9	33.5	30.0	23.3	20.2	17.6	14.2	11.6/31m				
32.0			40.0	39.8	39.5	39.6	39.0	39.0	38.5	36.9	33.5	30.0	23.3	20.2	17.6	14.2	11.6	9.0/33m			
34.0				36.7	36.5	36.5	36.0	35.9	35.5	35.3	33.5	30.0	23.3	20.2	17.6	14.2	11.4	8.9			
36.0					34.1	34.0	33.8	33.5	33.2	32.5	32.6	32.5	30.0	23.3	20.2	17.6	14.1	11.3	8.8		
38.0						31.5	31.5	31.0	30.8	30.5	30.2	30.0	30.0	23.2	20.2	17.6	14.1	11.2	8.6		
40.0							29.4	29.1	28.8	28.5	28.1	28.0	28.2	23.2	20.2	17.5	14.1	11.1	8.5		
42.0							27.6	27.3	26.9	26.6	26.3	26.2	26.3	23.2	20.2	17.5	14.0	10.9	8.3		
44.0								25.6	25.3	25.0	24.6	24.5	24.6	23.1	20.2	17.4	13.9	10.8	8.2		
46.0									23.8	23.5	23.1	23.0	23.1	22.5	20.2	17.3	13.8	10.7	8.0		
48.0									23.2/47m	22.2	21.8	21.7	21.7	21.1	20.2	17.2	13.7	10.5	7.9		
50.0										21.0	20.6	20.5	20.5	19.9	19.3	17.1	13.6	10.4	7.7		
54.0											19.0/53m	18.4	18.4	17.7	17.1	16.8	13.3	10.1	7.4		
58.0													16.6	15.9	15.3	15.5	13.0	9.8	7.1		
62.0														15.4/61m	14.3	13.7	13.9	12.7	9.5	6.8	
66.0															13.0	12.4	12.6	12.4	9.3	6.5	
70.0																11.3	11.4	11.3	9.0	6.2	
74.0																	10.5/73m	10.3	8.7	5.9	
78.0																		9.5	9.3	8.4	5.6
82.0																			8.5	8.1	5.4
84.0																			8.2	8.0	5.3
86.0																				7.9	5.1
90.0																				6.5	5.0
94.0																					4.8
96.0																					4.7
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	18~73	20~73	17~73	19~73	18~73	17~73	17~73			
条数	8	7	7	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2			
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08			
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	72041	72042			

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 120t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0#	90.0#	96.0#	
16.0	81.5	73.2/17m	67.5	60.2	54.5/17m														
18.0	77.0	72.1	66.5	59.9	54.5	49.3	45.0/19m	39.8/19m											
20.0	72.5	69.2	65.0	59.5	54.5	49.3	45.0	39.8	35.5	32.8/21m									
22.0	66.0	66.0	62.5	58.8	54.5	49.3	45.0	39.8	35.5	32.8	30.0	27.0/23m							
24.0	58.5	58.7	58.0	56.8	53.5	49.3	45.0	39.8	35.5	32.8	30.0	27.0	21.0/25m						
26.0	52.5	52.7	52.0	52.0	52.0	48.7	45.0	39.8	35.5	32.8	30.0	27.0	21.0	18.5/27m					
28.0	48.0	47.7	47.0	47.0	47.0	46.9	44.5	39.8	35.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0			
30.0		43.5	43.0	42.8	43.0	42.7	42.0	39.7	35.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0			
32.0			39.5	39.3	39.0	39.1	38.5	38.5	35.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0	11.0		
34.0			36.5	36.2	36.0	36.0	35.5	35.4	35.0	32.8	30.0	27.0	21.0	18.5	16.0	13.0	10.9	8.5	
36.0				33.6	33.5	33.3	33.0	32.7	32.0	32.1	30.0	27.0	21.0	18.5	16.0	13.0	10.9	8.4	
38.0					31.0	31.0	30.5	30.4	30.0	29.8	29.7	27.0	21.0	18.5	16.0	13.0	10.8	8.3	
40.0					29.4	29.0	28.7	28.3	28.0	27.7	27.6	27.0	21.0	18.5	16.0	13.0	10.8	8.1	
42.0						27.2	26.8	26.5	26.2	25.8	25.7	25.9	21.0	18.5	16.0	13.0	10.7	8.0	
44.0							25.2	24.8	24.6	24.2	24.1	24.2	21.0	18.5	16.0	13.0	10.6	7.9	
46.0							23.8	23.4	23.1	22.7	22.6	22.7	21.0	18.5	16.0	13.0	10.5	7.8	
48.0								22.1	21.8	21.4	21.3	21.4	20.7	18.5	16.0	13.0	10.5	7.6	
50.0									20.6	20.2	20.1	20.1	19.5	18.5	16.0	13.0	10.4	7.5	
54.0										18.2	18.0	18.0	17.3	16.8	16.0	13.0	10.2	7.2	
58.0											16.8/57m	16.2	15.5	15.0	15.2	13.0	10.0	6.9	
62.0												14.8	14.0	13.4	13.7	13.0	9.8	6.6	
66.0													12.7	12.1	12.3	12.2	9.6	6.3	
70.0													12.2/68m	11.0	11.1	11.0	9.3	6.1	
74.0														10.0	10.1	10.0	9.1	5.8	
78.0															9.2	9.1	8.9	5.6	
80.0															8.8	8.7	8.7	5.5	
82.0																8.3	8.5	5.4	
86.0																7.8/85m	7.7	5.2	
90.0																	6.8	5.1	
94.0																	6.0/91m	5.0	
98.0																		4.4/97m	
(°)	13~63	21~64	12~69	19~71	11~71	17~71	10~71	16~72	19~72	15~72	14~72	17~73	16~73	16~72	15~73	17~73	16~73	16~73	
条数	7	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2	2	
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	72041	72042	

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	78.0#	84.0#	90.0#	96.0#	
16.0	65.5/17m	60.4/17m	56.0/17m	48.8/17m															
18.0	65.5	60.3	56.0	48.8	43.0	38.9/19m													
20.0	63.0	60.1	56.0	48.8	43.0	38.9	35.5	32.1	29.2/21m										
22.0	60.0	56.9	55.0	48.8	43.0	38.9	35.5	32.1	29.2	27.2	25.2/23m								
24.0	56.5	54.2	52.0	47.7	43.0	38.9	35.5	32.1	29.2	27.2	25.2	21.9							
26.0	52.0	51.9	49.5	46.1	42.0	38.8	35.5	32.1	29.2	27.2	25.2	21.9	17.0						
28.0	47.5	47.2	47.0	44.7	41.0	38.4	35.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6/29m				
30.0		43.1	42.5	42.4	40.5	38.0	35.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0/31m			
32.0			39.0	38.8	39.0	37.7	35.0	32.0	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0	8.3/33m		
34.0			36.0	35.8	36.0	35.6	35.0	32.0	29.2	27.1	25.2	21.9	17.0	14.3	12.5	10.0	8.3	6.4/35m	
36.0				33.2	33.0	33.0	32.5	31.8	29.2	27.1	25.1	21.9	17.0	14.3	12.5	10.0	8.3	6.3	
38.0					31.0	30.6	30.0	30.0	29.1	27.1	25.1	21.9	17.0	14.3	12.4	10.0	8.2	6.2	
40.0					29.0	28.6	28.3	28.0	27.7	27.1	25.1	21.9	17.0	14.3	12.4	10.0	8.2	6.1	
42.0						26.8	26.5	26.1	25.9	25.5	25.1	21.9	17.0	14.3	12.4	10.0	8.2	5.9	
44.0							24.9	24.5	24.2	23.9	23.8	21.9	17.0	14.3	12.4	10.0	8.1	5.8	
46.0							23.5	23.1	22.8	22.4	22.3	21.9	17.0	14.3	12.4	10.0	8.1	5.7	
48.0								21.8	21.5	21.1	21.0	21.1	17.0	14.3	12.4	10.0	8.1	5.6	
50.0									20.3	19.9	19.8	19.9	17.0	14.3	12.4	10.0	8.0	5.5	
54.0										17.8	17.7	17.7	17.0	14.3	12.4	10.0	8.0	5.3	
58.0											16.1	16.0	15.3	14.3	12.4	10.0	7.9	5.1	
62.0												14.5	13.8	13.2	12.3	10.0	7.8	4.9	
66.0													12.5	11.8	12.1	9.9	7.7	4.7	
70.0													11.4	10.7	10.9	9.8	7.6	4.6	
74.0														9.8	9.9	9.6	7.4	4.4	
78.0															9.0	8.9	7.3	4.3	
82.0															8.4/81m	8.1	7.2	4.2	
86.0																7.4	7.1	4.1	
90.0																	6.9	4.0	
92.0																	5.6	3.9	
94.0																		3.9	
98.0																		3.8	
(°)	19~62	24~66	17~68	22~70	15~72	20~70	14~70	19~72	22~72	17~72	12~72	19~72	11~72	17~72	14~73	16~73	15~72	15~72	
条数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	72041	72042	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 120t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 45.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0#	78.0#	84.0#	90.0#	96.0#	
18.0	52.0/19m	48.4/19m	45.0/19m	40.1															
20.0	51.5	48.3	45.0	40.1	36.0	32.7	30.0/21m												
22.0	49.5	47.2	45.0	40.1	36.0	32.7	30.0	27.8	26.0	24.5/23m									
24.0	47.0	45.1	43.5	39.9	36.0	32.7	30.0	27.8	26.0	24.5	23.0								
26.0	44.5	43.3	41.5	38.9	35.5	32.7	30.0	27.8	26.0	24.5	23.0	19.0	14.7/27m						
28.0	42.5	41.9	40.0	38.0	35.0	32.6	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5/29m					
30.0		40.8	39.0	37.2	35.0	32.4	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5	10.6				
32.0		39.2	38.5	36.6	34.5	32.3	30.0	27.8	25.9	24.5	23.0	19.0	14.7	11.5	10.5	8.0/33m			
34.0			35.5	35.4	34.0	32.1	30.0	27.7	25.9	24.4	23.0	19.0	14.7	11.5	10.4	8.0	6.5/35m		
36.0				32.8	32.5	32.0	30.0	27.7	25.8	24.4	23.0	19.0	14.7	11.5	10.3	8.0	6.5	4.9	
38.0				30.6	30.5	30.3	30.0	27.6	25.7	24.3	22.9	19.0	14.7	11.5	10.2	8.0	6.5	4.8	
40.0					28.7	28.3	27.9	27.5	25.6	24.3	22.9	19.0	14.7	11.5	10.2	8.0	6.5	4.6	
42.0						26.5	26.2	25.8	25.5	24.2	22.9	19.0	14.7	11.5	10.1	8.0	6.5	4.5	
44.0						24.9	24.6	24.2	23.9	23.5	22.8	19.0	14.7	11.5	10.0	8.0	6.5	4.4	
46.0							23.2	22.7	22.5	22.1	22.0	19.0	14.7	11.5	10.0	8.0	6.5	4.3	
48.0								21.5	21.2	20.7	20.6	19.0	14.7	11.5	10.0	8.0	6.5	4.2	
50.0								20.3	20.0	19.6	19.5	19.0	14.7	11.5	10.0	8.0	6.5	4.1	
54.0										17.5	17.4	17.5	14.7	11.5	10.0	8.0	6.5	3.9	
58.0											15.7	15.7	14.7	11.5	10.0	8.0	6.5	3.8	
62.0												14.2	13.5	11.5	10.0	8.0	6.5	3.7	
66.0													12.2	11.5	10.0	8.0	6.5	3.6	
70.0													11.2	10.5	10.0	8.0	6.5	3.5	
74.0														9.5	9.7	8.0	6.5	3.5	
78.0															8.8	8.0	6.5	3.4	
82.0															8.0	7.9	6.5	3.4	
86.0																7.2	6.5	3.3	
90.0																	6.5	3.3	
94.0																	4.5	3.2	
98.0																		3.0	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~70	19~72	13~72	18~72	12~72	16~72	
索数	4	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	72041	72042	

主ジブ長さ+アダプタ長さ 50.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	78.0#	84.0#	
18.0	38.0/19m		33.0/19m	29.9/19m													
20.0	38.0	35.0	32.5	29.7	26.6	24.1/21m											
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m									
24.0	36.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m						
26.0	36.0	33.6	31.0	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5					
28.0	35.0	33.3	31.0	28.5	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3				
30.0	34.5	32.7	31.0	28.4	26.2	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8			
32.0		32.2	30.5	28.2	26.1	24.0	22.1	21.0	20.1	18.6	17.1	13.5	10.3	7.8	6.6		
34.0			30.0	28.0	25.9	23.9	22.1	20.9	20.0	18.6	17.1	13.5	10.3	7.8	6.5	4.8	
36.0			29.5	27.8	25.8	23.8	22.1	20.8	19.8	18.5	17.0	13.5	10.3	7.8	6.5	4.8	
38.0				27.5	25.7	23.8	22.1	20.7	19.6	18.4	17.0	13.5	10.3	7.8	6.5	4.8	
40.0					25.6	23.7	22.1	20.6	19.5	18.3	17.0	13.5	10.3	7.8	6.4	4.8	
42.0					25.5	23.6	22.0	20.5	19.3	18.2	17.0	13.5	10.3	7.8	6.4	4.8	
44.0						23.5	21.9	20.4	19.1	18.1	17.0	13.5	10.3	7.8	6.3	4.8	
46.0							21.9	20.3	19.0	18.0	17.0	13.5	10.3	7.8	6.3	4.8	
48.0							21.7	20.1	18.8	17.9	16.9	13.5	10.3	7.8	6.3	4.8	
50.0								20.0	18.7	17.8	16.8	13.5	10.3	7.8	6.3	4.8	
54.0									17.8	17.3	16.6	13.5	10.3	7.8	6.3	4.8	
58.0											15.5	13.5	10.3	7.8	6.3	4.8	
62.0												13.5	10.3	7.8	6.3	4.8	
66.0												12.9	10.3	7.8	6.3	4.8	
70.0													10.3	7.8	6.3	4.8	
74.0														7.8	6.3	4.8	
78.0															7.8/77m	6.3	4.8
82.0																6.3	4.8
86.0																	4.8
(°)	11~60	20~61	10~67	18~69	9~69	16~69	8~69	15~69	7~69	22~71	17~71	6~71	16~72	11~71	14~71	19~71	
索数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 120t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)															
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	78.0#	84.0#
20.0	31.0/21m	28.0/21m	25.5/21m	22.5												
22.0	31.0	28.0	25.5	22.6	20.0	18.1										
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m						
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m					
28.0	28.8	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m			
30.0	28.1	26.1	24.3	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0			
32.0		25.6	23.9	21.9	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0		
34.0			23.5	21.7	20.0	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	3.3	2.0/35m
36.0			23.2	21.6	20.0	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	3.3	2.0
38.0				21.4	20.0	18.1	16.6	16.0	15.7	14.5	12.9	9.5	7.0	5.0	3.3	2.0
40.0					20.0	18.1	16.6	15.8	15.5	14.3	12.9	9.5	7.0	5.0	3.3	2.0
42.0					20.0	18.1	16.6	15.7	15.2	14.2	12.9	9.5	7.0	5.0	3.3	2.0
44.0						18.1	16.6	15.6	15.0	14.1	12.9	9.5	7.0	5.0	3.3	2.0
46.0							16.6	15.5	14.8	13.9	12.9	9.5	7.0	5.0	3.3	2.0
48.0							16.6	15.4	14.6	13.8	12.9	9.5	7.0	5.0	3.3	2.0
50.0								15.4	14.5	13.7	12.8	9.5	7.0	5.0	3.3	2.0
54.0									14.3	13.6	12.7	9.5	7.0	5.0	3.3	2.0
58.0											12.6	9.5	7.0	5.0	3.3	2.0
62.0												9.5	7.0	5.0	3.3	2.0
66.0												9.5	7.0	5.0	3.3	2.0
70.0													7.0	5.0	3.3	2.0
74.0														5.0	3.3	2.0
78.0														5.0	3.3	2.0
82.0															3.3	2.0
86.0																2.0
90.0																2.0
(°)	18~56	24~60	16~64	21~68	14~67	19~69	13~67	18~69	12~68	24~70	20~69	11~70	18~71	10~70	16~71	9~71
条数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83
DSコード	72030	72043	72031	72044	72032	72045	72033	72046	72034	72047	72035	72036	72037	72038	72039	72040

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 15.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																			単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	90.0*	96.0#		
12.0	123.0	114/13m	105/13m	98.8/13m																
14.0	118.0	112.0	103.0	97.7	89.0	81.4	73/15m													
16.0	97.0	97.0	96.5	95.7	88.0	80.8	73.0	67.0	60.5/17m	56.3/17m										
18.0	81.0	81.4	81.0	80.8	80.5	80.2	73.0	66.8	60.5	56.3	52.0									
20.0	70.0	69.9	69.5	69.3	69.0	69.2	68.5	66.7	60.5	56.3	52.0	42.0								
22.0	61.0	61.1	60.5	60.5	60.5	60.4	60.0	59.9	59.5	56.3	52.0	42.0	35.5	30.5/23m						
24.0	57.5/23m	54.2	54.0	53.6	53.5	53.5	53.0	52.9	52.5	52.4	52.0	42.0	35.0	30.0	24.5/m					
26.0		48.7	48.0	48.0	48.0	47.8	47.5	47.3	47.0	46.8	46.5	42.0	34.5	30.0	24.3	19.9/27m				
28.0		46.4/27m	43.5	43.4	43.5	43.2	42.5	42.7	42.0	42.1	42.0	42.0	34.0	30.0	23.9	19.7	16.0			
30.0			40.0	39.6	39.5	39.3	39.0	38.8	38.5	38.2	38.0	38.0	33.5	30.0	23.5	19.3	15.6	13.0		
32.0				36.3	36.0	36.0	35.5	35.5	35.0	34.9	34.5	34.5	33.0	30.0	23.1	19.0	15.3	12.5		
34.0				34.9/33m	33.5	33.2	32.5	32.6	32.0	32.1	32.0	32.0	31.5	29.9	22.8	18.6	14.9	12.0		
36.0					31.0	30.8	30.5	30.2	29.9	29.6	29.5	29.6	29	28.5	22.4	18.3	14.6	11.6		
38.0						28.6	28.3	28.0	27.8	27.4	27.3	27.4	26.8	26.3	22.1	17.9	14.3	11.2		
40.0						27.7/39m	26.5	26.1	25.9	25.5	25.4	25.5	24.9	24.4	21.8	17.5	14.0	10.9		
42.0							24.8	24.4	24.2	23.8	23.7	23.8	23.2	22.6	21.5	17.2	13.7	10.6		
44.0								22.9	22.7	22.3	22.2	22.2	21.6	21.1	21.2	16.8	13.4	10.3		
46.0								22.3/45m	21.3	20.9	20.8	20.9	20.2	19.7	20.0	16.4	13.1	10.0		
48.0									20.7/47m	19.7	19.9	19.6	19.6	19.0	18.4	18.7	16.1	12.8	9.7	
50.0										18.6	18.5	18.5	17.8	17.3	17.5	15.7	12.5	9.5		
54.0											17.1/53m	16.5	15.8	15.3	15.5	15.0	12.0	9.0		
58.0												14.9	14.2	13.6	13.8	13.7	11.5	8.7		
62.0													12.8	12.2	12.3	12.3	11.1	8.4		
66.0													11.9/65m	11.0	11.1	11.0	10.7	8.1		
70.0														9.9	10.0	9.9	10.1	7.8		
74.0																9.0	8.9	9.1	7.5	
76.0																8.6	8.5	8.6	7.4	
78.0																	8.1	8.2	7.3	
82.0																	7.4	7.4	7.0	
86.0																		6.7	6.6	
88.0																		6.4	6.3	
90.0																			5.9	
94.0																			5.3/93m	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	20~74	19~74	18~73	18~74	19~74		
条数	10	9	9	8	7	7	6	6	5	5	4	4	3	3	2	2	2	2		
LKコード	00	0	00	0	00	0	00	0	00	0	00	00	00	00	00	00	00	00		
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	73041	73042		

主ジブ長さ+アダプタ長さ 20.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																			単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0*	96.0#		
12.0	116.0/13m	109.0/13m	100.0/13m	89.9/13m																
14.0	114.0	107.0	98.5	89.2	78.5	71.0/15m														
16.0	95.0	95.4	95.0	87.9	77.5	70.9	63.5	57.8	52.0/17m											
18.0	80.0	80.0	79.5	79.4	77.0	70.6	63.5	57.8	52.0	48.1	44.0/19m									
20.0	68.5	68.7	68.0	68.1	68.0	68.0	63.0	57.7	52.0	48.1	44.0	37.0								
22.0	60.0	60.0	59.5	59.4	59.5	59.3	58.5	57.6	52.0	48.1	44.0	37.0	30.0							
24.0	53.0	53.2	53.0	52.6	52.5	52.5	52.0	51.9	51.5	48.1	44.0	37.0	30.0	25.9						
26.0	48.0	47.7	47.5	47.1	47.0	46.9	46.5	46.4	46.0	45.8	44.0	37.0	29.9	25.8	21.7	17.6/27m				
28.0		43.2	43.0	42.6	42.5	42.4	42.0	41.8	41.5	41.3	41.0	37.0	29.7	25.7	21.5	17.5	14.0/29m			
30.0			39.0	38.8	38.5	38.6	38.0	38.0	37.5	37.4	37.0	37.0	29.5	25.7	21.3	17.4	13.8	11.1/31m		
32.0				37.5/31m	35.5	35.5	35.3	35.0	34.7	34.5	34.2	34.0	34.0	29.2	25.6	21.2	17.2	13.6	10.9	
34.0					32.8	32.5	32.5	32.0	31.9	31.5	31.4	31.0	31.0	29.0	25.6	21.0	17.0	13.3	10.6	
36.0						30.5	30.1	29.8	29.5	29.3	28.9	28.8	28.9	28.3	25.6	20.8	16.8	13.1	10.4	
38.0						29.4/37m	28.0	27.7	27.4	27.1	26.8	26.7	26.8	26.2	25.6	20.6	16.6	12.8	10.1	
40.0							26.2	25.9	25.5	25.3	24.9	24.8	24.9	24.3	23.8	20.3	16.3	12.6	9.8	
42.0								24.2	23.8	23.6	23.2	23.1	23.2	22.6	22.1	20.1	16.0	12.3	9.6	
44.0								23.5/43m	22.4	22.1	21.7	21.7	21.7	21.1	20.5	19.9	15.7	12.1	9.3	
46.0									21.7/45m	20.8	20.4	20.3	20.3	19.7	19.2	19.5	15.4	11.9	9.1	
48.0										19.6	19.2	19.1	19.1	18.5	17.9	18.2	15.1	11.6	8.9	
50.0											18.1	18.0	18.0	17.3	16.8	17.1	14.8	11.4	8.7	
54.0												16.1	16.0	15.4	14.8	15.1	14.2	11.0	8.3	
58.0													14.4	13.7	13.2	13.4	13.3	10.5	7.9	
62.0														13.8/60m	12.4	11.8	11.9	10.1	7.6	
66.0														11.5/65m	10.6	10.7	10.6	9.8	7.3	
70.0															9.6	9.6	9.5	9.4	7.0	
74.0																9.4/71m	8.7	8.6	8.7	
78.0																	8.1/77m	7.8	7.9	6.4
82.0																		7.1	7.2	6.1
86.0																		6.9/83m	6.5	5.8
88.0																			6.2	5.7
90.0																				5.6
94.0																				5.1
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	21~73	18~73	20~74	19~74	18~73		
条数	9	9	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2		
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02		
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	73041	73042		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 25.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0#	96.0#	
14.0	111.0	101.0	92.5	83.6	76.0/15m														
16.0	93.5	93.8	91.5	83.0	76.0	67.5	60.5/17m	54.2/17m											
18.0	78.5	78.6	78.0	78.0	76.0	67.5	60.5	54.2	49.0	45.0/19m									
20.0	67.5	67.5	67.0	66.9	66.5	66.8	60.5	54.2	49.0	45.0	41.0	36.0/21m							
22.0	59.0	59.0	58.5	58.3	58.0	58.2	57.5	54.2	49.0	45.0	41.0	36.0	28.0/23m						
24.0	52.5	52.3	52.0	51.6	51.5	51.5	51.0	50.9	49.0	45.0	41.0	36.0	28.0	24.0/25m					
26.0	47.0	46.8	46.5	46.2	46.0	46.0	45.5	45.5	45.0	44.9	41.0	36.0	28.0	24.0	21.0				
28.0		42.4	42.0	41.7	41.5	41.6	41.0	41.0	40.5	40.4	40.0	36.0	28.0	24.0	21.0	17.0			
30.0		40.6/29m	38.0	38.0	38.0	37.8	37.5	37.2	36.5	36.6	36.5	36.0	28.0	24.0	21.0	16.9	13.5		
32.0			35.0	34.8	34.5	34.6	34.0	34.0	33.5	33.4	33.0	33.5	28.0	24.0	21.0	16.9	13.3	10.4	
34.0				32.1	32.0	31.8	31.5	31.3	31.0	30.7	30.5	30.5	28.0	24.0	21.0	16.8	13.1	10.3	
36.0				31.0/35m	29.8	29.5	29.2	28.9	28.6	28.3	28.2	28.3	27.7	24.0	21.0	16.7	12.9	10.1	
38.0					27.8	27.4	27.1	26.8	26.5	26.2	26.1	26.2	25.6	24.0	21.0	16.6	12.7	9.9	
40.0						25.6	25.3	24.9	24.7	24.3	24.2	24.3	23.7	23.2	20.8	16.6	12.5	9.7	
42.0						24.8/41m	23.7	23.3	23.0	22.7	22.6	22.7	22.0	21.5	20.7	16.5	12.3	9.5	
44.0							22.9/43m	21.8	21.6	21.2	21.2	21.1	21.2	20.6	20.0	16.2	12.1	9.3	
46.0								20.5	20.3	19.9	19.8	19.8	19.2	18.7	19.0	15.9	11.9	9.1	
48.0									19.1	18.7	18.6	18.6	18.0	17.4	17.7	15.6	11.7	9.0	
50.0									18.6/49m	17.6	17.5	17.5	16.9	16.3	16.6	15.3	11.5	8.8	
54.0										16.8/52m	15.7	15.6	14.9	14.4	14.6	14.6	11.1	8.4	
58.0												14.0	13.3	12.7	13.0	12.9	10.7	8.0	
62.0													13.0/61m	12.0	11.4	11.6	11.5	10.3	7.6
66.0														10.8	10.2	10.3	10.3	9.9	7.2
70.0															9.2	9.3	9.2	9.4	6.9
72.0															8.8	8.8	8.7	9.0	6.7
74.0																8.4	8.3	8.5	6.5
78.0																7.6	7.5	7.6	6.2
82.0																	6.8	6.9	5.9
86.0																	6.6/83m	6.2	5.6
90.0																		5.8/89m	5.3
(°)	21~66	19~68	18~71	17~73	16~72	16~72	20~72	19~73	19~73	18~73	21~73	16~73	19~73	18~73	17~74	19~73	18~73	18~73	
条数	9	8	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	73041	73042	

主ジブ長さ+アダプタ長さ 30.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 :t	
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0*	90.0#	96.0#		
14.0	96.5/15m	88.4/15m	80.5/15m	70.5/15m																
16.0	92.5	87.0	80.5	70.2	62.0	55.5/17m														
18.0	77.5	77.7	77.0	69.6	62.0	55.5	50.0	44.6	40.0/19m											
20.0	66.5	66.6	66.0	66.0	62.0	55.5	50.0	44.6	40.0	36.9	33.5/21m									
22.0	58.0	58.2	57.5	57.6	57.5	55.5	50.0	44.6	40.0	36.9	33.5	30.0								
24.0	51.5	51.6	51.0	50.9	51.0	50.8	50.0	44.6	40.0	36.9	33.5	30.0	23.3							
26.0	46.5	46.2	45.5	45.5	45.4	45.0	44.6	40.0	36.9	33.5	30.0	23.3	20.2	17.6/27m						
28.0		41.8	41.5	41.1	41.0	41.0	40.5	40.4	40.0	36.9	33.5	30.0	23.3	20.2	17.6	14.2/29m				
30.0		38.1	37.5	37.4	37.5	37.2	36.5	36.6	36.0	36.1	33.5	30.0	23.3	20.2	17.6	14.2	11.6/31m			
32.0			34.5	34.3	34.0	34.1	33.5	33.5	33.0	32.9	32.5	30.0	23.3	20.2	17.6	14.2	11.6	9/33m		
34.0				31.6	31.5	31.3	31.0	30.7	30.5	30.1	30.0	30.0	23.3	20.2	17.6	14.2	11.4	8.9		
36.0				29.3	29.4	29.0	28.7	28.4	28.1	27.8	27.7	27.8	23.3	20.2	17.6	14.1	11.3	8.8		
38.0					27.3	26.9	26.6	26.3	26.0	25.7	25.6	25.7	23.2	20.2	17.6	14.1	11.2	8.6		
40.0						25.1	24.8	24.5	24.2	23.9	23.8	23.9	23.2	20.2	17.5	14.1	11.1	8.5		
42.0						23.6	23.2	22.9	22.6	22.2	22.1	22.3	21.6	20.2	17.5	14.0	10.9	8.3		
44.0							21.8	21.4	21.2	20.8	20.7	20.8	20.1	19.6	17.4	13.9	10.8	8.2		
46.0								20.1	19.9	19.5	19.4	19.5	18.8	18.3	17.3	13.8	10.7	8.0		
48.0								19.6/47m	18.7	18.3	18.2	18.3	17.6	17.1	17.2	13.7	10.5	7.9		
50.0									17.7	17.2	17.1	17.2	16.5	16.0	16.2	13.6	10.4	7.7		
54.0										15.9/53m	15.3	15.3	14.6	14.0	14.3	13.3	10.1	7.4		
58.0												13.7	13.0	12.4	12.7	12.6	9.8	7.1		
62.0													12.7/61m	11.6	11.1	11.3	11.2	9.5	6.8	
66.0														10.5	9.9	10.1	10.0	9.3	6.5	
70.0															8.9	9.0	8.9	9.0	6.2	
74.0																8.3/73m	8.1	8.0	8.2	5.9
78.0																	7.4	7.2	7.4	5.6
82.0																		6.5	6.7	5.4
84.0																		6.2	6.3	5.3
86.0																			6.0	5.1
90.0																			5.4	5.0
94.0																				4.7
96.0																				4.5
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	18~73	20~73	17~73	19~73	18~73	17~73	17~73		
条数	8	7	7	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2		
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08		
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	73041	73042		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 35.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0#	90.0#	96.0#	
16.0	81.5	73.2/17m	67.5	60.2	54.5/17m														
18.0	76.5	72.1	66.5	59.9	54.5	49.3	45.0/19m	39.8/19m											
20.0	65.5	65.8	65.0	59.5	54.5	49.3	45.0	39.8	35.5	32.8/21m									
22.0	57.5	57.4	57.0	56.8	54.5	49.3	45.0	39.8	35.5	32.8	30.0	27.0/23m							
24.0	51.0	50.9	50.5	50.2	50.0	49.3	45.0	39.8	35.5	32.8	30.0	27.0	21.0/25m						
26.0	45.5	45.5	45.0	44.9	45.0	44.7	44.0	39.8	35.5	32.8	30.0	27.0	21.0	18.5/27m					
28.0	41.5	41.2	40.5	40.5	40.5	40.3	40.0	39.8	35.5	32.8	30.0	27.0	21.0	18.5	16.0				
30.0		37.5	37.0	36.8	37.0	36.7	36.0	36.1	35.5	32.8	30.0	27.0	21.0	18.5	16.0	13.0			
32.0			34.0	33.7	33.5	33.5	33.0	32.9	32.5	32.3	30.0	27.0	21.0	18.5	16.0	13.0	11.0		
34.0			31.5	31.1	31.0	30.8	30.5	30.2	30.0	29.6	29.5	27.0	21.0	18.5	16.0	13.0	10.9	8.5	
36.0				28.8	28.9	28.5	28.2	27.9	27.6	27.3	27.2	27.0	21.0	18.5	16.0	13.0	10.9	8.4	
38.0					26.9	26.5	26.2	25.8	25.6	25.2	25.1	25.3	21.0	18.5	16.0	13.0	10.8	8.3	
40.0					25.1	24.7	24.4	24.0	23.8	23.4	23.3	23.5	21.0	18.5	16.0	13.0	10.8	8.1	
42.0						23.1	22.8	22.4	22.2	21.8	21.7	21.8	21.0	18.5	16.0	13.0	10.7	8.0	
44.0							21.4	21.0	20.7	20.4	20.3	20.4	19.7	18.5	16.0	13.0	10.6	7.9	
46.0							20.2	19.7	19.4	19.1	19.0	19.1	18.4	17.9	16.0	13.0	10.5	7.8	
48.0								18.6	18.3	17.9	17.8	17.9	17.2	16.7	16.0	13.0	10.5	7.6	
50.0									17.3	16.9	16.7	16.8	16.1	15.6	15.9	13.0	10.4	7.5	
54.0										15.1	14.9	14.9	14.3	13.7	14.0	13.0	10.2	7.2	
58.0											13.9/57m	13.4	12.7	12.1	12.4	12.3	10.0	6.9	
62.0												12.1	11.3	10.7	11.0	10.9	9.8	6.6	
66.0													10.2	9.6	9.8	9.7	9.6	6.3	
70.0													9.8/68m	8.6	8.8	8.7	9.0	6.1	
74.0														7.8	7.9	7.8	8.0	5.8	
78.0															7.1	7.0	7.2	5.6	
80.0															6.8	6.6	6.8	5.5	
82.0																6.3	6.5	5.4	
86.0																5.8/85m	5.8	5.2	
90.0																	5.2	5.0	
94.0																	5.1/91m	4.5	
98.0																		4.2/97m	
(°)	13~63	21~64	12~69	19~71	11~71	17~71	10~71	16~72	19~72	15~72	14~72	17~73	16~73	16~72	15~73	17~73	16~73	16~73	
条数	7	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2	2	
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	73041	73042	

主ジブ長さ+アダプタ長さ 40.5m+4.0m

単位 : t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	78.0#	84.0#	90.0#	96.0#	
16.0	65.5/17m	60.4/17m	56.0/17m	48.8/17m															
18.0	65.5	60.3	56.0	48.8	43.0	38.9/19m													
20.0	63.0	60.1	56.0	48.8	43.0	38.9	35.5	32.1	29.2/21m										
22.0	57.0	56.8	55.0	48.8	43.0	38.9	35.5	32.1	29.2	27.2	25.2/23m								
24.0	50.5	50.3	50.0	47.7	43.0	38.9	35.5	32.1	29.2	27.2	25.2	21.9							
26.0	45.0	45.0	44.5	44.4	42.0	38.8	35.5	32.1	29.2	27.2	25.2	21.9	17.0						
28.0	41.0	40.7	40.5	40.0	40.0	38.4	35.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6/29m				
30.0		37.1	36.5	36.4	36.5	36.2	35.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0/31m			
32.0			33.5	33.3	33.5	33.1	32.5	32.0	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0	8.3/33m		
34.0			31.0	30.6	30.5	30.4	30.0	29.8	29.2	27.1	25.2	21.9	17.0	14.3	12.5	10.0	8.3	6.4/35m	
36.0				28.4	28.5	28.1	27.8	27.5	27.2	26.9	25.1	21.9	17.0	14.3	12.5	10.0	8.3	6.3	
38.0					26.5	26.1	25.8	25.5	25.2	24.8	24.8	21.9	17.0	14.3	12.4	10.0	8.2	6.2	
40.0					24.8	24.3	24.0	23.7	23.4	23.0	23.0	21.9	17.0	14.3	12.4	10.0	8.2	6.1	
42.0						22.8	22.5	22.1	21.8	21.4	21.4	21.5	17.0	14.3	12.4	10.0	8.2	5.9	
44.0							21.1	20.7	20.4	20.0	19.9	20.1	17.0	14.3	12.4	10.0	8.1	5.8	
46.0							19.8	19.4	19.1	18.7	18.6	18.8	17.0	14.3	12.4	10.0	8.1	5.7	
48.0								18.3	18.0	17.6	17.5	17.6	16.9	14.3	12.4	10.0	8.1	5.6	
50.0									17.0	16.5	16.4	16.5	15.9	14.3	12.4	10.0	8.0	5.5	
54.0										14.8	14.6	14.7	14.0	13.4	12.4	10.0	8.0	5.3	
58.0											13.2	13.1	12.4	11.8	12.1	10.0	7.9	5.1	
62.0												11.8	11.1	10.5	10.8	10.0	7.8	4.9	
66.0													10.0	9.3	9.6	9.5	7.7	4.7	
70.0													9.1	8.4	8.6	8.5	7.6	4.6	
74.0														7.6	7.7	7.6	7.4	4.4	
78.0															6.9	6.8	7.0	4.3	
82.0															6.4/81m	6.1	6.3	4.2	
86.0																5.5	5.6	4.1	
90.0																	5.1	4.0	
92.0																	4.8	3.9	
94.0																		3.9	
98.0																		3.8	
(°)	19~62	24~66	17~68	22~70	15~72	20~70	14~70	19~72	22~72	17~72	12~72	19~72	11~72	17~72	14~73	16~73	15~72	15~72	
条数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	73041	73042	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 45.5m+4.0m**

単位 :t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0	78.0	84.0*	90.0*	96.0#	
18.0	52.0/19m	48.4/19m	45.0/19m	40.1															
20.0	51.5	48.3	45.0	40.1	36.0	32.7	30.0/21m												
22.0	49.5	47.2	45.0	40.1	36.0	32.7	30.0	27.8	26.0	24.5/23m									
24.0	47.0	45.1	43.5	39.9	36.0	32.7	30.0	27.8	26.0	24.5	23.0								
26.0	44.5	43.3	41.5	38.9	35.5	32.7	30.0	27.8	26.0	24.5	23.0	19.0	14.7/27m						
28.0	40.5	40.2	40.0	38.0	35.0	32.6	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5/29m					
30.0		36.6	36.0	35.9	35.0	32.4	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5	10.6				
32.0		33.6	33.0	32.8	33.0	32.3	30.0	27.8	25.9	24.5	23.0	19.0	14.7	11.5	10.5	8.0/33m			
34.0			30.5	30.2	30.0	30.1	29.8	27.7	25.9	24.4	23.0	19.0	14.7	11.5	10.4	8.0	6.5/35m		
36.0				28.0	28.1	27.8	27.5	27.1	25.8	24.4	23.0	19.0	14.7	11.5	10.3	8.0	6.5	4.9	
38.0				26.0	26.1	25.7	25.5	25.1	24.8	24.3	22.9	19.0	14.7	11.5	10.2	8.0	6.5	4.8	
40.0				24.4	24.0	23.7	23.3	23.1	22.7	22.6	19.0	14.7	11.5	10.2	8.0	6.5	4.6		
42.0					22.4	22.1	21.7	21.5	21.1	21.0	19.0	14.7	11.5	10.1	8.0	6.5	4.5		
44.0					21.1	20.7	20.3	20.1	19.7	19.6	19.0	14.7	11.5	10.0	8.0	6.5	4.4		
46.0						19.5	19.1	18.8	18.4	18.3	18.5	14.7	11.5	10.0	8.0	6.5	4.3		
48.0							18.0	17.7	17.3	17.1	17.3	14.7	11.5	10.0	8.0	6.5	4.2		
50.0							17.0	16.6	16.2	16.1	16.2	14.7	11.5	10.0	8.0	6.5	4.1		
54.0									14.5	14.3	14.4	13.7	11.5	10.0	8.0	6.5	3.9		
58.0										12.9	12.8	12.1	11.5	10.0	8.0	6.5	3.8		
62.0												11.6	10.8	10.2	10.0	8.0	6.5	3.7	
66.0													9.7	9.1	9.4	8.0	6.5	3.6	
70.0													8.8	8.1	8.3	8.0	6.5	3.5	
74.0														7.3	7.5	7.4	6.5	3.5	
78.0															6.7	6.6	6.5	3.4	
82.0															6.1	5.9	6.1	3.4	
86.0																5.3	5.5	3.3	
90.0																	4.9	3.3	
94.0																	4.4	3.2	
98.0																		3.0	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~70	19~72	13~72	18~72	12~72	16~72	
索数	4	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	73041	73042	

**主ジブ長さ+アダプタ長さ 50.5m+4.0m**

単位 :t

作業半径 (m)	補ジブ長さ(m)																	
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	78.0#	84.0#		
18.0	38.0/19m		33.0/19m	29.9/19m														
20.0	38.0	35.0	32.5	29.7	26.6	24.1/21m												
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m										
24.0	36.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m							
26.0	36.0	33.6	31.0	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5						
28.0	35.0	33.3	31.0	28.5	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3					
30.0	34.5	32.7	31.0	28.4	26.2	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8				
32.0		32.2	30.5	28.2	26.1	24.0	22.1	21.0	20.1	18.6	17.1	13.5	10.3	7.8	6.6			
34.0			30.0	28.0	25.9	23.9	22.1	20.9	20.0	18.6	17.1	13.5	10.3	7.8	6.5	4.8		
36.0			28.3	27.6	25.8	23.8	22.1	20.8	19.8	18.5	17.0	13.5	10.3	7.8	6.5	4.8		
38.0				25.7	25.7	23.8	22.1	20.7	19.6	18.4	17.0	13.5	10.3	7.8	6.5	4.8		
40.0					24.1	23.7	22.1	20.6	19.5	18.3	17.0	13.5	10.3	7.8	6.4	4.8		
42.0					22.6	22.1	21.8	20.5	19.3	18.2	17.0	13.5	10.3	7.8	6.4	4.8		
44.0						20.8	20.4	20.1	19.1	18.1	17.0	13.5	10.3	7.8	6.3	4.8		
46.0							19.2	18.8	18.5	18.0	17.0	13.5	10.3	7.8	6.3	4.8		
48.0							18.2	17.7	17.4	17.0	16.9	13.5	10.3	7.8	6.3	4.8		
50.0								16.7	16.4	16.0	15.8	13.5	10.3	7.8	6.3	4.8		
54.0									14.7	14.2	14.1	13.5	10.3	7.8	6.3	4.8		
58.0											12.6	12.6	10.3	7.8	6.3	4.8		
62.0												11.3	10.3	7.8	6.3	4.8		
66.0												10.4	9.5	7.8	6.3	4.8		
70.0													8.6	7.8	6.3	4.8		
74.0														7.1	6.3	4.8		
78.0															6.7/77m	6.3	4.8	
82.0																5.9	4.8	
86.0																	4.8	
(°)	11~60	20~61	10~67	18~69	9~69	16~69	8~69	15~69	7~69	22~71	17~71	6~72	16~72	11~71	14~71	19~71		
索数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s



TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	78.0#	84.0#	
20.0	31.0/21m	28.0/21m	25.5/21m	22.5													
22.0	31.0	28.0	25.5	22.6	20.0	18.1											
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m							
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m						
28.0	28.8	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m				
30.0	28.1	26.1	24.3	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0				
32.0		25.6	23.9	21.9	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0	3.3/33m		
34.0			23.5	21.7	20.0	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	3.3	2.0/35m	
36.0			23.2	21.6	20.0	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	3.3	2.0	
38.0				21.4	20.0	18.1	16.6	16.0	15.7	14.5	12.9	9.5	7.0	5.0	3.3	2.0	
40.0					20.0	18.1	16.6	15.8	15.5	14.3	12.9	9.5	7.0	5.0	3.3	2.0	
42.0					20.0	18.1	16.6	15.7	15.2	14.2	12.9	9.5	7.0	5.0	3.3	2.0	
44.0						18.1	16.6	15.6	15.0	14.1	12.9	9.5	7.0	5.0	3.3	2.0	
46.0							16.6	15.5	14.8	13.9	12.9	9.5	7.0	5.0	3.3	2.0	
48.0							16.6	15.4	14.6	13.8	12.9	9.5	7.0	5.0	3.3	2.0	
50.0								15.4	14.5	13.7	12.8	9.5	7.0	5.0	3.3	2.0	
54.0									14.3	13.6	12.7	9.5	7.0	5.0	3.3	2.0	
58.0											12.4	9.5	7.0	5.0	3.3	2.0	
62.0												9.5	7.0	5.0	3.3	2.0	
66.0												9.5	7.0	5.0	3.3	2.0	
70.0													7.0	5.0	3.3	2.0	
74.0														5.0	3.3	2.0	
78.0														5.0	3.3	2.0	
82.0															3.3	2.0	
86.0																2.0	
90.0																2.0	
(°)	18~56	24~60	16~64	21~68	14~67	19~69	13~67	18~69	12~68	24~70	20~69	11~70	18~71	10~70	16~71	9~71	
条数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	73030	73043	73031	73044	73032	73045	73033	73046	73034	73047	73035	73036	73037	73038	73039	73040	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 15.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																			単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	90.0*	96.0#		
12.0	123.0	114.0/13m	105.0/13m	98.8/13m																
14.0	104.0	104.0	103.0	97.7	89.0	81.4	73.0/15m													
16.0	84.0	84.3	83.5	83.8	83.5	80.8	73.0	67.0	60.5/17m	56.3/17m										
18.0	70.5	70.6	70.0	70.0	70.0	69.9	69.5	66.8	60.5	56.3	52.0									
20.0	60.5	60.5	60.0	60.0	60.0	59.9	59.5	59.4	59.0	56.3	52.0	42.0								
22.0	53.0	52.9	52.5	52.3	52.0	52.2	51.5	51.6	51.0	51.1	51.0	42.0	35.5	30.5/23m						
24.0	50.0/23m	46.8	46.5	46.2	46.0	46.1	45.5	45.6	45.0	45.0	44.5	42.0	35.0	30.0	24.5/25m					
26.0		42.0	41.5	41.4	41.0	41.2	40.5	40.6	40.0	40.1	40.0	40.0	34.5	30.0	24.3	19.9/27m				
28.0		40.0/27m	37.5	37.3	37.0	37.1	36.5	36.6	36.0	36.0	35.5	36.0	34.0	30.0	23.9	19.7	16.0			
30.0			34.0	34.0	34.0	33.7	33.0	33.2	32.5	32.6	32.5	32.0	30.0	23.5	19.3	15.6	13.0			
32.0				31.1	31.0	30.9	30.5	30.3	30.0	29.7	29.6	29.7	29.1	28.6	23.1	19.0	15.3	12.5		
34.0				29.9/33m	28.6	28.4	28.0	27.8	27.5	27.2	27.1	27.2	26.6	26.1	22.8	18.6	14.9	12.0		
36.0					26.5	26.2	25.8	25.7	25.3	25.1	24.9	25.0	24.4	23.9	22.4	18.3	14.6	11.6		
38.0						24.4	24.0	23.8	23.4	23.2	23.0	23.1	22.5	22.0	22.1	17.9	14.3	11.2		
40.0						23.6/39m	22.3	22.1	21.7	21.5	21.3	21.4	20.8	20.2	20.5	17.5	14.0	10.9		
42.0							20.9	20.6	20.2	20.0	19.8	19.9	19.3	18.7	19.0	17.2	13.7	10.6		
44.0								19.3	18.9	18.7	18.5	18.5	17.9	17.4	17.6	16.8	13.4	10.3		
46.0								18.8/45m	17.8	17.5	17.3	17.3	16.7	16.2	16.4	16.4	13.1	10.0		
48.0									17.2/47m	16.5	16.2	16.2	15.6	15.1	15.3	15.3	12.8	9.7		
50.0										15.5	15.3	15.2	14.6	14.1	14.3	14.2	12.5	9.5		
54.0											14.0/53m	13.5	12.9	12.3	12.5	12.5	12.0	9.0		
58.0												12.1	11.4	10.8	11.0	11.0	11.2	8.7		
62.0													10.2	9.6	9.8	9.7	9.9	8.4		
66.0													9.5/65m	8.6	8.7	8.6	8.8	8.1		
70.0														7.7	7.7	7.6	7.8	7.7		
74.0															6.9	6.8	7.0	6.8		
76.0															6.6	6.5	6.6	6.4		
78.0																6.1	6.2	6.1		
82.0																5.5	5.5	5.4		
86.0																	4.9	4.8		
88.0																	4.7	4.5		
90.0																		4.2		
94.0																			3.9/93m	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	20~74	19~74	18~73	18~74	19~74		
索数	10	9	9	8	7	7	6	6	5	5	4	4	3	3	2	2	2	2		
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00		
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040	74041	74042		

主ジブ長さ+アダプタ長さ 20.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																			単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0*	96.0#		
12.0	116.0/13m	109.0/13m	100.0/13m	89.9/13m																
14.0	102.0	102.0	98.5	89.2	78.5	71.0/15m														
16.0	82.5	82.7	82.0	82.1	77.5	70.9	63.5	57.8	52.0/17m											
18.0	69.0	69.2	68.5	68.6	68.5	68.5	63.5	57.8	52.0	48.1	44.0/19m									
20.0	59.5	59.3	59.0	58.7	58.5	58.6	58.0	57.7	52.0	48.1	44.0	37.0								
22.0	52.0	51.8	51.5	51.2	51.0	51.0	50.5	50.5	50.0	48.1	44.0	37.0	30.0							
24.0	46.0	45.8	45.5	45.2	45.0	45.1	44.5	44.5	44.0	44.0	43.5	37.0	30.0	25.9						
26.0	41.0	41.1	40.5	40.4	40.5	40.3	40.0	39.7	39.0	39.2	39.0	37.0	29.9	25.8	21.7	17.6/27m				
28.0		37.1	36.5	36.5	36.5	36.3	36.0	35.7	35.5	35.2	35.0	35.0	29.7	25.7	21.5	17.5	14.0/29m			
30.0			33.5	33.2	33.0	32.9	32.5	32.4	32.0	31.8	31.5	31.5	29.5	25.7	21.3	17.4	13.8	11.1/31m		
32.0			32.0/31m	30.4	30.0	30.1	29.8	29.5	29.2	29.0	28.8	29.0	28.4	25.6	21.2	17.2	13.6	10.9		
34.0				28.0	27.9	27.7	27.3	27.1	26.8	26.5	26.3	26.5	25.9	25.4	21.0	17.0	13.3	10.6		
36.0					25.8	25.6	25.2	25.0	24.6	24.4	24.2	24.3	23.7	23.2	20.8	16.8	13.1	10.4		
38.0					24.9/37m	23.7	23.3	23.1	22.8	22.5	22.3	22.4	21.8	21.3	20.6	16.6	12.8	10.1		
40.0						22.2	21.7	21.5	21.1	20.9	20.7	20.8	20.2	19.6	19.9	16.3	12.6	9.8		
42.0							20.3	20.1	19.7	19.4	19.2	19.3	18.7	18.1	18.4	16.0	12.3	9.6		
44.0							19.7/43m	18.8	18.4	18.1	17.9	18.0	17.3	16.8	17.1	15.7	12.1	9.3		
46.0								18.2/45m	17.2	17.0	16.7	16.8	16.2	15.6	15.9	15.4	11.9	9.1		
48.0									16.2	15.9	15.7	15.7	15.1	14.5	14.8	14.8	11.6	8.9		
50.0										15.0	14.7	14.7	14.1	13.6	13.8	13.8	11.4	8.7		
54.0											13.1	12.4	11.8	12.1	12.0	11.0	8.3			
58.0												11.7	11.0	10.4	10.6	10.6	10.5	7.9		
62.0												11.1/60m	9.8	9.2	9.4	9.3	9.6	7.6		
66.0													9.1/65m	8.2	8.3	8.2	8.5	7.3		
70.0														7.3	7.4	7.3	7.5	7.0		
74.0															7.1/71m	6.6	6.7	6.5		
78.0																6.1/77m	5.8	5.9	5.8	
82.0																	5.2	5.3	5.1	
86.0																	5.1/83m	4.7	4.5	
90.0																		4.4/88m	4.0	
94.0																			3.4	
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	21~73	18~73	20~74	19~74	18~73		
索数	9	9	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2		
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02		
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040	74041	74042		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 25.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0#	96.0#	
14.0	100.0	100.0	92.5	83.6	76.0/15m														
16.0	81.0	81.1	80.5	80.5	76.0	67.5	60.5/17m	54.2/17m											
18.0	68.0	67.8	67.5	67.2	67.0	67.1	60.5	54.2	49.0	45.0/19m									
20.0	58.0	58.1	57.5	57.5	57.5	57.4	57.0	54.2	49.0	45.0	41.0	36.0/21m							
22.0	50.5	50.7	50.5	50.1	50.0	50.0	49.5	49.4	49.0	45.0	41.0	36.0	28.0/23m						
24.0	45.0	44.9	44.5	44.2	44.0	44.1	43.5	43.6	43.0	43.0	41.0	36.0	28.0	24.0/25m					
26.0	40.5	40.2	39.5	39.5	39.5	39.4	39.0	38.8	38.5	38.3	38.0	36.0	28.0	24.0	21.0				
28.0		36.3	36.0	35.6	35.5	35.5	35.0	34.9	34.5	34.3	34.0	34.0	28.0	24.0	21.0	17.0			
30.0		34.7/29m	32.5	32.4	32.0	32.2	31.5	31.6	31.0	31.0	30.5	31.0	28.0	24.0	21.0	16.9	13.5		
32.0			30.0	29.6	29.6	29.4	29.0	28.8	28.5	28.2	28.1	28.2	27.6	24.0	21.0	16.9	13.3	10.4	
34.0				27.3	27.2	27.0	26.6	26.4	26.1	25.8	25.6	25.8	25.2	24.0	21.0	16.8	13.1	10.3	
36.0				26.3/35m	25.2	24.9	24.5	24.3	24.0	23.7	23.5	23.7	23.1	22.5	21.0	16.7	12.9	10.1	
38.0					23.4	23.1	22.7	22.5	22.1	21.9	21.7	21.8	21.2	20.7	21.0	16.6	12.7	9.9	
40.0						21.6	21.1	20.9	20.5	20.3	20.1	20.2	19.6	19.0	19.4	16.6	12.5	9.7	
42.0						20.9/41m	19.7	19.5	19.1	18.9	18.6	18.7	18.1	17.6	17.9	16.5	12.3	9.5	
44.0							19.1/43m	18.2	17.8	17.6	17.4	17.4	16.8	16.3	16.6	16.2	12.1	9.3	
46.0								17.1	16.7	16.4	16.2	16.3	15.6	15.1	15.4	15.3	11.9	9.1	
48.0									15.7	15.4	15.2	15.2	14.6	14.0	14.3	14.3	11.7	9.0	
50.0									15.2/49m	14.5	14.3	14.3	13.6	13.1	13.4	13.3	11.5	8.8	
54.0										13.8/52m	12.7	12.6	12.0	11.4	11.7	11.6	11.1	8.4	
58.0												11.3	10.6	10.0	10.2	10.2	10.5	8.0	
62.0													10.4/61m	9.4	8.8	9.0	8.9	7.6	
66.0														8.4	7.8	8.0	7.9	7.2	
70.0															6.9	7.0	7.0	6.9	
72.0															6.6	6.7	6.6	6.5	
74.0																6.3	6.2	6.2	
78.0																5.6	5.5	5.5	
82.0																	4.9	4.8	
86.0																	4.7/83m	4.4	
90.0																	4.0/89m	3.7	
94.0																		3.1	
96.0																		3/95m	
(°)	21~66	19~68	18~71	17~73	16~72	16~72	20~72	19~73	19~73	18~73	21~73	16~73	19~73	18~73	17~74	19~73	18~73	18~73	
条数	8	8	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040	74041	74042	

主ジブ長さ+アダプタ長さ 30.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0*	90.0#	96.0#	
14.0	89.5/15m	88.4/15m	80.5/15m	70.5/15m															
16.0	80.0	80.0	79.5	70.2	62.0	55.5/17m													
18.0	67.0	66.9	66.5	66.2	62.0	55.5	50.0	44.6	40.0/19m										
20.0	57.5	57.3	57.0	56.6	56.5	55.5	50.0	44.6	40.0	36.9	33.5/21m								
22.0	50.0	49.9	49.5	49.3	49.0	49.2	48.5	44.6	40.0	36.9	33.5	30.0							
24.0	44.0	44.2	43.5	43.5	43.5	43.4	43.0	42.8	40.0	36.9	33.5	30.0	23.3						
26.0	39.5	39.5	39.0	38.9	39.0	38.7	38.0	38.2	37.5	36.9	33.5	30.0	23.3	20.2	17.6/27m				
28.0		35.7	35.0	35.0	35.0	34.9	34.5	34.3	34.0	33.7	33.5	30.0	23.3	20.2	17.6	14.2/29m			
30.0		32.5	32.0	31.8	31.5	31.6	31.0	31.0	30.5	30.5	30.0	30.0	23.3	20.2	17.6	14.2	11.6/31m		
32.0			29.5	29.1	29.1	28.9	28.5	28.3	27.9	27.7	27.5	27.7	23.3	20.2	17.6	14.2	11.6	9/33m	
34.0				26.7	26.7	26.5	26.1	25.9	25.5	25.3	25.1	25.3	23.3	20.2	17.6	14.2	11.4	8.9	
36.0				24.8	24.7	24.5	24.1	23.9	23.5	23.3	23.0	23.2	22.6	20.2	17.6	14.1	11.3	8.8	
38.0					22.9	22.7	22.3	22.1	21.7	21.4	21.2	21.4	20.7	20.2	17.6	14.1	11.2	8.6	
40.0						21.1	20.7	20.5	20.1	19.9	19.6	19.8	19.1	18.6	17.5	14.1	11.1	8.5	
42.0						19.8	19.3	19.1	18.7	18.4	18.2	18.3	17.7	17.1	17.5	14.0	10.9	8.3	
44.0							18.1	17.8	17.4	17.2	16.9	17.0	16.4	15.9	16.2	13.9	10.8	8.2	
46.0								16.7	16.3	16.0	15.8	15.9	15.3	14.7	15.0	13.8	10.7	8.0	
48.0								16.2/47m	15.3	15.0	14.8	14.9	14.2	13.7	14.0	13.7	10.5	7.9	
50.0									14.4	14.1	13.9	13.9	13.3	12.7	13.0	12.9	10.4	7.7	
54.0										13.0/53m	12.3	12.3	11.6	11.1	11.3	11.3	10.1	7.4	
58.0												10.9	10.2	9.7	9.9	9.8	9.8	7.1	
62.0													10.1/61m	9.1	8.5	8.7	8.6	6.8	
66.0														8.1	7.5	7.7	7.6	6.5	
70.0															6.7	6.8	6.7	6.2	
74.0															6.1/73m	6.0	5.9	5.9	
78.0																5.4	5.2	5.3	
82.0																	4.6	4.6	
84.0																	4.4	4.5	
86.0																		4.2	
90.0																		3.7	
94.0																		2.9	
96.0																		2.6	
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	18~73	20~73	17~73	19~73	18~73	17~73	17~73	
条数	7	7	7	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2	
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040	74041	74042	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0#	90.0#	96.0#	
16.0	78.5	72.4/17m	67.5	60.2	54.5/17m														
18.0	66.0	65.9	65.5	59.9	54.5	49.3	45.0/19m	39.8/19m											
20.0	56.5	56.4	56.0	55.8	54.5	49.3	45.0	39.8	35.5	32.8/21m									
22.0	49.0	49.2	48.5	48.5	48.5	48.4	45.0	39.8	35.5	32.8	30.0	27.0/23m							
24.0	43.5	43.5	43.0	42.8	43.0	42.7	42.0	39.8	35.5	32.8	30.0	27.0	21.0/25m						
26.0	39.0	38.9	38.5	38.2	38.0	38.1	37.5	37.5	35.5	32.8	30.0	27.0	21.0	18.5/27m					
28.0	35.0	35.1	34.5	34.4	34.5	34.3	33.5	33.7	33.0	32.8	30.0	27.0	21.0	18.5	16.0				
30.0		31.9	31.5	31.2	31.0	31.1	30.5	30.5	30.0	29.9	29.7	27.0	21.0	18.5	16.0	13.0			
32.0			28.9	28.5	28.6	28.3	28.0	27.7	27.4	27.1	27.0	27.0	21.0	18.5	16.0	13.0	11.0		
34.0			26.7	26.2	26.2	26.0	25.6	25.4	25.0	24.8	24.6	24.8	21.0	18.5	16.0	13.0	10.9	8.5	
36.0				24.3	24.2	24.0	23.6	23.4	23.0	22.8	22.5	22.7	21.0	18.5	16.0	13.0	10.9	8.4	
38.0					22.5	22.2	21.8	21.6	21.2	21.0	20.7	20.9	20.3	18.5	16.0	13.0	10.8	8.3	
40.0					21.0	20.7	20.2	20.0	19.6	19.4	19.2	19.3	18.7	18.1	16.0	13.0	10.8	8.1	
42.0						19.3	18.9	18.6	18.2	18.0	17.8	17.9	17.3	16.7	16.0	13.0	10.7	8.0	
44.0							17.6	17.4	17.0	16.8	16.5	16.6	16.0	15.4	15.8	13.0	10.6	7.9	
46.0							16.6	16.3	15.9	15.6	15.4	15.5	14.9	14.3	14.6	13.0	10.5	7.8	
48.0								15.4	14.9	14.6	14.4	14.5	13.8	13.3	13.6	13.0	10.5	7.6	
50.0									14.0	13.7	13.5	13.6	12.9	12.3	12.7	12.6	10.4	7.5	
54.0										12.2	11.9	11.9	11.3	10.7	11.0	10.9	10.2	7.2	
58.0											11.0/57m	10.6	9.9	9.3	9.6	9.5	9.9	6.9	
62.0												9.5	8.8	8.2	8.4	8.3	8.7	6.6	
66.0													7.8	7.2	7.4	7.3	7.6	6.3	
70.0													7.5/68m	6.4	6.5	6.4	6.7	6.1	
74.0														5.7	5.8	5.7	5.9	5.7	
78.0															5.1	5.0	5.2	5.0	
80.0															4.9	4.7	4.9	4.7	
82.0																4.4	4.6	4.4	
86.0																4.0/85m	4.0	3.8	
90.0																	3.4	3.2	
94.0																	3.3/91m	2.6	
98.0																		2.3/97m	
(°)	13~63	21~64	12~69	19~71	11~71	17~71	10~71	16~72	19~72	15~72	14~72	17~73	16~73	16~72	15~73	17~73	16~73	16~73	
条数	6	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2	2	
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040	74041	74042	

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	78.0#	84.0#	90.0#	96.0#	
16.0	65.5/17m	60.4/17m	56.0/17m	48.8/17m															
18.0	65.0	60.3	56.0	48.8	43.0	38.9/19m													
20.0	56.0	55.8	55.5	48.8	43.0	38.9	35.5	32.1	29.2/21m										
22.0	48.5	48.6	48.0	47.9	43.0	38.9	35.5	32.1	29.2	27.2	25.2/23m								
24.0	43.0	42.9	42.5	42.3	42.0	38.9	35.5	32.1	29.2	27.2	25.2	21.9							
26.0	38.5	38.4	38.0	37.7	37.5	37.6	35.5	32.1	29.2	27.2	25.2	21.9	17.0						
28.0	34.5	34.6	34.0	33.9	34.0	33.8	33.5	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6/29m				
30.0		31.5	31.0	30.8	30.5	30.6	30.0	30.0	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0/31m			
32.0			28.5	28.1	28.2	27.9	27.5	27.3	27.0	26.7	25.2	21.9	17.0	14.3	12.6	10.0	8.3/33m		
34.0			26.2	25.8	25.9	25.6	25.2	25.0	24.6	24.4	24.2	21.9	17.0	14.3	12.5	10.0	8.3	6.4/35m	
36.0				23.8	23.8	23.6	23.2	23.0	22.6	22.4	22.1	21.9	17.0	14.3	12.5	10.0	8.3	6.3	
38.0					22.1	21.9	21.4	21.2	20.8	20.6	20.4	20.5	17.0	14.3	12.4	10.0	8.2	6.2	
40.0					20.6	20.3	19.9	19.7	19.3	19.0	18.8	19.0	17.0	14.3	12.4	10.0	8.2	6.1	
42.0						19.0	18.5	18.3	17.9	17.7	17.4	17.6	16.9	14.3	12.4	10.0	8.2	5.9	
44.0							17.3	17.1	16.7	16.4	16.2	16.3	15.7	14.3	12.4	10.0	8.1	5.8	
46.0							16.3	16.0	15.6	15.3	15.1	15.2	14.5	14.0	12.4	10.0	8.1	5.7	
48.0								15.0	14.6	14.3	14.1	14.2	13.5	13.0	12.4	10.0	8.1	5.6	
50.0									13.7	13.4	13.2	13.3	12.6	12.0	12.4	10.0	8.0	5.5	
54.0										11.9	11.6	11.7	11.0	10.4	10.7	10.0	8.0	5.3	
58.0											10.4	10.4	9.7	9.1	9.4	9.3	7.9	5.1	
62.0												9.3	8.5	7.9	8.2	8.1	7.8	4.9	
66.0													7.6	7.0	7.2	7.1	7.4	4.7	
70.0													6.8	6.1	6.3	6.2	6.5	4.6	
74.0														5.5	5.6	5.5	5.7	4.4	
78.0															4.9	4.8	5.0	4.3	
82.0															4.5/81m	4.2	4.4	4.2	
86.0																3.6	3.8	3.5	
90.0																	3.2	3.0	
92.0																	3.0	2.7	
94.0																		2.4	
(°)	19~62	24~66	17~68	22~70	15~72	20~70	14~70	19~72	22~72	17~72	12~72	19~72	11~72	17~72	14~73	16~73	15~72	23~72	
条数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040	74041	74042	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 45.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																		単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0	78.0	84.0*	90.0*	96.0#	
18.0	52.0/19m	48.4/19m	45.0/19m	40.1															
20.0	51.5	48.3	45.0	40.1	36.0	32.7	30.0/21m												
22.0	48.0	47.2	45.0	40.1	36.0	32.7	30.0	27.8	26.0	24.5/23m									
24.0	42.5	42.4	42.0	39.9	36.0	32.7	30.0	27.8	26.0	24.5	23.0								
26.0	38.0	37.9	37.5	37.2	35.5	32.7	30.0	27.8	26.0	24.5	23.0	19.0	14.7/27m						
28.0	34.0	34.1	33.5	33.4	33.5	32.6	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5/29m					
30.0		31.0	30.5	30.3	30.0	30.2	29.8	27.8	26.0	24.5	23.0	19.0	14.7	11.5	10.6				
32.0		28.4	28.1	27.7	27.8	27.5	27.1	26.9	25.9	24.5	23.0	19.0	14.7	11.5	10.5	8.0/33m			
34.0			25.8	25.4	25.5	25.2	24.8	24.6	24.2	24.0	23.0	19.0	14.7	11.5	10.4	8.0	6.5/35m		
36.0				23.4	23.5	23.2	22.8	22.6	22.2	22.0	21.7	19.0	14.7	11.5	10.3	8.0	6.5	4.9	
38.0				21.8	21.7	21.5	21.1	20.9	20.4	20.2	20.0	19.0	14.7	11.5	10.2	8.0	6.5	4.8	
40.0					20.2	20.0	19.5	19.3	18.9	18.7	18.4	18.6	14.7	11.5	10.2	8.0	6.5	4.6	
42.0						18.6	18.2	18.0	17.5	17.3	17.1	17.2	14.7	11.5	10.1	8.0	6.5	4.5	
44.0						17.5	17.0	16.7	16.3	16.1	15.8	16.0	14.7	11.5	10.0	8.0	6.5	4.4	
46.0							15.9	15.7	15.2	15.0	14.7	14.9	14.2	11.5	10.0	8.0	6.5	4.3	
48.0								14.7	14.3	14.0	13.7	13.9	13.2	11.5	10.0	8.0	6.5	4.2	
50.0								13.9	13.4	13.1	12.9	13.0	12.3	11.5	10.0	8.0	6.5	4.1	
54.0										11.6	11.3	11.4	10.7	10.1	10.0	8.0	6.5	3.9	
58.0											10.1	10.1	9.4	8.8	9.1	8.0	6.5	3.8	
62.0												9.0	8.3	7.7	8.0	7.9	6.5	3.7	
66.0													7.3	6.7	7.0	6.9	6.5	3.6	
70.0													6.6	5.9	6.1	6.0	6.3	3.5	
74.0														5.2	5.4	5.2	5.5	3.5	
78.0															4.7	4.6	4.9	3.4	
82.0															4.1	3.9	4.2	3.4	
86.0																3.3	3.6	3.3	
90.0																	3.0	2.7	
94.0																		2.5	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~70	19~72	13~72	18~72	12~72	23~72	
条数	4	4	4	3	3	3	3	3	3	2	2	2	2	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040	74041	74042	

**主ジブ長さ+アダプタ長さ 50.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																	単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	78.0#	84.0#		
18.0	38.0/19m		33.0/19m	29.9/19m														
20.0	38.0	35.0	32.5	29.7	26.6	24.1/21m												
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m										
24.0	36.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m							
26.0	36.0	33.6	31.0	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5						
28.0	34.0	33.3	31.0	28.5	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3					
30.0	31.0	30.7	30.0	28.4	26.2	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8				
32.0		28.1	27.7	27.3	26.1	24.0	22.1	21.0	20.1	18.6	17.1	13.5	10.3	7.8	6.6			
34.0			25.5	25.1	25.2	23.9	22.1	20.9	20.0	18.6	17.1	13.5	10.3	7.8	6.5	4.8		
36.0			23.6	23.1	23.2	22.9	22.1	20.8	19.8	18.5	17.0	13.5	10.3	7.8	6.5	4.8		
38.0				21.4	21.5	21.2	20.8	20.6	19.6	18.4	17.0	13.5	10.3	7.8	6.5	4.8		
40.0					20.0	19.7	19.2	19.0	18.6	18.3	17.0	13.5	10.3	7.8	6.4	4.8		
42.0					18.7	18.4	17.9	17.7	17.3	17.0	16.8	13.5	10.3	7.8	6.4	4.8		
44.0						17.2	16.7	16.5	16.0	15.8	15.6	13.5	10.3	7.8	6.3	4.8		
46.0							15.6	15.4	15.0	14.7	14.5	13.5	10.3	7.8	6.3	4.8		
48.0							14.8	14.4	14.0	13.7	13.5	13.5	10.3	7.8	6.3	4.8		
50.0								13.6	13.1	12.9	12.6	12.7	10.3	7.8	6.3	4.8		
54.0									11.7	11.4	11.1	11.2	10.3	7.8	6.3	4.8		
58.0										9.9	9.9	9.2	7.8	6.3	4.8			
62.0											8.8	8.1	7.5	6.3	4.8			
66.0											8.0	7.1	6.5	6.3	4.8			
70.0												6.4	5.7	5.9	4.8			
74.0													5.0	5.2	4.8			
78.0														4.7/77m	4.5	4.4		
82.0															3.9	3.7		
86.0																3.1		
(°)	11~60	20~61	10~67	18~69	9~69	16~69	8~69	15~69	7~69	22~71	17~71	6~71	16~72	11~71	14~71	19~71		
条数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウェイト 80t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)															
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	78.0#	84.0#
20.0	31.0/21m	28.0/21m	25.5/21m	22.5												
22.0	31.0	28.0	25.5	22.6	20.0	18.1										
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m						
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m					
28.0	28.8	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m			
30.0	28.1	26.1	24.3	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0			
32.0		25.6	23.9	21.9	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0	3.3/33m	
34.0			23.5	21.7	20.0	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	3.3	2.0/35m
36.0			23.2	21.6	20.0	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	3.3	2.0
38.0				21.1	20.0	18.1	16.6	16.0	15.7	14.5	12.9	9.5	7.0	5.0	3.3	2.0
40.0					19.7	18.1	16.6	15.8	15.5	14.3	12.9	9.5	7.0	5.0	3.3	2.0
42.0					18.4	18.1	16.6	15.7	15.2	14.2	12.9	9.5	7.0	5.0	3.3	2.0
44.0						16.9	16.4	15.6	15.0	14.1	12.9	9.5	7.0	5.0	3.3	2.0
46.0							15.4	15.1	14.7	13.9	12.9	9.5	7.0	5.0	3.3	2.0
48.0							14.5	14.2	13.7	13.5	12.9	9.5	7.0	5.0	3.3	2.0
50.0								13.3	12.9	12.6	12.3	9.5	7.0	5.0	3.3	2.0
54.0									11.4	11.1	10.8	9.5	7.0	5.0	3.3	2.0
58.0											9.6	9.5	7.0	5.0	3.3	2.0
62.0												8.6	7.0	5.0	3.3	2.0
66.0												7.7	6.9	5.0	3.3	2.0
70.0													6.2	5.0	3.3	2.0
74.0														4.8	3.3	2.0
78.0														4.2	3.3	2.0
82.0															3.3	2.0
86.0																2.0
90.0																2.0
(°)	18~56	24~60	16~64	21~68	14~67	19~69	13~67	18~69	12~68	24~70	20~69	11~70	18~71	10~70	16~71	9~71
条数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	2
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83
DSコード	74030	74043	74031	74044	74032	74045	74033	74046	74034	74047	74035	74036	74037	74038	74039	74040

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフイングジブ)

カウンタウエイト 60t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 15.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)														
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	
12.0	115.0	101.0/13m	101.0/13m	98.8/13m											
14.0	88.5	88.5	88.0	88.0	88.0	81.4	73.0/15m								
16.0	71.5	71.5	71.0	71.0	71.0	70.9	70.5	67.0	60.5/17m	56.3/17m					
18.0	59.5	59.8	59.5	59.2	59.0	59.1	58.5	58.7	58.0	56.3	52.0				
20.0	51.0	51.2	50.5	50.6	50.5	50.5	50.0	50.0	49.5	49.5	49.0	42.0			
22.0	44.5	44.6	44.0	44.0	44.0	43.9	43.5	43.4	43.0	42.9	42.5	42.0	35.5	30.5/23m	
24.0	42.0/23m	39.5	39.0	38.9	38.5	38.7	38.0	38.2	37.5	37.7	37.0	37.5	35.0	30.0	
26.0		35.3	34.5	34.7	34.5	34.5	34.0	34.0	33.5	33.4	33.0	33.0	32.5	30.0	
28.0		33.6/27m	31.0	31.2	31.0	31.0	30.5	30.5	30.0	30.0	29.6	29.7	29.2	28.7	
30.0			28.5	28.4	28.1	28.1	27.5	27.6	27.0	27.0	26.6	26.8	26.2	25.7	
32.0				25.9	25.7	25.7	25.1	25.1	24.5	24.5	24.1	24.3	23.7	23.2	
34.0				24.9/33m	23.6	23.5	22.9	23.0	22.4	22.4	22.0	22.1	21.5	21.0	
36.0					21.8	21.7	21.1	21.1	20.6	20.6	20.2	20.3	19.7	19.2	
38.0						20.1	19.5	19.5	19.0	18.9	18.5	18.6	18.0	17.5	
40.0						19.4/39m	18.1	18.1	17.5	17.5	17.1	17.2	16.6	16.1	
42.0							16.9	16.8	16.3	16.2	15.8	15.9	15.3	14.8	
44.0								15.7	15.2	15.1	14.7	14.8	14.2	13.6	
46.0								15.2/45m	14.2	14.1	13.7	13.7	13.1	12.6	
48.0									13.8/47m	13.2	12.8	12.8	12.2	11.7	
50.0										12.3	12.0	12.0	11.3	10.8	
54.0											11.0/53m	10.5	9.9	9.3	
58.0												9.3	8.7	8.1	
62.0													7.7	7.1	
66.0													7.0/65m	6.2	
70.0														5.5	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	20~74	
条数	9	8	8	8	7	7	6	6	5	5	4	4	3	3	
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	00	
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038	

**主ジブ長さ+アダプタ長さ 20.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)														
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	
12.0	99.0/13m	98.1/13m	96.5/13m	89.9/13m											
14.0	86.5	86.6	86.0	86.0	78.5	71.0/15m									
16.0	70.0	69.9	69.5	69.4	69.0	69.3	63.5	57.8	52.0/17m						
18.0	58.5	58.4	58.0	57.8	57.5	57.7	57.0	57.2	52.0	48.1	44.0/19m				
20.0	50.0	50.0	49.5	49.4	49.5	49.3	48.5	48.8	48.0	48.1	44.0	37.0			
22.0	43.5	43.5	43.0	42.9	42.5	42.8	42.0	42.3	41.5	41.7	41.5	37.0	30.0		
24.0	38.5	38.5	38.0	37.8	37.5	37.7	37.0	37.2	36.5	36.6	36.0	36.5	30.0	25.9	
26.0	34.0	34.4	33.5	33.7	33.5	33.6	33.0	33.0	32.5	32.5	32.0	32.0	29.9	25.8	
28.0		31.0	30.5	30.4	30.0	30.2	29.6	29.6	29.1	29.1	28.7	28.9	28.3	25.7	
30.0			27.7	27.6	27.3	27.3	26.7	26.8	26.2	26.2	25.8	26.0	25.4	24.9	
32.0			26.5/31m	25.2	24.9	24.9	24.3	24.4	23.8	23.8	23.4	23.5	22.9	22.4	
34.0				23.1	22.9	22.9	22.2	22.3	21.7	21.7	21.3	21.4	20.8	20.3	
36.0					21.1	21.1	20.5	20.5	19.9	19.9	19.5	19.6	19.0	18.5	
38.0					20.3/37m	19.5	18.9	18.9	18.3	18.3	17.9	18.0	17.4	16.9	
40.0						18.1	17.5	17.5	16.9	16.9	16.5	16.6	16.0	15.5	
42.0							16.3	16.2	15.7	15.6	15.3	15.3	14.7	14.2	
44.0							15.8/43m	15.2	14.6	14.5	14.2	14.2	13.6	13.1	
46.0								14.7/45m	13.7	13.5	13.2	13.2	12.6	12.1	
48.0									12.8	12.6	12.3	12.3	11.7	11.1	
50.0										11.8	11.5	11.5	10.9	10.3	
54.0											10.2	10.1	9.4	8.9	
58.0												8.9	8.2	7.7	
62.0												8.5/60m	7.2	6.6	
66.0													6.6/65m	5.8	
70.0														5.1	
72.0														4.9/71m	
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	21~73	
条数	8	8	8	7	6	6	5	5	4	4	4	3	3	2	
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 25.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0
14.0	84.5	84.7	84.0	82.6	74.0/15m									
16.0	68.0	68.3	68.0	67.7	67.5	60.5/17m	54.2/17m							
18.0	57.0	57.0	56.5	56.4	56.5	56.4	56.0	54.2	49.0	45.0/19m				
20.0	49.0	48.8	48.5	48.2	48.0	48.1	47.5	47.5	47.0	45.0	41.0	36.0/21m		
22.0	42.5	42.5	42.0	41.9	41.5	41.7	41.0	41.2	40.5	40.6	40.0	36.0	28.0/23m	
24.0	37.5	37.5	37.0	36.9	36.5	36.7	36.0	36.2	35.5	35.6	35.0	35.5	28.0	24.0/25m
26.0	33.5	33.5	33.0	32.8	32.5	32.7	32.0	32.1	31.5	31.6	31.0	31.0	28.0	24.0
28.0		30.2	29.7	29.5	29.4	29.4	28.8	28.8	28.2	28.2	27.8	28.0	27.4	24.0
30.0		28.9/29m	26.9	26.8	26.6	26.6	26.0	26.0	25.4	25.4	25.0	25.2	24.6	24.0
32.0			24.6	24.4	24.2	24.2	23.6	23.6	23.0	23.1	22.6	22.8	22.2	21.7
34.0				22.4	22.2	22.2	21.6	21.6	21.0	21.0	20.6	20.7	20.1	19.6
36.0				21.6/35m	20.4	20.4	19.8	19.8	19.2	19.2	18.8	18.9	18.3	17.8
38.0					19.0	18.9	18.3	18.3	17.7	17.7	17.3	17.4	16.8	16.2
40.0						17.5	16.9	16.9	16.3	16.3	15.9	16.0	15.4	14.9
42.0						17.0/41m	15.8	15.7	15.1	15.1	14.7	14.8	14.2	13.6
44.0							15.2/43m	14.6	14.1	14.0	13.6	13.7	13.1	12.5
46.0								13.7	13.1	13.0	12.6	12.7	12.1	11.5
48.0									12.3	12.1	11.8	11.8	11.2	10.6
50.0									11.9/49m	11.3	11.0	11.0	10.4	9.8
54.0										10.7/52m	9.7	9.6	9.0	8.4
58.0												8.5	7.8	7.2
62.0												7.8/61m	6.8	6.3
66.0													6.0	5.4
70.0														4.7
72.0														4.4
(°)	21~66	19~68	18~71	17~73	16~72	16~72	20~72	19~73	19~73	18~73	21~73	16~73	19~73	18~73
条数	7	7	7	7	6	6	5	5	4	4	4	3	3	2
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038

**主ジブ長さ+アダプタ長さ 30.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*
14.0	75.0/15m	74.6/15m	73.5/15m	70.5/15m										
16.0	67.0	67.2	66.5	66.6	62.0	55.5/17m								
18.0	56.0	56.1	55.5	55.5	55.5	55.4	50.0	44.6	40.0/19m					
20.0	48.0	47.9	47.5	47.3	47.0	47.2	46.5	44.6	40.0	36.9	33.5/21m			
22.0	41.5	41.7	41.0	41.1	41.0	40.9	40.5	40.4	39.5	36.9	33.5	30.0		
24.0	36.5	36.8	36.0	36.2	36.0	36.0	35.5	35.5	34.5	34.9	33.5	30.0	23.3	
26.0	32.5	32.8	32.0	32.2	32.0	32.0	31.5	31.5	30.5	30.9	30.5	30.0	23.3	20.2
28.0		29.6	29.0	28.9	28.7	28.8	28.1	28.2	27.6	27.6	27.2	27.4	23.3	20.2
30.0		26.9	26.3	26.2	26.0	26.0	25.4	25.4	24.8	24.8	24.4	24.6	23.3	20.2
32.0			24.0	23.9	23.7	23.7	23.1	23.1	22.5	22.5	22.1	22.2	21.6	20.2
34.0				21.9	21.7	21.7	21.1	21.1	20.5	20.5	20.1	20.2	19.6	19.1
36.0				20.2	20.0	19.9	19.3	19.3	18.7	18.7	18.3	18.5	17.8	17.3
38.0					18.5	18.4	17.8	17.8	17.2	17.2	16.8	16.9	16.3	15.8
40.0						17.1	16.5	16.4	15.9	15.8	15.4	15.6	14.9	14.4
42.0						15.9	15.3	15.2	14.7	14.6	14.3	14.4	13.7	13.2
44.0							14.3	14.2	13.7	13.5	13.2	13.3	12.7	12.1
46.0								13.3	12.7	12.6	12.2	12.3	11.7	11.1
48.0								12.9/47m	11.9	11.7	11.4	11.5	10.8	10.3
50.0									11.2	11.0	10.6	10.7	10.0	9.5
54.0										10.0/53m	9.3	9.3	8.6	8.1
58.0												8.2	7.5	6.9
62.0												7.5/61m	6.5	5.9
66.0													5.7	5.1
70.0														4.4
74.0														4.0/73m
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	18~73	20~73	17~73
条数	6	6	6	6	5	5	4	4	3	3	3	3	2	2
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038



TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)														単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	
16.0	66.0	60.6/17m	65.5	60.2	54.5/17m										
18.0	55.0	55.1	54.5	54.5	54.5	49.3	45.0/19m	39.8/19m							
20.0	47.0	47.1	46.5	46.4	46.5	46.3	45.0	39.8	35.5	32.8/21m					
22.0	41.0	40.9	40.5	40.3	40.0	40.2	39.5	39.6	35.5	32.8	30.0	27.0/23m			
24.0	36.0	36.1	35.5	35.4	35.0	35.3	34.5	34.7	34.0	32.8	30.0	27.0	21.0/25m		
26.0	32.0	32.2	31.5	31.5	31.0	31.4	30.5	30.8	30.0	30.2	29.8	27.0	21.0	18.5/27m	
28.0	29.0	29.0	28.4	28.3	28.1	28.2	27.5	27.6	27.0	27.0	26.5	26.8	21.0	18.5	
30.0		26.3	25.7	25.6	25.4	25.5	24.8	24.9	24.3	24.3	23.8	24.0	21.0	18.5	
32.0			23.5	23.3	23.1	23.2	22.5	22.6	21.9	22.0	21.5	21.7	21.0	18.5	
34.0			21.6	21.4	21.2	21.2	20.5	20.6	20.0	20.0	19.5	19.7	19.1	18.5	
36.0				19.7	19.5	19.5	18.8	18.9	18.3	18.2	17.8	18.0	17.4	16.8	
38.0					18.0	18.0	17.3	17.3	16.8	16.7	16.3	16.5	15.8	15.3	
40.0					16.8	16.6	16.0	16.0	15.4	15.4	15.0	15.1	14.5	14.0	
42.0						15.5	14.9	14.8	14.3	14.2	13.8	14.0	13.3	12.8	
44.0							13.9	13.8	13.2	13.1	12.8	12.9	12.3	11.7	
46.0							13.0	12.8	12.3	12.2	11.8	11.9	11.3	10.7	
48.0								12.0	11.5	11.3	11.0	11.1	10.4	9.9	
50.0									10.8	10.6	10.2	10.3	9.7	9.1	
54.0										9.3	9.0	9.0	8.3	7.7	
58.0											8.2/57m	7.9	7.2	6.6	
62.0												7.0	6.2	5.6	
66.0													5.4	4.8	
70.0													5.2/68m	4.1	
74.0														3.5	
(°)	13~63	21~64	12~69	19~71	11~71	17~71	10~71	16~72	19~72	15~72	14~72	17~73	16~73	16~72	
条数	5	5	5	5	5	4	4	3	3	3	3	2	2	2	
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038	

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)														単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	
16.0	60.0/17m	59.4/17m	56.0/17m	48.8/17m											
18.0	54.5	54.4	54.0	48.8	43.0	38.9/19m									
20.0	46.5	46.4	46.0	45.7	43.0	38.9	35.5	32.1	29.2/21m						
22.0	40.0	40.3	39.5	39.7	39.5	38.9	35.5	32.1	29.2	27.2	25.2/23m				
24.0	35.5	35.6	35.0	34.9	34.5	34.8	34.0	32.1	29.2	27.2	25.2	21.9			
26.0	31.5	31.7	31.0	31.0	30.5	30.9	30.0	30.3	29.2	27.2	25.2	21.9	17.0		
28.0	28.5	28.5	28.0	27.8	27.7	27.7	27.1	27.1	26.5	26.5	25.2	21.9	17.0	14.3	
30.0		25.9	25.3	25.2	25.0	25.0	24.4	24.4	23.8	23.8	23.4	21.9	17.0	14.3	
32.0			23.1	22.9	22.7	22.7	22.1	22.1	21.5	21.5	21.1	21.3	17.0	14.3	
34.0			21.2	21.0	20.8	20.8	20.1	20.2	19.6	19.6	19.1	19.3	17.0	14.3	
36.0				19.3	19.1	19.1	18.5	18.5	17.9	17.8	17.4	17.6	17.0	14.3	
38.0					17.7	17.6	17.0	17.0	16.4	16.3	15.9	16.1	15.5	14.3	
40.0					16.4	16.3	15.7	15.6	15.1	15.0	14.6	14.8	14.1	13.6	
42.0						15.1	14.6	14.5	13.9	13.8	13.5	13.6	13.0	12.4	
44.0							13.6	13.4	12.9	12.8	12.4	12.6	11.9	11.4	
46.0							12.7	12.5	12.0	11.8	11.5	11.6	11.0	10.4	
48.0								11.7	11.2	11.0	10.7	10.8	10.1	9.6	
50.0									10.5	10.3	9.9	10.0	9.4	8.8	
54.0										9.0	8.7	8.7	8.0	7.5	
58.0											7.7	7.6	6.9	6.3	
62.0												6.7	6.0	5.4	
66.0													5.2	4.6	
70.0													4.6	3.8	
74.0														3.1	
(°)	19~62	24~66	17~68	22~70	15~72	20~70	14~70	19~72	22~72	17~72	12~72	19~72	11~72	17~72	
条数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 45.5m+4.0m

作業半径 (m)	補ジブ長さ(m)														
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0#	
18.0	49.5/19m	48.4/19m	45.0/19m	40.1											
20.0	45.5	45.8	45.0	40.1	36.0	32.7	30.0/21m								
22.0	39.5	39.8	39.0	39.1	36.0	32.7	30.0	27.8	26.0	24.5/23m					
24.0	35.0	35.0	34.5	34.3	34.0	32.7	30.0	27.8	26.0	24.5	23.0				
26.0	31.0	31.2	30.5	30.5	30.0	30.4	29.7	27.8	26.0	24.5	23.0	19.0	14.7/27m		
28.0	28.0	28.0	27.5	27.3	27.2	27.2	26.6	26.6	26.0	24.5	23.0	19.0	14.7	11.5/29m	
30.0		25.4	24.8	24.7	24.6	24.6	23.9	24.0	23.3	23.3	22.9	19.0	14.7	11.5	
32.0		23.2	22.6	22.5	22.3	22.3	21.7	21.7	21.1	21.1	20.6	19.0	14.7	11.5	
34.0			20.7	20.6	20.4	20.4	19.7	19.8	19.1	19.1	18.7	18.9	14.7	11.5	
36.0				18.9	18.7	18.7	18.1	18.1	17.5	17.4	17.0	17.2	14.7	11.5	
38.0				17.5	17.3	17.2	16.6	16.6	16.0	16.0	15.5	15.7	14.7	11.5	
40.0					16.0	15.9	15.3	15.3	14.7	14.6	14.3	14.4	13.8	11.5	
42.0						14.8	14.2	14.1	13.6	13.5	13.1	13.3	12.6	11.5	
44.0						13.8	13.2	13.1	12.6	12.4	12.1	12.3	11.6	11.0	
46.0							12.4	12.2	11.7	11.5	11.2	11.3	10.7	10.1	
48.0								11.4	10.9	10.7	10.4	10.5	9.8	9.3	
50.0								10.7	10.1	9.9	9.6	9.7	9.1	8.5	
54.0									8.7	8.4	8.4	7.7	7.2		
58.0										7.4	7.4	6.6	6.1		
62.0												6.4	5.7	5.1	
66.0													4.9	4.3	
70.0													4.3	3.5	
74.0														2.8	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~70	19~72	
条数	4	4	4	3	3	3	3	3	2	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038	

主ジブ長さ+アダプタ長さ 50.5m+4.0m

作業半径 (m)	補ジブ長さ(m)														
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	
18.0	38.0/19m		33.0/19m	29.9/19m											
20.0	38.0	35.0	32.5	29.7	26.6	24.1/19m									
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m							
24.0	34.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m				
26.0	30.5	30.8	30.0	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5			
28.0	27.7	27.7	27.1	27.0	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3		
30.0	25.1	25.1	24.5	24.3	24.2	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8	
32.0		22.9	22.3	22.1	22.0	22.0	21.3	21.0	20.1	18.6	17.1	13.5	10.3	7.8	
34.0			20.4	20.2	20.1	20.1	19.4	19.5	18.8	18.6	17.1	13.5	10.3	7.8	
36.0			18.8	18.6	18.4	18.4	17.8	17.8	17.2	17.1	16.7	13.5	10.3	7.8	
38.0				17.2	17.0	16.9	16.3	16.3	15.7	15.7	15.2	13.5	10.3	7.8	
40.0					15.8	15.6	15.1	15.0	14.4	14.4	14.0	13.5	10.3	7.8	
42.0					14.7	14.5	13.9	13.9	13.3	13.2	12.8	13.0	10.3	7.8	
44.0						13.5	13.0	12.8	12.3	12.2	11.8	12.0	10.3	7.8	
46.0							12.1	11.9	11.4	11.2	10.9	11.1	10.3	7.8	
48.0							11.4	11.1	10.6	10.4	10.1	10.3	9.6	7.8	
50.0							10.4	9.9	9.7	9.4	9.5	8.8	7.8		
54.0								8.8	8.4	8.1	8.2	7.5	6.9		
58.0										7.1	7.1	6.4	5.8		
62.0												6.2	5.5	4.9	
66.0												5.6	4.7	4.0	
70.0													4.1	3.2	
74.0														2.5	
78.0														2.2/77m	
(°)	11~60	20~61	10~67	18~69	9~69	16~69	8~69	15~69	7~69	22~71	17~71	6~71	16~72	11~71	
条数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 10.44 × 10.03m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)														
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	
20.0	31.0/21m	28.0/21m	25.5/21m	22.5											
22.0	31.0	28.0	25.5	22.6	20.0	18.1									
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m					
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m				
28.0	27.3	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m		
30.0	24.7	24.7	24.1	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0		
32.0		22.5	21.9	21.8	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0	
34.0			20.1	19.9	19.8	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	
36.0			18.5	18.3	18.1	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	
38.0				16.8	16.7	16.6	16.0	16.0	15.4	14.5	12.9	9.5	7.0	5.0	
40.0					15.5	15.4	14.8	14.7	14.1	14.1	12.9	9.5	7.0	5.0	
42.0					14.4	14.2	13.7	13.6	13.0	12.9	12.5	9.5	7.0	5.0	
44.0						13.3	12.7	12.6	12.0	11.9	11.5	9.5	7.0	5.0	
46.0							11.8	11.7	11.1	11.0	10.6	9.5	7.0	5.0	
48.0							11.1	10.9	10.3	10.2	9.8	9.5	7.0	5.0	
50.0								10.2	9.6	9.4	9.1	9.3	7.0	5.0	
54.0									8.5	8.2	7.9	8.0	7.0	5.0	
58.0											6.9	6.9	6.2	5.0	
62.0												6.0	5.3	4.6	
66.0												5.3	4.5	3.7	
70.0													3.8	2.9	
74.0														2.3	
(°)	18~56	24~60	16~64	21~68	14~67	19~69	13~67	18~69	12~68	24~70	20~69	11~70	18~71	22~70	
索数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	75030	75043	75031	75044	75032	75045	75033	75046	75034	75047	75035	75036	75037	75038	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 15.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	90.0*	96.0#	
12.0	123.0	111.0/13m	105.0/13m	98.8/13m															
14.0	98.0	98.0	97.5	97.5	89.0	81.4	73.0/15m												
16.0	80.5	80.6	80.0	80.0	80.0	79.9	73.0	67.0	60.5/17m	56.3/17m									
18.0	68.0	68.2	67.5	67.6	67.5	67.5	67.0	66.8	60.5	56.3	52.0								
20.0	59.0	59.0	58.5	58.4	58.5	58.2	57.5	57.7	57.0	56.3	52.0	42.0							
22.0	52.0	51.8	51.5	51.2	51.0	51.0	50.5	50.5	50.0	50.0	49.5	42.0	35.5	30.5/23m					
24.0	49.0/23m	46.1	45.5	45.5	45.5	45.3	45.0	44.8	44.5	44.2	44.0	42.0	35.0	30.0	24.5/25m				
26.0		41.5	41.0	40.9	41.0	40.7	40.0	40.1	39.5	39.6	39.5	39.5	34.5	30.0	24.3	19.9/27m			
28.0		39.6/27m	37.5	37.0	37.0	36.8	36.5	36.2	36.0	35.7	35.5	35.5	34.0	30.0	23.9	19.7	16.0		
30.0			34.0	33.7	33.5	33.5	33.0	32.9	32.5	32.4	32.0	32.0	31.5	30.0	23.5	19.3	15.6	13.0	
32.0				30.9	31.0	30.7	30.0	30.1	29.9	29.5	29.5	29.6	29.0	28.5	23.1	19.0	15.3	12.5	
34.0				29.7/33m	28.6	28.2	28.0	27.7	27.5	27.1	27.0	27.1	26.5	26.0	22.8	18.6	14.9	12.0	
36.0					26.6	26.1	25.9	25.5	25.3	25.0	24.9	25.0	24.4	23.9	22.4	18.3	14.6	11.6	
38.0						24.3	24.1	23.7	23.5	23.1	23.0	23.1	22.5	22.0	22.1	17.9	14.3	11.2	
40.0							23.5/39m	22.4	22.0	21.8	21.4	21.4	21.5	20.9	20.3	20.6	17.5	14.0	10.9
42.0								21.0	20.6	20.4	20.0	19.9	20.0	19.4	18.8	19.1	17.2	13.7	10.6
44.0									19.3	19.1	18.7	18.6	18.7	18.0	17.5	17.8	16.8	13.4	10.3
46.0									18.8/45m	17.9	17.5	17.5	17.5	16.8	16.3	16.5	16.4	13.1	10.0
48.0										17.4/47m	16.5	16.4	16.4	15.8	15.2	15.5	15.4	12.8	9.7
50.0											15.5	15.5	15.4	14.8	14.2	14.5	14.4	12.5	9.5
54.0												14.2/53m	13.7	13.1	12.5	12.7	12.6	12.0	9.0
58.0													12.3	11.6	11.0	11.2	11.2	11.4	8.7
62.0														10.4	9.8	10.0	9.9	10.1	8.4
66.0														9.7/65m	8.8	8.9	8.8	9.0	8.1
70.0															7.9	7.9	7.8	8.0	7.8
74.0																7.1	7.0	7.2	7.0
76.0																6.8	6.6	6.8	6.6
78.0																	6.3	6.4	6.2
82.0																	5.7	5.7	5.6
86.0																		5.1	4.9
88.0																		4.9	4.7
90.0																			4.4
94.0																			4.0/93m
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	20~74	19~73	18~73	13~74	19~74	
条数	10	9	9	8	7	7	6	6	5	5	4	4	3	3	2	2	2	2	
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	36041	36042	

主ジブ長さ+アダプタ長さ 20.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																		単位 : t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0*	96.0#	
12.0	109.0/13m	109.0/13m	100.0/13m	89.9/13m															
14.0	96.0	96.2	95.5	89.2	78.5	71.0/15m													
16.0	79.0	79.0	78.5	78.4	77.5	70.9	63.5	57.8	52.0/17m										
18.0	67.0	66.9	66.5	66.2	66.0	66.1	63.5	57.8	52.0	48.1	44.0/19m								
20.0	58.0	57.8	57.5	57.2	57.0	57.0	56.5	56.5	52.0	48.1	44.0	37.0							
22.0	51.0	50.7	50.5	50.1	50.0	50.0	49.5	49.4	49.0	48.1	44.0	37.0	30.0						
24.0	45.5	45.2	45.0	44.5	44.5	44.3	44.0	43.8	43.5	43.2	43.0	37.0	30.0	25.9					
26.0		40.6	40.0	40.0	40.0	39.8	39.5	39.2	39.0	38.6	38.5	37.0	29.9	25.8	21.7	17.6/27m			
28.0		36.8	36.5	36.1	36.0	36.0	35.5	35.4	35.0	34.8	34.5	34.5	29.7	25.7	21.5	17.5	14.0/29m		
30.0			33.0	32.9	33.0	32.7	32.5	32.1	31.5	31.6	31.5	31.5	29.5	25.7	21.3	17.4	13.8	11.1/31m	
32.0				30.2	30.0	29.9	29.7	29.4	29.1	28.8	28.7	28.9	28.2	25.6	21.2	17.2	13.6	10.9	
34.0				27.8	27.9	27.5	27.3	27.0	26.8	26.4	26.3	26.4	25.8	25.3	21	17.0	13.3	10.6	
36.0					25.9	25.5	25.2	24.9	24.7	24.3	24.2	24.3	23.7	23.2	20.8	16.8	13.1	10.4	
38.0						23.7	23.4	23.1	22.9	22.4	22.4	22.5	21.9	21.4	20.6	16.6	12.8	10.1	
40.0						22.1	21.8	21.4	21.2	20.8	20.8	20.9	20.3	19.7	20.0	16.3	12.6	9.8	
42.0							20.4	20.0	19.8	19.4	19.4	19.4	18.8	18.3	18.5	16.0	12.3	9.6	
44.0								18.8	18.5	18.1	18.1	18.1	17.5	17.0	17.2	15.7	12.1	9.3	
46.0								18.2/45m	17.4	17.0	16.9	17.0	16.3	15.8	16.0	15.4	11.9	9.1	
48.0									16.4	15.9	15.9	15.9	15.3	14.7	15.0	14.9	11.6	8.9	
50.0										15.0	14.9	14.9	14.3	13.7	14.0	13.9	11.4	8.7	
54.0											13.4	13.3	12.6	12.0	12.3	12.2	11.0	8.3	
58.0												11.9	11.2	10.6	10.8	10.7	10.5	7.9	
62.0													10.0	9.4	9.6	9.5	9.8	7.6	
66.0													9.3/65m	8.4	8.5	8.4	8.7	7.3	
70.0														7.5	7.6	7.5	7.7	7.0	
74.0															6.8	6.7	6.9	6.7	
78.0															6.3/77m	6.0	6.1	5.9	
82.0																5.4	5.4	5.3	
86.0																	4.9	4.7	
88.0																	4.6	4.4	
90.0																		4.1	
94.0																		3.6	
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	21~73	18~73	20~74	19~73	18~73	
条数	9	9	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2	
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	36041	36042	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 25.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																			単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	90.0#	96.0#		
14.0	94.5	94.4	92.5	83.6	76.0/15m															
16.0	77.5	77.5	77.0	76.9	76.0	67.5	60.5/17m	54.2/17m												
18.0	65.5	65.6	65.0	64.9	65.0	64.8	60.5	54.2	49.0	45/19m										
20.0	56.5	56.6	56.0	56.0	56.0	55.9	55.5	54.2	49.0	45.0	41.0	36.0/21m								
22.0	50.0	49.7	49.5	49.1	49.0	48.9	48.5	48.4	48.0	45.0	41.0	36.0	28.0/23m							
24.0	44.5	44.2	44.0	43.6	43.5	43.4	43.0	42.8	42.5	42.3	41.0	36.0	28.0	24.0/25m						
26.0		39.7	39.5	39.1	39.0	38.9	38.5	38.3	38.0	37.7	37.5	36.0	28.0	24.0	21.0					
28.0		36.0	35.5	35.3	35.5	35.1	34.5	34.6	34.0	34.0	33.5	34.0	28.0	24.0	21.0	17.0				
30.0		34.4/29m	32.5	32.1	32.0	31.9	31.5	31.4	31.0	30.8	30.5	30.5	28.0	24.0	21.0	16.9	13.5			
32.0				29.4	29.6	29.2	29.0	28.6	28.4	28.0	28.0	28.1	27.5	24.0	21.0	16.9	13.3	10.4		
34.0				27.1	27.3	26.9	26.6	26.3	26.1	25.7	25.6	25.8	25.2	24.0	21.0	16.8	13.1	10.3		
36.0				26.2/35m	25.3	24.8	24.6	24.2	24.0	23.6	23.6	23.7	23.1	22.6	21.0	16.7	12.9	10.1		
38.0						23.1	22.8	22.4	22.2	21.8	21.8	21.9	21.3	20.7	21.0	16.6	12.7	9.9		
40.0						21.5	21.3	20.9	20.7	20.2	20.2	20.3	19.7	19.1	19.4	16.6	12.5	9.7		
42.0						20.9/41m	19.9	19.5	19.3	18.8	18.8	18.9	18.2	17.7	18.0	16.5	12.3	9.5		
44.0								18.2	18.0	17.6	17.5	17.6	17.0	16.4	16.7	16.2	12.1	9.3		
46.0								17.1	16.9	16.4	16.4	16.5	15.8	15.3	15.5	15.5	11.9	9.1		
48.0									15.9	15.4	15.4	15.4	14.8	14.2	14.5	14.4	11.7	9.0		
50.0										14.5	14.5	14.5	13.8	13.3	13.5	13.5	11.5	8.8		
54.0										13.8/52m	12.9	12.8	12.2	11.6	11.8	11.8	11.1	8.4		
58.0												11.5	10.8	10.2	10.4	10.3	10.6	8.0		
62.0													9.6	9.0	9.2	9.1	9.4	7.6		
66.0													8.6	8.0	8.2	8.1	8.3	7.2		
70.0														7.2	7.3	7.2	7.4	6.9		
74.0															6.5	6.4	6.6	6.4		
78.0															5.8	5.7	5.8	5.7		
82.0																5.1	5.2	5.0		
86.0																	4.6	4.4		
90.0																	4.2/89m	3.9		
94.0																		3.3		
(°)	32~66	19~68	29~71	17~73	26~72	16~72	24~72	19~73	22~73	18~73	21~73	25~74	19~73	23~73	17~74	21~73	18~73	19~73		
条数	8	8	8	7	6	6	5	5	4	4	4	3	3	2	2	2	2	2		
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03		
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	36041	36042		

主ジブ長さ+アダプタ長さ 30.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																			単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0*	90.0#	96.0#		
14.0	85.0/15m	84.8/15m	80.5/15m	70.5/15m																
16.0	76.5	76.5	76.0	70.2	62.0	55.5/17m														
18.0	64.5	64.6	64.0	64.0	62.0	55.5	50.0	44.6	40.0/19m											
20.0	56.0	55.8	55.5	55.2	55.0	55.0	50.0	44.6	40.0	36.9	33.5/21m									
22.0	49.0	49.0	48.5	48.3	48.5	48.2	47.5	44.6	40.0	36.9	33.5	30.0								
24.0	43.5	43.5	43.0	42.9	43.0	42.7	42.0	42.1	40.0	36.9	33.5	30.0	23.3							
26.0	39.5	39.1	38.5	38.4	38.5	38.3	38.0	37.7	37.0	36.9	33.5	30.0	23.3	20.2	17.6/27m					
28.0		35.4	35.0	34.7	34.5	34.6	34.0	34.0	33.5	33.4	33.0	30.0	23.3	20.2	17.6	14.2/29m				
30.0		32.3	32.0	31.6	31.5	31.4	31.0	30.8	30.5	30.2	30.0	30.0	23.3	20.2	17.6	14.2	11.6/31m			
32.0			29.5	28.9	29.1	28.7	28.5	28.1	27.9	27.5	27.4	27.6	23.3	20.2	17.6	14.2	11.6	9.0/33m		
34.0				26.6	26.8	26.4	26.1	25.8	25.6	25.2	25.1	25.3	23.3	20.2	17.6	14.2	11.4	8.9		
36.0				24.7	24.8	24.4	24.1	23.8	23.5	23.1	23.1	23.2	22.6	20.2	17.6	14.1	11.3	8.8		
38.0					23.1	22.6	22.4	22.0	21.8	21.4	21.3	21.5	20.8	20.2	17.6	14.1	11.2	8.6		
40.0						21.1	20.8	20.4	20.2	19.8	19.8	19.9	19.2	18.7	17.5	14.1	11.1	8.5		
42.0						19.7	19.5	19.0	18.8	18.4	18.4	18.5	17.8	17.3	17.5	14.0	10.9	8.3		
44.0							18.3	17.8	17.6	17.2	17.1	17.2	16.6	16.0	16.3	13.9	10.8	8.2		
46.0								16.7	16.5	16.0	16.0	16.1	15.4	14.9	15.2	13.8	10.7	8.0		
48.0								16.2/47m	15.5	15.0	15.0	15.0	14.4	13.8	14.1	13.7	10.5	7.9		
50.0									14.6	14.1	14.1	14.1	13.5	12.9	13.2	13.1	10.4	7.7		
54.0										13.0/53m	12.5	12.5	11.8	11.3	11.5	11.4	10.1	7.4		
58.0												11.2	10.5	9.9	10.1	10.0	9.8	7.1		
62.0													10.3/61m	9.3	8.7	8.9	8.8	6.8		
66.0														8.3	7.7	7.9	7.8	6.5		
70.0															6.9	7.0	6.9	6.2		
74.0															6.4/73m	6.2	6.1	6.3	5.9	
78.0																5.6	5.4	5.6	5.4	
82.0																	4.8	5.0	4.8	
84.0																	4.6	4.7	4.5	
86.0																		4.4	4.2	
90.0																		3.9	3.6	
94.0																			3.1	
96.0																			2.8	
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	18~73	20~73	17~73	19~73	18~73	17~73	17~73		
条数	7	7	7	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2		
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08		
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	36041	36042		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

単位 :t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0#	90.0#	96.0#	
16.0	75.5	69.6/17m	67.5	60.2	54.5/17m														
18.0	64.0	63.7	63.5	59.9	54.5	49.3	45.0/19m	39.8/19m											
20.0	55.0	55.0	54.5	54.3	54.5	49.3	45.0	39.8	35.5	32.8/21m									
22.0	48.5	48.2	48.0	47.6	47.5	47.4	45.0	39.8	35.5	32.8	30.0	27.0/23m							
24.0	43.0	42.9	42.5	42.2	42.0	42.0	41.5	39.8	35.5	32.8	30.0	27.0	21.0/25m						
26.0	38.5	38.5	38.0	37.8	38.0	37.6	37.0	37.0	35.5	32.8	30.0	27.0	21.0	18.5/27m					
28.0		34.8	34.5	34.1	34.0	34.0	33.5	33.4	33.0	32.8	30.0	27.0	21.0	18.5	16.0				
30.0		31.7	31.5	31.0	31.0	30.8	30.5	30.2	30.0	29.6	29.6	27.0	21.0	18.5	16.0	13.0			
32.0			28.9	28.4	28.6	28.2	27.9	27.6	27.3	27.0	26.9	27.0	21.0	18.5	16.0	13.0	11.0		
34.0				26.1	26.3	25.9	25.7	25.3	25.1	24.7	24.6	24.8	21.0	18.5	16.0	13.0	10.9	8.5	
36.0					24.2	24.3	23.9	23.7	23.3	23.1	22.7	22.6	22.8	21.0	18.5	16.0	13.0	10.9	8.4
38.0						22.6	22.2	21.9	21.5	21.3	20.9	20.9	21.0	20.4	18.5	16.0	13.0	10.8	8.3
40.0							20.6	20.4	20.0	19.8	19.3	19.3	19.5	18.8	18.2	16.0	13.0	10.8	8.1
42.0							19.3	19.0	18.6	18.4	18.0	17.9	18.1	17.4	16.9	16.0	13.0	10.7	8.0
44.0								17.8	17.4	17.2	16.7	16.7	16.8	16.2	15.6	15.9	13.0	10.6	7.9
46.0									16.3	16.1	15.6	15.6	15.7	15.0	14.5	14.8	13.0	10.5	7.8
48.0									15.4	15.1	14.6	14.6	14.7	14.0	13.5	13.8	13.0	10.5	7.6
50.0										14.2	13.8	13.7	13.8	13.1	12.5	12.8	12.8	10.4	7.5
54.0											12.3	12.2	12.2	11.5	10.9	11.2	11.1	10.2	7.2
58.0													10.8	10.1	9.6	9.8	9.7	10.0	6.9
62.0													9.7	9.0	8.4	8.6	8.5	8.9	6.6
66.0														8.1	7.4	7.6	7.5	7.8	6.3
70.0															6.6	6.7	6.6	6.9	6.1
74.0															5.9	6.0	5.9	6.1	5.8
78.0																5.3	5.2	5.4	5.2
82.0																	4.6	4.8	4.6
86.0																	4.2/85m	4.2	4.0
90.0																		3.6	3.4
94.0																			2.8
98.0																			2.5/97m
(°)	28~63	21~64	25~69	19~71	23~71	17~71	21~71	16~72	29~72	15~72	24~72	17~73	22~73	16~72	20~73	17~73	19~73	16~73	
索数	7	6	6	5	5	4	4	3	3	3	3	2	2	2	2	2	2	2	
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	36041	36042	

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

単位 :t

作業半径 (m)	補ジブ長さ(m)																		
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	78.0#	84.0#	90.0#	96.0#	
16.0	65.5/17m	60.4/17m	56.0/17m	48.8/17m															
18.0	63.0	60.3	56.0	48.8	43.0	38.9/19m													
20.0	54.5	54.4	54.0	48.8	43.0	38.9	35.5	32.1	29.2/21m										
22.0	48.0	47.7	47.5	47.0	43.0	38.9	35.5	32.1	29.2	27.2	25.2/23m								
24.0	42.5	42.3	42.0	41.6	41.5	38.9	35.5	32.1	29.2	27.2	25.2	21.9							
26.0	38.0	38.0	37.5	37.3	37.5	37.2	35.5	32.1	29.2	27.2	25.2	21.9	17.0						
28.0		34.3	34.0	33.6	33.5	33.5	33.0	32.1	29.2	27.2	25.2	21.9	17.0	14.3	12.6/29m				
30.0		31.3	31.0	30.6	30.5	30.4	30.0	29.8	29.2	27.2	25.2	21.9	17.0	14.3	12.6	10.0/31m			
32.0			28.5	27.9	28.2	27.8	27.5	27.2	26.9	26.5	25.2	21.9	17.0	14.3	12.6	10.0	8.3/33m		
34.0				25.7	25.9	25.5	25.3	24.9	24.7	24.3	24.2	21.9	17.0	14.3	12.5	10.0	8.3	6.4/35m	
36.0					23.8	24.0	23.5	23.3	22.9	22.7	22.3	22.2	21.9	17.0	14.3	12.5	10.0	8.3	6.3
38.0						22.3	21.8	21.6	21.2	21.0	20.5	20.5	20.7	17.0	14.3	12.4	10.0	8.2	6.2
40.0							20.3	20.0	19.6	19.4	19.0	19.0	19.1	17.0	14.3	12.4	10.0	8.2	6.1
42.0							19.0	18.7	18.3	18.1	17.6	17.6	17.7	17.0	14.3	12.4	10.0	8.2	5.9
44.0								17.5	17.1	16.9	16.4	16.4	16.5	15.8	14.3	12.4	10.0	8.1	5.8
46.0									16.0	15.8	15.3	15.3	15.4	14.7	14.2	12.4	10.0	8.1	5.7
48.0									15.0	14.8	14.3	14.3	14.4	13.7	13.2	12.4	10.0	8.1	5.6
50.0										13.9	13.4	13.4	13.5	12.8	12.2	12.4	10.0	8.0	5.5
54.0											11.9	11.9	11.9	11.2	10.6	10.9	10.0	8.0	5.3
58.0													10.6	9.9	9.3	9.6	9.5	7.9	5.1
62.0													9.5	8.8	8.1	8.4	8.3	7.8	4.9
66.0														7.8	7.2	7.4	7.3	7.6	4.7
70.0															6.3	6.5	6.4	6.7	4.6
74.0																5.7	5.8	5.7	4.4
78.0																	5.1	5.0	4.3
82.0																		4.4	4.2
86.0																		3.8	3.7
90.0																			3.1
94.0																			2.6
98.0																			2.1
(°)	31~62	24~66	28~68	22~70	25~72	20~70	23~70	19~72	22~72	17~72	26~72	19~72	23~72	17~72	21~73	16~73	20~72	15~72	
索数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	36041	36042	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 45.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)																	
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0#	78.0#	84.0#	90.0#	96.0#
18.0	52.0/19m	48.4/19m	45.0/19m	40.1														
20.0	51.5	48.3	45.0	40.1	36.0	32.7	30.0/21m											
22.0	47.0	47.1	45.0	40.1	36.0	32.7	30.0	27.8	26.0	24.5/23m								
24.0	42.0	41.8	41.5	39.9	36.0	32.7	30.0	27.8	26.0	24.5	23.0							
26.0	37.5	37.5	37.0	36.8	35.5	32.7	30.0	27.8	26.0	24.5	23.0	19.0	14.7/27m					
28.0	34.0	33.9	33.5	33.2	33.0	32.6	30.0	27.8	26.0	24.5	23.0	19.0	14.7	11.5/29m				
30.0		30.8	30.5	30.1	30.0	30.0	29.7	27.8	26.0	24.5	23.0	19.0	14.7	11.5	10.6			
32.0			28.1	27.5	27.8	27.4	27.1	26.7	25.9	24.5	23.0	19.0	14.7	11.5	10.5	8.0/33m		
34.0			25.9	25.3	25.5	25.1	24.9	24.5	24.2	23.8	23.0	19.0	14.7	11.5	10.4	8.0	6.5/35m	
36.0				23.4	23.6	23.1	22.9	22.5	22.3	21.9	21.8	19.0	14.7	11.5	10.3	8.0	6.5	4.9
38.0				21.7	21.9	21.4	21.2	20.8	20.6	20.2	20.1	19.0	14.7	11.5	10.2	8.0	6.5	4.8
40.0					20.4	19.9	19.7	19.3	19.1	18.6	18.8	18.8	14.7	11.5	10.2	8.0	6.5	4.6
42.0						18.6	18.4	17.9	17.7	17.3	17.2	17.4	14.7	11.5	10.1	8.0	6.5	4.5
44.0						17.5	17.2	16.7	16.5	16.1	16.0	16.2	14.7	11.5	10.0	8.0	6.5	4.4
46.0							16.1	15.7	15.4	15.0	14.9	15.1	14.4	11.5	10.0	8.0	6.5	4.3
48.0								14.7	14.5	14.0	14.0	14.1	13.4	11.5	10.0	8.0	6.5	4.2
50.0								13.9	13.6	13.1	13.1	13.2	12.5	11.5	10.0	8.0	6.5	4.1
54.0										11.6	11.6	11.6	10.9	10.4	10.0	8.0	6.5	3.9
58.0											10.4	10.3	9.6	9.0	9.3	8.0	6.5	3.8
62.0												9.2	8.5	7.9	8.2	8.0	6.5	3.7
66.0													7.6	6.9	7.2	7.1	6.5	3.6
70.0													6.8	6.1	6.3	6.2	6.5	3.5
74.0														5.4	5.6	5.4	5.7	3.5
78.0															4.9	4.8	5.0	3.4
82.0															4.4	4.1	4.4	3.4
86.0																3.5	3.8	3.3
90.0																	3.2	2.9
94.0																		2.7
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~72	19~72	12~72	18~72	21~72	24~73
条数	4	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	2	2
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	36041	36042

主ジブ長さ+アダプタ長さ 50.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	78.0#	84.0#	
18.0	38.0/19m		33.0/19m	29.9/19m													
20.0	38.0	35.0	32.5	29.7	26.6	24.1/21m											
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m									
24.0	36.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m						
26.0	36.0	33.6	31.0	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5					
28.0	33.5	33.3	31.0	28.5	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3				
30.0		30.5	30.0	28.4	26.2	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8			
32.0		27.9	27.8	27.2	26.1	24.0	22.1	21.0	20.1	18.6	17.1	13.5	10.3	7.8	6.6		
34.0			25.6	25.0	25.2	23.9	22.1	20.9	20.0	18.6	17.1	13.5	10.3	7.8	6.5	4.8	
36.0				23.0	23.3	22.9	22.1	20.8	19.8	18.5	17.0	13.5	10.3	7.8	6.5	4.8	
38.0				21.4	21.6	21.2	20.9	20.5	19.6	18.4	17.0	13.5	10.3	7.8	6.5	4.8	
40.0					20.1	19.7	19.4	19.0	18.8	18.3	17.0	13.5	10.3	7.8	6.4	4.8	
42.0						18.3	18.1	17.7	17.4	17.0	17.0	13.5	10.3	7.8	6.4	4.8	
44.0						17.2	16.9	16.5	16.3	15.8	15.8	13.5	10.3	7.8	6.3	4.8	
46.0							15.9	15.4	15.2	14.7	14.7	13.5	10.3	7.8	6.3	4.8	
48.0								14.5	14.2	13.8	13.7	13.5	10.3	7.8	6.3	4.8	
50.0								13.6	13.4	12.9	12.8	13.0	10.3	7.8	6.3	4.8	
54.0										11.4	11.3	11.4	10.3	7.8	6.3	4.8	
58.0											10.1	10.1	9.4	7.8	6.3	4.8	
62.0												9.0	8.3	7.7	6.3	4.8	
66.0													7.4	6.7	6.3	4.8	
70.0													6.6	5.9	6.1	4.8	
74.0														5.2	5.4	4.8	
78.0															4.8	4.6	
82.0															4.1	3.9	
86.0																3.3	
(°)	27~60	20~61	24~67	18~69	22~69	16~69	20~69	15~69	25~69	22~71	18~71	22~72	16~71	20~71	14~71	19~71	
条数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	36040	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 100t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)															
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	78.0#	
20.0	31.0/21m	28.0/21m	25.5/21m	22.5												
22.0	31.0	28.0	25.5	22.6	20.0	18.1										
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m						
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m					
28.0	28.8	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m			
30.0		26.1	24.3	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0			
32.0		25.6	23.9	21.9	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0	3.3/33m	
34.0			23.5	21.7	20.0	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	3.3	
36.0				21.6	20.0	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	3.3	
38.0				21.1	20.0	18.1	16.6	16.0	15.7	14.5	12.9	9.5	7.0	5.0	3.3	
40.0					19.9	18.1	16.6	15.8	15.5	14.3	12.9	9.5	7.0	5.0	3.3	
42.0						18.1	16.6	15.7	15.2	14.2	12.9	9.5	7.0	5.0	3.3	
44.0						16.9	16.6	15.6	15.0	14.1	12.9	9.5	7.0	5.0	3.3	
46.0							15.6	15.1	14.8	13.9	12.9	9.5	7.0	5.0	3.3	
48.0								14.2	14.0	13.5	12.9	9.5	7.0	5.0	3.3	
50.0								13.4	13.1	12.6	12.6	9.5	7.0	5.0	3.3	
54.0										11.1	11.1	9.5	7.0	5.0	3.3	
58.0											9.9	9.5	7.0	5.0	3.3	
62.0												8.8	7.0	5.0	3.3	
66.0													7.0	5.0	3.3	
70.0													6.4	5.0	3.3	
74.0														5.0	3.3	
78.0															3.3	
82.0															3.3	
(°)	31~56	24~60	27~64	21~68	25~67	19~69	23~67	18~69	27~68	24~70	20~69	24~70	18~71	22~70	16~71	
条数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	36030	36043	36031	36044	36032	36045	36033	36046	36034	36047	36035	36036	36037	36038	36039	



TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 15.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0	84.0*	
12.0	107.0	96.2/13m	95.5/13m	95.7/13m													
14.0	84.5	84.7	84.0	84.1	84.0	81.4	73.0/15m										
16.0	69.5	69.5	69.0	68.9	69.0	68.8	68.5	67.0	60.5/17m	56.3/17m							
18.0	59.0	58.7	58.5	58.1	58.0	58.0	57.5	57.5	57.0	56.3	52.0						
20.0	51.0	50.7	50.5	50.1	50.0	49.9	49.5	49.4	49.0	48.9	48.5	42.0					
22.0	44.5	44.3	44.0	43.7	43.5	43.6	43.0	43.1	42.5	42.5	42.5	42.0	35.5	30.5/23m			
24.0	42.0/23m	39.3	39.0	38.7	38.5	38.5	38.0	38.0	37.5	37.5	37.0	37.5	35.0	30.0	24.5/25m		
26.0		35.2	35.0	34.6	34.5	34.4	34.0	33.9	33.5	33.3	33.0	33.0	32.5	30.0	24.3	19.9/27m	
28.0		33.6/27m	31.5	31.2	31.0	31.0	30.5	30.5	30.0	29.9	29.9	30.0	29.4	28.9	23.9	19.7	
30.0			28.9	28.4	28.5	28.2	28.0	27.6	27.4	27.0	27.0	27.1	26.5	26.0	23.5	19.3	
32.0				26.0	26.1	25.7	25.5	25.2	25.0	24.6	24.6	24.7	24.1	23.6	23.1	19.0	
34.0				25.0/33m	24.1	24.7	23.4	23.1	22.9	22.5	22.5	22.6	22.0	21.4	21.7	18.6	
36.0					22.3	23.6	21.6	21.2	21.1	20.7	20.6	20.7	20.1	19.6	19.9	18.3	
38.0						21.8	20.0	19.6	19.5	19.0	19.0	19.1	18.5	18.0	18.3	17.9	
40.0						20.3	18.6	18.2	18.0	17.6	17.6	17.7	17.1	16.5	16.8	16.8	
42.0						19.6/39m	17.4	17.0	16.8	16.4	16.3	16.4	15.8	15.2	15.5	15.5	
44.0								15.9	15.7	15.2	15.2	15.2	14.6	14.1	14.3	14.3	
46.0								15.4/45m	14.7	14.2	14.2	14.2	13.6	13.1	13.3	13.2	
48.0									14.3/47m	13.3	13.3	13.3	12.7	12.1	12.4	12.3	
50.0										12.5	12.5	12.5	11.8	11.3	11.5	11.4	
54.0											11.5/53m	11.0	10.3	9.8	10.0	9.9	
58.0												9.8	9.1	8.5	8.7	8.6	
62.0													8.1	7.5	7.6	7.5	
66.0													7.4/65m	6.6	6.7	6.6	
70.0														5.8	5.9	5.8	
74.0															5.2	5.1	
76.0															4.9	4.8	
78.0																4.5	
82.0																3.9	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	20~74	22~73	18~73	
条数	9	8	8	8	7	7	6	6	5	5	4	4	3	3	2	2	
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	00	
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040	

**主ジブ長さ+アダプタ長さ 20.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																単位:t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*	
12.0	94.0/13m	94.2/13m	93.5/13m	89.9/13m													
14.0	83.0	82.9	82.5	82.3	78.5	71.0/15m											
16.0	68.0	68.0	67.5	67.4	67.5	67.2	63.5	57.8	52.0/17m								
18.0	57.5	57.4	57.0	56.8	56.5	56.7	56.0	56.1	52.0	48.1	44.0/19m						
20.0	49.5	49.5	49.0	48.9	49.0	48.7	48.5	48.2	48.0	47.7	44.0	37.0					
22.0	43.5	43.3	43.0	42.6	42.5	42.5	42.0	42.0	41.5	41.4	41.0	37.0	30.0				
24.0	38.5	38.3	38.0	37.7	37.5	37.5	37.0	37.0	36.5	36.4	36.0	36.5	30.0	25.9			
26.0		34.3	34.0	33.7	33.5	33.5	33.0	33.0	32.5	32.4	32.0	32.5	29.9	25.8	21.7	17.6/27m	
28.0		31.1	30.5	30.4	30.5	30.2	30.0	29.6	29.4	29.1	29.0	29.2	28.6	25.7	21.5	17.5	
30.0			28.2	27.6	27.8	27.4	27.2	26.8	26.6	26.2	26.2	26.3	25.7	25.2	21.3	17.4	
32.0				25.2	25.4	25.0	24.8	24.4	24.2	23.8	23.8	23.9	23.3	22.8	21.2	17.2	
34.0				23.3	23.4	23.0	22.7	22.4	22.2	21.8	21.8	21.9	21.3	20.7	21.0	17.0	
36.0					21.6	21.2	21.0	20.6	20.4	20.0	20.0	20.1	19.5	18.9	19.2	16.8	
38.0						19.6	19.4	19.0	18.8	18.4	18.4	18.5	17.9	17.3	17.6	16.6	
40.0							18.3	18.0	17.6	17.4	17.0	17.0	17.1	16.5	15.9	16.2	
42.0							16.9	16.4	16.2	15.8	15.8	15.8	15.2	14.7	14.9	14.9	
44.0								15.3	15.1	14.7	14.7	14.7	14.1	13.5	13.8	13.8	
46.0								14.9/45m	14.2	13.7	13.7	13.7	13.1	12.5	12.8	12.7	
48.0									13.3	12.8	12.8	12.8	12.2	11.6	11.9	11.8	
50.0										12.0	12.0	12.0	11.3	10.8	11.0	11.0	
54.0											10.6	10.5	9.9	9.3	9.5	9.5	
58.0												9.4	8.7	8.1	8.3	8.2	
62.0													7.7	7.1	7.2	7.2	
66.0													7.0/65m	6.2	6.3	6.2	
70.0														5.5	5.5	5.4	
74.0															4.9	4.7	
78.0															4.4/77m	4.1	
82.0																3.6	
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	21~73	18~73	20~74	
条数	8	8	8	7	6	6	5	5	4	4	4	3	3	2	2	2	
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	02	
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040	

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 25.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																	単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0	78.0*	84.0*		
14.0	81.0	81.1	80.5	80.5	73.0/15m													
16.0	66.5	66.5	66.0	65.8	66.0	65.7	60.0/17m	54.2/17m										
18.0	56.0	56.1	55.5	55.5	55.5	55.3	55.0	54.2	49.0	45.0/19m								
20.0	48.5	48.3	48.0	47.7	47.5	47.6	47.0	47.0	46.5	45.0	41.0	36.0/21m						
22.0	42.5	42.2	42.0	41.6	41.5	41.4	41.0	40.9	40.5	40.3	40.0	36.0	28.0/23m					
24.0	37.5	37.4	37.0	36.7	36.5	36.6	36.0	36.0	35.5	35.5	35.0	35.5	28.0	24.0/25m				
26.0		33.5	33.0	32.8	33.0	32.6	32.0	32.1	31.5	31.5	31.0	31.5	28.0	24.0	21.0	17.0		
28.0		30.2	30.0	29.6	29.8	29.4	29.2	28.8	28.6	28.2	28.2	28.3	27.7	24.0	21.0	17.0		
30.0		28.9/29m	27.4	26.8	27.0	26.6	26.4	26.1	25.9	25.5	25.4	25.6	25.0	24.0	21.0	16.9		
32.0				24.5	24.7	24.3	24.1	23.7	23.5	23.1	23.1	23.2	22.6	22.1	21.0	16.9		
34.0				22.6	22.7	22.3	22.1	21.7	21.5	21.1	21.1	21.2	20.6	20.0	20.4	16.8		
36.0				21.7/35m	21.0	20.5	20.3	19.9	19.7	19.3	19.3	19.4	18.8	18.3	18.6	16.7		
38.0						19.0	18.8	18.4	18.2	17.8	17.8	17.9	17.3	16.7	17.0	16.6		
40.0						17.7	17.5	17.0	16.9	16.4	16.4	16.5	15.9	15.3	15.6	15.6		
42.0						17.1/41m	16.3	15.9	15.7	15.2	15.2	15.3	14.7	14.1	14.4	14.3		
44.0								14.8	14.6	14.1	14.1	14.2	13.6	13.0	13.3	13.2		
46.0								13.9	13.6	13.2	13.1	13.2	12.6	12.0	12.3	12.2		
48.0									12.8	12.3	12.3	12.3	11.7	11.1	11.4	11.3		
50.0										11.5	11.5	11.5	10.9	10.3	10.6	10.5		
54.0										10.9/52m	10.2	10.1	9.4	8.9	9.1	9.1		
58.0												9.0	8.3	7.7	7.9	7.8		
62.0													7.3	6.7	6.9	6.8		
66.0													6.5	5.8	6.0	5.9		
70.0														5.1	5.2	5.1		
74.0															4.5	4.4		
78.0															4.0	3.8		
82.0																3.2		
(°)	32~66	19~68	29~71	17~73	26~72	16~72	24~72	19~73	22~73	18~73	21~73	25~74	19~73	23~73	17~74	21~73		
索数	7	7	7	7	6	5	5	5	4	4	4	3	3	2	2	2		
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03	03		
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040		

**主ジブ長さ+アダプタ長さ 30.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)																	単位 :t
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0*		
14.0	72.5/15m	72.6/15m	72.0/15m	70.5/15m														
16.0	65.5	65.4	65.0	64.8	62.0	55.5/17m												
18.0	55.5	55.2	55.0	54.5	54.5	54.4	50.0	44.6	40.0/19m									
20.0	47.5	47.5	47.0	46.8	47.0	46.7	46.5	44.6	40.0	36.9	33.5/21m							
22.0	41.5	41.5	41.0	40.8	41.0	40.7	40.0	40.1	39.5	36.9	33.5	30.0						
24.0	37.0	36.7	36.5	36.0	36.0	35.9	35.5	35.3	35.0	34.7	33.5	30.0	23.3					
26.0	33.0	32.8	32.5	32.1	32.0	32.0	31.5	31.4	31.0	30.8	30.5	30.0	23.3	20.2	17.6/27m			
28.0		29.6	29.5	28.9	29.2	28.8	28.6	28.2	28.0	27.6	27.6	27.7	23.3	20.2	17.6	14.2/29m		
30.0		27.0	26.8	26.3	26.5	26.1	25.9	25.5	25.3	24.9	24.8	25.0	23.3	20.2	17.6	14.2		
32.0			24.6	24.0	24.2	23.8	23.6	23.2	23.0	22.6	22.5	22.7	22.1	20.2	17.6	14.2		
34.0				22.0	22.2	21.8	21.6	21.2	21.0	20.6	20.6	20.7	20.1	19.5	17.6	14.2		
36.0				20.4	20.5	20.1	19.9	19.5	19.3	18.8	18.8	19.0	18.3	17.8	17.6	14.1		
38.0					19.0	18.6	18.4	17.9	17.8	17.3	17.3	17.4	16.8	16.2	16.6	14.1		
40.0						17.3	17.0	16.6	16.4	16.0	16.0	16.1	15.4	14.9	15.2	14.1		
42.0						16.1	15.9	15.4	15.2	14.8	14.8	14.9	14.2	13.7	14.0	13.9		
44.0							14.8	14.4	14.2	13.7	13.7	13.8	13.2	12.6	12.9	12.8		
46.0								13.5	13.2	12.8	12.7	12.8	12.2	11.6	11.9	11.9		
48.0								13.1/47m	12.4	11.9	11.9	12.0	11.3	10.7	11.0	11.0		
50.0									11.7	11.2	11.1	11.2	10.5	9.9	10.2	10.1		
54.0										10.2/53m	9.8	9.8	9.1	8.5	8.8	8.7		
58.0												8.6	7.9	7.4	7.6	7.5		
62.0												7.9/61m	7.0	6.4	6.6	6.5		
66.0													6.2	5.5	5.7	5.6		
70.0														4.8	4.9	4.8		
74.0														4.4/73m	4.3	4.2		
78.0															3.7	3.5		
82.0																2.9		
84.0																2.6		
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	18~73	20~73	17~73	19~73	18~73		
索数	6	6	6	6	5	5	4	4	3	3	3	3	2	2	2	2		
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08	08		
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040		

補ジブ起伏角度(最小~最大) LKコード:ジブ伸縮コード DSコード:作業設定コード \* 最大風速7.0m/s # 最大風速5.0m/s

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	72.0*	78.0*	84.0#	
16.0	64.5	59.3/17m	64.0	60.2	54.5/17m												
18.0	54.5	54.3	54.0	53.6	53.5	49.3	45.0/19m	39.8/19m									
20.0	47.0	46.6	46.5	46.0	46.0	45.9	45.0	39.8	35.5	32.8/21m							
22.0	41.0	40.7	40.5	40.0	40.0	39.9	39.5	39.3	35.5	32.8	30.0	27.0/23m					
24.0	36.0	36.0	35.5	35.3	35.5	35.2	34.5	34.6	34.0	32.8	30.0	27.0	21.0/25m				
26.0	32.5	32.2	32.0	31.5	31.5	31.4	31.0	30.8	30.5	30.2	30.0	27.0	21.0	18.5/27m			
28.0		29.0	28.9	28.3	28.6	28.2	28.0	27.6	27.4	27.0	26.9	27.0	21.0	18.5	16.0	13.0	
30.0		26.4	26.3	25.7	25.9	25.5	25.3	24.9	24.7	24.3	24.3	24.4	21.0	18.5	16.0	13.0	
32.0			24.0	23.4	23.7	23.2	23.0	22.6	22.4	22.0	22.0	22.2	21.0	18.5	16.0	13.0	
34.0				21.5	21.7	21.3	21.1	20.7	20.5	20.1	20.0	20.2	19.6	18.5	16.0	13.0	
36.0				19.9	20.1	19.6	19.4	19.0	18.8	18.4	18.3	18.5	17.8	17.3	16.0	13.0	
38.0					18.6	18.1	17.9	17.5	17.3	16.9	16.8	17.0	16.3	15.8	16.0	13.0	
40.0						16.8	16.6	16.2	16.0	15.5	15.5	15.7	15.0	14.4	14.8	13.0	
42.0						15.7	15.4	15.0	14.8	14.4	14.3	14.5	13.8	13.3	13.6	13.0	
44.0							14.4	14.0	13.8	13.3	13.3	13.4	12.8	12.2	12.5	12.4	
46.0								13.1	12.8	12.4	12.3	12.5	11.8	11.2	11.6	11.5	
48.0								12.3	12.0	11.5	11.5	11.6	10.9	10.4	10.7	10.6	
50.0									11.3	10.8	10.7	10.8	10.1	9.6	9.9	9.8	
54.0										9.5	9.4	9.4	8.8	8.2	8.5	8.4	
58.0												8.3	7.6	7.0	7.3	7.2	
62.0												7.4	6.7	6.1	6.3	6.2	
66.0													5.9	5.2	5.4	5.3	
70.0														4.5	4.7	4.6	
74.0														3.9	4.0	3.8	
78.0															3.3	3.1	
82.0																2.6	
86.0																2.2/85m	
(°)	28~63	21~64	25~69	19~71	23~71	17~71	21~71	16~72	29~72	15~72	24~72	17~73	22~73	16~72	20~73	17~73	
条数	6	5	5	5	5	4	4	3	3	3	3	2	2	2	2	2	
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	23	
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040	

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0*	72.0*	78.0#	84.0#	
16.0	58.5/17m	58.6/17m	56.0/17m	48.8/17m													
18.0	53.5	53.6	53.0	48.8	43.0	38.9/19m											
20.0	46.0	46.0	45.5	45.3	43.0	38.9	35.5	32.1	29.2/21m								
22.0	40.5	40.1	40.0	39.4	39.5	38.9	35.5	32.1	29.2	27.2	25.2/23m						
24.0	35.5	35.5	35.0	34.8	35.0	34.7	34.0	32.1	29.2	27.2	25.2	21.9					
26.0	32.0	31.7	31.5	31.0	31.0	30.9	30.5	30.3	29.2	27.2	25.2	21.9	17.0				
28.0		28.6	28.4	27.9	28.1	27.7	27.5	27.1	26.9	26.5	25.2	21.9	17.0	14.3	12.6/29m		
30.0		26.0	25.8	25.2	25.5	25.1	24.9	24.5	24.3	23.9	23.8	21.9	17.0	14.3	12.6	10.0/31m	
32.0			23.6	23.0	23.3	22.8	22.6	22.2	22.0	21.6	21.6	21.8	17.0	14.3	12.6	10.0	
34.0				21.1	21.3	20.9	20.7	20.3	20.1	19.7	19.6	19.8	17.0	14.3	12.5	10.0	
36.0				19.5	19.7	19.2	19.0	18.6	18.4	18.0	17.9	18.1	17.0	14.3	12.5	10.0	
38.0					18.2	17.8	17.5	17.1	16.9	16.5	16.5	16.6	16.0	14.3	12.4	10.0	
40.0						16.5	16.2	15.8	15.6	15.2	15.2	15.3	14.7	14.1	12.4	10.0	
42.0						15.3	15.1	14.7	14.5	14.0	14.0	14.1	13.5	12.9	12.4	10.0	
44.0							14.1	13.6	13.4	13.0	13.0	13.1	12.4	11.9	12.2	10.0	
46.0								12.7	12.5	12.0	12.0	12.1	11.5	10.9	11.3	10.0	
48.0								11.9	11.7	11.2	11.2	11.3	10.6	10.1	10.4	10.0	
50.0									11.0	10.5	10.4	10.5	9.9	9.3	9.6	9.5	
54.0										9.2	9.1	9.2	8.5	7.9	8.2	8.1	
58.0												8.1	7.4	6.8	7.1	7.0	
62.0												7.1	6.4	5.8	6.1	6.0	
66.0													5.6	5.0	5.2	5.1	
70.0														4.2	4.5	4.3	
74.0														3.6	3.7	3.6	
78.0															3.1	2.9	
82.0																2.3	
(°)	31~62	24~66	28~68	22~70	25~72	20~70	23~70	19~72	22~72	17~72	26~72	19~72	23~72	17~72	21~73	16~73	
条数	5	5	5	4	4	3	3	3	3	3	2	2	2	2	2	2	
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	43	
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040	

TEREX-DEMAG  
AC650

定格総荷重表  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 45.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	72.0#	78.0#	84.0#	
18.0	49.5/19m	48.4/19m	45.0/19m	40.1													
20.0	45.5	45.4	45.0	40.1	36.0	32.7	30.0/21m										
22.0	39.5	39.5	39.0	38.8	36.0	32.7	30.0	27.8	26.0	24.5/23m							
24.0	35.0	34.9	34.5	34.2	34.5	32.7	30.0	27.8	26.0	24.5	23.0						
26.0	31.5	31.2	31.0	30.5	30.5	30.4	30.0	27.8	26.0	24.5	23.0	19.0	14.7/27m				
28.0	28.5	28.1	28.0	27.4	27.7	27.3	27.0	26.6	26.0	24.5	23.0	19.0	14.7				
30.0		25.5	25.4	24.8	25.1	24.6	24.4	24.0	23.8	23.4	23.0	19.0	14.7	11.5	10.6		
32.0		23.3	23.2	22.6	22.9	22.4	22.2	21.8	21.6	21.2	21.1	19.0	14.7	11.5	10.5	8.0/33m	
34.0			21.3	20.7	21.0	20.5	20.3	19.9	19.7	19.2	19.2	19.0	14.7	11.5	10.4	8.0	
36.0				19.1	19.3	18.8	18.6	18.2	18.0	17.6	17.5	17.7	14.7	11.5	10.3	8.0	
38.0				17.7	17.9	17.4	17.2	16.8	16.6	16.1	16.1	16.3	14.7	11.5	10.2	8.0	
40.0					16.6	16.1	15.9	15.5	15.3	14.8	14.8	15.0	14.3	11.5	10.2	8.0	
42.0						15.0	14.8	14.3	14.1	13.7	13.6	13.8	13.1	11.5	10.1	8.0	
44.0						14.0	13.8	13.3	13.1	12.6	12.6	12.8	12.1	11.5	10.0	8.0	
46.0							12.9	12.4	12.2	11.7	11.7	11.8	11.2	10.6	10.0	8.0	
48.0								11.6	11.4	10.9	10.9	11.0	10.3	9.7	10.0	8.0	
50.0								10.9	10.7	10.2	10.1	10.2	9.6	9.0	9.3	8.0	
54.0										8.9	8.8	8.9	8.2	7.6	8.0	7.9	
58.0												7.8	7.8	7.1	6.5	6.8	
62.0													6.9	6.2	5.5	5.8	
66.0														5.4	4.7	5.0	
70.0														4.7	3.9	4.2	
74.0															3.2	3.4	
78.0																2.8	
82.0																2.3	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~72	19~72	12~72	25~72	
条数	4	4	4	3	3	3	3	3	2	2	2	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040	

主ジブ長さ+アダプタ長さ 50.5m+4.0m

作業半径 (m)	補ジブ長さ(m)																
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	72.0#	78.0#	84.0#	
18.0	38.0/19m		33.0/19m	29.9/19m													
20.0	38.0	35.0	32.5	29.7	26.6	24.1/21m											
22.0	37.5	34.2	31.5	29.2	26.6	24.1	22.1	21.1/23m									
24.0	34.5	33.9	31.0	28.7	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m						
26.0	31.0	30.8	30.5	28.6	26.6	24.1	22.1	21.1	20.2	18.6	17.1	13.5					
28.0	28.2	27.7	27.6	27.0	26.4	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3				
30.0		25.2	25.0	24.4	24.8	24.1	22.1	21.1	20.2	18.6	17.1	13.5	10.3	7.8			
32.0		23.0	22.9	22.2	22.6	22.1	21.9	21.0	20.1	18.6	17.1	13.5	10.3	7.8	6.6		
34.0			21.0	20.4	20.7	20.2	20.0	19.6	19.4	18.6	17.1	13.5	10.3	7.8	6.5	4.8	
36.0				18.7	19.0	18.6	18.3	17.9	17.7	17.3	17.0	13.5	10.3	7.8	6.5	4.8	
38.0				17.4	17.6	17.1	16.9	16.5	16.3	15.8	15.8	13.5	10.3	7.8	6.5	4.8	
40.0					16.3	15.8	15.6	15.2	15.0	14.5	14.5	13.5	10.3	7.8	6.4	4.8	
42.0						14.7	14.5	14.1	13.9	13.4	13.4	13.5	10.3	7.8	6.4	4.8	
44.0						13.8	13.5	13.0	12.8	12.4	12.3	12.5	10.3	7.8	6.3	4.8	
46.0							12.6	12.1	11.9	11.5	11.4	11.6	10.3	7.8	6.3	4.8	
48.0								11.4	11.1	10.6	10.6	10.8	10.1	7.8	6.3	4.8	
50.0								10.7	10.4	9.9	9.9	10.0	9.3	7.8	6.3	4.8	
54.0										8.7	8.6	8.7	8.0	7.4	6.3	4.8	
58.0											7.6	7.6	6.9	6.3	6.3	4.8	
62.0												6.7	6.0	5.3	5.6	4.8	
66.0													5.2	4.4	4.8	4.7	
70.0													4.5	3.6	3.9	3.8	
74.0														3.0	3.2	3.0	
78.0															2.6	2.4	
82.0																2.0	
(°)	27~60	20~61	24~67	18~69	22~69	16~69	20~69	15~69	25~69	22~71	18~71	22~72	16~71	20~71	14~71	32~71	
条数	3	3	3	3	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	37040	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 80t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)															
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	72.0#	78.0#	
20.0	31.0/21m	28.0/21m	25.5/21m	22.5												
22.0	31.0	28.0	25.5	22.6	20.0	18.1										
24.0	30.0	27.8	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m						
26.0	29.5	27.2	25.2	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m					
28.0	27.8	26.6	24.7	22.3	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m			
30.0		24.8	24.3	22.1	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0			
32.0		22.7	22.5	21.9	20.0	18.1	16.6	16.4	16.4	14.7	12.9	9.5	7.0	5.0	3.3/33m	
34.0			20.7	20.0	20.0	18.1	16.6	16.3	16.3	14.7	12.9	9.5	7.0	5.0	3.3	
36.0				18.4	18.7	18.1	16.6	16.1	16.0	14.6	12.9	9.5	7.0	5.0	3.3	
38.0				17.0	17.3	16.8	16.6	16.0	15.7	14.5	12.9	9.5	7.0	5.0	3.3	
40.0					16.1	15.6	15.3	14.9	14.7	14.2	12.9	9.5	7.0	5.0	3.3	
42.0						14.5	14.2	13.8	13.6	13.1	12.9	9.5	7.0	5.0	3.3	
44.0						13.5	13.2	12.8	12.6	12.1	12.1	9.5	7.0	5.0	3.3	
46.0							12.4	11.9	11.7	11.2	11.2	9.5	7.0	5.0	3.3	
48.0								11.1	10.9	10.4	10.4	9.5	7.0	5.0	3.3	
50.0								10.4	10.2	9.6	9.6	9.5	7.0	5.0	3.3	
54.0										8.4	8.4	8.5	7.0	5.0	3.3	
58.0											7.3	7.4	6.7	5.0	3.3	
62.0												6.5	5.7	5.0	3.3	
66.0													5.0	4.2	3.3	
70.0													4.3	3.4	3.3	
74.0														2.7	3.0	
78.0															2.3	
(°)	31~56	24~60	27~64	21~68	25~67	19~69	23~67	18~69	27~68	24~70	20~69	24~70	18~71	22~70	25~71	
索数	3	3	2	2	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	37030	37043	37031	37044	37032	37045	37033	37046	37034	37047	37035	37036	37037	37038	37039	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 15.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	
12.0	91.0	81.2/13m	80.5/13m	80.6/13m										
14.0	71.5	71.4	71.0	70.8	71.0	70.7	63.5/15m							
16.0	58.5	58.3	58.0	57.7	57.5	57.6	57.0	57.1	52.0/17m	51.9/17m				
18.0	49.0	48.9	48.5	48.3	48.5	48.2	48.0	47.7	47.5	47.2	47.0			
20.0	42.0	41.9	41.5	41.3	41.5	41.2	41.0	40.7	40.5	40.2	40.0	40.0		
22.0	36.5	36.6	36.0	36.0	36.0	35.8	35.5	35.3	35.0	34.8	34.5	34.5	34.0	
24.0	34.5/23m	32.3	32.0	31.7	31.5	31.6	31.0	31.0	30.5	30.5	30.5	30.5	30.0	
26.0		28.9	28.8	28.3	28.5	28.1	27.9	27.6	27.4	27.0	27.0	27.1	26.6	
28.0		27.5/27m	26.0	25.5	25.6	25.2	25.1	24.7	24.5	24.1	24.1	24.3	23.7	
30.0			23.6	23.1	23.3	22.8	22.7	22.3	22.1	21.7	21.7	21.8	21.2	
32.0				21.1	21.2	20.8	20.6	20.2	20.1	19.7	19.7	19.8	19.2	
34.0				20.2/33m	19.5	19.0	18.9	18.5	18.3	17.9	17.9	18.0	17.4	
36.0					18.0	17.5	17.3	16.9	16.8	16.3	16.3	16.4	15.8	
38.0						16.2	16.0	15.6	15.4	15.0	15.0	15.1	14.5	
40.0						15.6/39m	14.8	14.4	14.2	13.8	13.8	13.9	13.3	
42.0							13.8	13.4	13.2	12.7	12.7	12.8	12.2	
44.0								12.5	12.3	11.8	11.8	11.8	11.2	
46.0								12.1/45m	11.5	11.0	11.0	11.0	10.3	
48.0									11.1/47m	10.2	10.2	10.2	9.6	
50.0										9.6	9.5	9.5	8.8	
54.0											8.7/53m	8.3	7.6	
58.0												7.3	6.6	
62.0													5.7	
66.0													5.2/65m	
(°)	31~68	24~68	23~70	22~72	21~72	20~73	19~73	18~73	21~73	21~74	20~74	22~73	18~73	
条数	8	7	7	7	6	6	5	5	5	4	4	4	3	
LKコード	00	00	00	00	00	00	00	00	00	00	00	00	00	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	

**主ジブ長さ+アダプタ長さ 20.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	
12.0	79.0/13m	79.1/13m	78.0/13m	76.8/13m										
14.0	69.5	69.5	69.0	69.0	68.5	62.3/15m								
16.0	57.0	56.7	56.5	56.1	56.0	56.0	55.5	55.5	50.5/17m					
18.0	47.5	47.5	47.0	46.9	47.0	46.8	46.5	46.3	46.0	45.8	42.0/19m			
20.0	41.0	40.7	40.5	40.1	40.0	40.0	39.5	39.4	39.0	38.9	38.5	37.0		
22.0	35.5	35.5	35.0	34.9	35.0	34.7	34.5	34.2	34.0	33.7	33.5	33.5	30.0	
24.0	31.5	31.4	31.0	30.7	31.0	30.6	30.0	30.0	29.8	29.5	29.5	29.6	29.0	
26.0		28.0	27.9	27.4	27.6	27.2	27.0	26.6	26.5	26.1	26.1	26.2	25.6	
28.0		25.3	25.2	24.6	24.8	24.4	24.2	23.8	23.7	23.3	23.3	23.4	22.8	
30.0			22.9	22.3	22.5	22.1	21.9	21.5	21.3	20.9	20.9	21.1	20.4	
32.0				20.3	20.5	20.1	19.9	19.5	19.3	18.9	18.9	19.0	18.4	
34.0				18.7	18.8	18.4	18.2	17.8	17.6	17.2	17.2	17.3	16.7	
36.0					17.3	16.9	16.7	16.3	16.1	15.7	15.7	15.8	15.2	
38.0						15.6	15.4	15.0	14.8	14.4	14.4	14.5	13.8	
40.0						14.5	14.3	13.8	13.6	13.2	13.2	13.3	12.7	
42.0							13.3	12.8	12.6	12.2	12.2	12.2	11.6	
44.0								11.9	11.7	11.3	11.2	11.3	10.7	
46.0								11.5/45m	10.9	10.4	10.4	10.5	9.8	
48.0									10.2	9.7	9.7	9.7	9.1	
50.0										9.1	9.0	9.0	8.4	
54.0											7.9	7.8	7.2	
58.0												6.9	6.2	
62.0													5.3	
66.0													4.8/65m	
(°)	29~67	22~69	26~71	20~73	23~73	18~73	22~73	21~74	20~74	23~73	19~73	23~74	20~74	
条数	7	6	6	6	6	5	5	5	4	4	4	3	3	
LKコード	02	02	02	02	02	02	02	02	02	02	02	02	02	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 25.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	
14.0	68.0	67.8	67.0	66.8	59.5/15m									
16.0	55.0	55.2	55.0	54.6	54.5	54.5	49.5/17m	49/17m						
18.0	46.5	46.2	46.0	45.6	45.5	45.5	45.0	44.9	44.5	41.0/19m				
20.0	39.5	39.5	39.0	38.9	39.0	38.8	38.5	38.3	38.0	37.7	37.5	35.0/21m		
22.0	34.5	34.4	34.0	33.8	34.0	33.7	33.5	33.1	32.5	32.6	32.5	32.5	28.0/23m	
24.0	30.5	30.4	30.0	29.8	30.0	29.6	29.4	29.1	28.9	28.5	28.5	28.6	28.0	
26.0		27.1	27.0	26.5	26.7	26.3	26.1	25.8	25.6	25.2	25.2	25.3	24.7	
28.0		24.5	24.3	23.8	24.0	23.6	23.4	23.0	22.9	22.4	22.4	22.6	22.0	
30.0		23.4/29m	22.1	21.5	21.7	21.3	21.1	20.7	20.6	20.1	20.1	20.3	19.7	
32.0				19.6	19.8	19.4	19.2	18.8	18.6	18.2	18.2	18.3	17.7	
34.0				18.0	18.1	17.7	17.5	17.1	16.9	16.5	16.5	16.6	16.0	
36.0				17.3/35m	16.7	16.2	16.0	15.6	15.5	15.0	15.0	15.2	14.5	
38.0						15.0	14.8	14.4	14.2	13.7	13.7	13.9	13.2	
40.0						13.9	13.7	13.2	13.1	12.6	12.6	12.7	12.1	
42.0						13.4/41m	12.7	12.2	12.1	11.6	11.6	11.7	11.1	
44.0								11.4	11.2	10.7	10.7	10.8	10.1	
46.0								10.6	10.4	9.9	9.9	10.0	9.3	
48.0									9.7	9.2	9.2	9.2	8.6	
50.0										8.6	8.5	8.5	7.9	
54.0										8.1/52m	7.5	7.4	6.7	
58.0												6.4	5.7	
62.0													4.9	
66.0													4.3	
(°)	32~66	19~68	29~71	17~73	26~72	16~72	24~72	19~73	22~73	18~73	21~73	25~74	19~73	
索数	6	6	6	6	5	5	4	4	4	4	3	3	3	
LKコード	03	03	03	03	03	03	03	03	03	03	03	03	03	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	

**主ジブ長さ+アダプタ長さ 30.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	
14.0	60.5/15m	60.1/15m	59.0/15m	58.2/15m										
16.0	54.0	54.1	53.5	53.4	52.5	48.5/17m								
18.0	45.5	45.2	45.0	44.6	44.5	44.5	44.0	43.9	40.0/19m					
20.0	39.0	38.7	38.5	38.1	38.0	37.9	37.5	37.4	37.0	36.8	33.5/21m			
22.0	34.0	33.7	33.5	33.0	33.0	32.9	32.5	32.3	32.0	31.8	31.5	30.0		
24.0	30.0	29.7	29.6	29.1	29.3	28.9	28.7	28.3	28.2	27.8	27.7	27.9	23.3	
26.0	26.9	26.5	26.4	25.8	26.1	25.7	25.5	25.1	24.9	24.5	24.5	24.7	23.3	
28.0		23.9	23.7	23.2	23.4	23.0	22.8	22.4	22.2	21.8	21.8	22.0	21.4	
30.0		21.7	21.5	20.9	21.2	20.8	20.6	20.2	20.0	19.6	19.6	19.7	19.1	
32.0			19.7	19.0	19.3	18.8	18.6	18.2	18.1	17.6	17.6	17.8	17.2	
34.0				17.4	17.6	17.2	17.0	16.6	16.4	16.0	16.0	16.1	15.5	
36.0				16.1	16.2	15.8	15.6	15.2	15.0	14.5	14.5	14.7	14.0	
38.0					15.0	14.5	14.3	13.9	13.7	13.3	13.3	13.4	12.8	
40.0						13.4	13.2	12.8	12.6	12.2	12.2	12.3	11.6	
42.0						12.5	12.3	11.8	11.6	11.2	11.2	11.3	10.6	
44.0							11.4	11.0	10.8	10.3	10.3	10.4	9.7	
46.0								10.2	10.0	9.5	9.5	9.6	8.9	
48.0								9.9/47m	9.3	8.8	8.8	8.9	8.2	
50.0									8.7	8.2	8.2	8.2	7.5	
54.0										7.4/53m	7.1	7.1	6.4	
58.0												6.1	5.4	
62.0												5.6/61m	4.6	
66.0													4.0	
(°)	25~64	16~68	22~70	15~72	20~72	13~72	18~72	18~73	17~73	16~73	23~72	19~73	20~73	
索数	5	5	5	5	4	4	4	4	3	3	3	3	2	
LKコード	08	08	08	08	08	08	08	08	08	08	08	08	08	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 35.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	
16.0	53.0	48.6/17m	52.0	51.6	46.5/17m									
18.0	44.5	44.3	44.0	43.6	43.5	43.5	39.5/19m	39.1/19m						
20.0	38.0	37.9	37.5	37.2	37.5	37.1	36.5	36.5	35.5	32.8/21m				
22.0	33.0	32.9	32.5	32.3	32.5	32.2	31.5	31.6	31.0	31.0	30.0	27.0/23m		
24.0	29.4	29.0	28.9	28.4	28.6	28.2	28.0	27.6	27.4	27.0	27.0	26.9	21/25m	
26.0	26.3	25.9	25.8	25.2	25.5	25.0	24.8	24.5	24.3	23.8	23.8	24.0	21.0	
28.0		23.3	23.1	22.6	22.8	22.4	22.2	21.8	21.6	21.2	21.2	21.4	20.7	
30.0		21.1	21.0	20.4	20.6	20.2	20.0	19.6	19.4	19.0	19.0	19.2	18.5	
32.0			19.1	18.5	18.8	18.3	18.1	17.7	17.5	17.1	17.1	17.3	16.6	
34.0				16.9	17.2	16.7	16.5	16.1	15.9	15.5	15.5	15.6	15.0	
36.0				15.6	15.8	15.3	15.1	14.7	14.5	14.1	14.0	14.2	13.6	
38.0					14.6	14.1	13.9	13.4	13.3	12.8	12.8	13.0	12.3	
40.0						13.0	12.8	12.4	12.2	11.7	11.7	11.9	11.2	
42.0						12.1	11.9	11.4	11.2	10.7	10.7	10.9	10.2	
44.0							11.0	10.5	10.4	9.9	9.9	10.0	9.3	
46.0								9.8	9.6	9.1	9.1	9.2	8.5	
48.0								9.1	8.9	8.4	8.4	8.5	7.8	
50.0									8.3	7.8	7.8	7.8	7.2	
54.0										6.8	6.7	6.7	6.0	
58.0												5.8	5.1	
62.0												5.1	4.3	
66.0													3.6	
(°)	28~63	21~64	25~69	19~71	23~71	17~71	21~71	16~72	29~72	15~72	24~72	17~73	22~73	
索数	5	4	4	4	4	4	3	3	3	3	3	2	2	
LKコード	23	23	23	23	23	23	23	23	23	23	23	23	23	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	

**主ジブ長さ+アダプタ長さ 40.5m+4.0m**

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0	66.0	
16.0	48.0/17m	47.6/17m	46.5/17m	46.0/17m										
18.0	43.5	43.6	43.0	42.9	41.5	38.9/19m								
20.0	37.5	37.2	37.0	36.6	36.5	36.5	35.5	32.1	29.2/21m					
22.0	32.5	32.4	32.0	31.7	32.0	31.6	31.0	31.0	29.2	27.2	25.2/23m			
24.0	28.9	28.5	28.4	27.8	28.1	27.7	27.5	27.1	26.9	26.5	25.2	21.9		
26.0	25.8	25.4	25.3	24.7	25.0	24.5	24.3	23.9	23.7	23.3	23.3	21.9	17.0	
28.0		22.8	22.7	22.1	22.4	21.9	21.7	21.3	21.2	20.7	20.7	20.9	17.0	
30.0		20.6	20.5	19.9	20.2	19.8	19.6	19.2	19.0	18.5	18.5	18.7	17.0	
32.0			18.7	18.1	18.4	17.9	17.7	17.3	17.1	16.7	16.7	16.8	16.2	
34.0				16.5	16.8	16.3	16.1	15.7	15.5	15.1	15.0	15.2	14.6	
36.0				15.2	15.4	14.9	14.7	14.3	14.1	13.7	13.7	13.8	13.2	
38.0					14.2	13.7	13.5	13.1	12.9	12.4	12.4	12.6	11.9	
40.0						12.7	12.5	12.0	11.8	11.4	11.4	11.5	10.9	
42.0						11.7	11.5	11.1	10.9	10.4	10.4	10.5	9.9	
44.0							10.7	10.2	10.0	9.5	9.5	9.7	9.0	
46.0								9.5	9.3	8.8	8.8	8.9	8.2	
48.0								8.8	8.6	8.1	8.1	8.2	7.5	
50.0									8.0	7.5	7.5	7.6	6.9	
54.0										6.5	6.4	6.5	5.8	
58.0												5.5	4.8	
62.0												4.8	4.0	
66.0													3.3	
(°)	31~62	24~66	28~68	22~70	25~72	20~70	23~70	19~72	22~72	17~72	26~72	19~72	23~72	
索数	4	4	4	4	4	3	3	3	3	3	2	2	2	
LKコード	43	43	43	43	43	43	43	43	43	43	43	43	43	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	



TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウエイト 60t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

**主ジブ長さ+アダプタ長さ 45.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0	60.0*	66.0*	
18.0	40.0/19m	39.7/19m	39.5/19m	40.1										
20.0	37.0	36.6	36.5	35.9	35.5	32.7	30.0/21m							
22.0	32.0	31.8	31.5	31.1	31.0	31.0	30.0	27.8	26.0	24.5/23m				
24.0	28.4	28.0	27.8	27.3	27.6	27.2	26.9	26.5	26.0	24.5	23.0			
26.0	25.3	24.9	24.8	24.2	24.5	24.0	23.8	23.4	23.2	22.8	22.8	19.0	14.7/27m	
28.0	22.8	22.3	22.2	21.6	21.9	21.5	21.3	20.9	20.7	20.2	20.2	19.0	14.7	
30.0		20.2	20.1	19.5	19.8	19.3	19.1	18.7	18.5	18.1	18.0	18.3	14.7	
32.0		18.4	18.3	17.6	18.0	17.5	17.3	16.9	16.7	16.2	16.2	16.4	14.7	
34.0			16.7	16.1	16.4	15.9	15.7	15.3	15.1	14.6	14.6	14.8	14.2	
36.0				14.8	15.0	14.5	14.3	13.9	13.7	13.3	13.3	13.5	12.8	
38.0				13.6	13.8	13.4	13.2	12.7	12.5	12.1	12.1	12.2	11.6	
40.0					12.8	12.3	12.1	11.7	11.5	11.0	11.0	11.2	10.5	
42.0						11.4	11.2	10.7	10.5	10.1	10.0	10.2	9.6	
44.0						10.6	10.4	9.9	9.7	9.2	9.2	9.4	8.7	
46.0							9.6	9.1	8.9	8.5	8.4	8.6	7.9	
48.0								8.5	8.3	7.8	7.8	7.9	7.2	
50.0								8.0	7.7	7.2	7.2	7.3	6.6	
54.0										6.2	6.1	6.2	5.5	
58.0											5.3	5.3	4.6	
62.0												4.5	3.7	
66.0													2.9	
70.0													2.4	
(°)	24~58	15~62	21~65	13~70	19~68	12~70	17~70	11~70	24~71	20~71	15~71	21~71	14~72	
条数	4	3	3	3	3	3	3	3	2	2	2	2	2	
LKコード	63	63	63	63	63	63	63	63	63	63	63	63	63	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	

**主ジブ長さ+アダプタ長さ 50.5m+4.0m**

単位 : t

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0	51.0	54.0*	60.0*	66.0#	
18.0	38.0/19m		33.0/19m	29.9/19m										
20.0	36.5	35.0	32.5	29.7	26.6	24.1/21m								
22.0	31.5	31.3	31.0	29.2	26.6	24.1	22.1	21.1/23m						
24.0	28.0	27.6	27.4	26.8	26.6	24.1	22.1	21.1	20.2	18.6	17.1/25m			
26.0	24.9	24.5	24.4	23.8	24.1	23.7	22.1	21.1	20.2	18.6	17.1	13.5		
28.0	22.4	22.0	21.9	21.2	21.6	21.1	20.9	20.5	20.2	18.6	17.1	13.5	10.3	
30.0		19.9	19.7	19.1	19.5	19.0	18.8	18.4	18.2	17.7	17.1	13.5	10.3	
32.0		18.1	17.9	17.3	17.6	17.2	17.0	16.5	16.4	15.9	15.9	13.5	10.3	
34.0			16.4	15.8	16.1	15.6	15.4	15.0	14.8	14.3	14.3	13.5	10.3	
36.0				14.4	14.7	14.3	14.1	13.6	13.4	13.0	12.9	13.2	10.3	
38.0				13.3	13.6	13.1	12.9	12.4	12.2	11.8	11.8	12.0	10.3	
40.0					12.5	12.0	11.8	11.4	11.2	10.7	10.7	10.9	10.2	
42.0						11.1	10.9	10.4	10.3	9.8	9.8	10.0	9.3	
44.0						10.3	10.1	9.6	9.4	8.9	8.9	9.1	8.4	
46.0							9.4	8.9	8.7	8.2	8.2	8.4	7.7	
48.0								8.2	8.0	7.5	7.5	7.7	7.0	
50.0								7.7	7.4	6.9	6.9	7.0	6.4	
54.0										5.9	5.9	6.0	5.3	
58.0											5.1	5.1	4.3	
62.0												4.3	3.4	
66.0													2.7	
70.0													2.1	
(°)	27~60	20~61	24~67	18~69	22~69	16~69	20~69	15~69	25~69	22~71	18~71	23~72	16~72	
条数	3	3	3	3	2	2	2	2	2	2	2	2	2	
LKコード	73	73	73	73	73	73	73	73	73	73	73	73	73	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	

TEREX-DEMAG  
AC650

**定格総荷重表**  
WIHI仕様(ラフティングジブ)

カウンタウェイト 60t  
アウトリガ 9.02 × 8.45m  
主ジブ角 83°

主ジブ長さ+アダプタ長さ 55.5m+4.0m

単位 :t

作業半径 (m)	補ジブ長さ(m)													
	24.0	27.0	30.0	33.0	36.0	39.0	42.0	45.0	48.0*	51.0	54.0*	60.0#	66.0#	
20.0	31.0/21m	28.0/21m	25.5/21m	22.5										
22.0	31.0	28.0	25.5	22.6	20.0	18.1								
24.0	27.6	27.2	25.5	22.6	20.0	18.1	16.6	16.6		14.7/25m				
26.0	24.6	24.1	24.0	22.5	20.0	18.1	16.6	16.6	16.5	14.7	12.9/27m			
28.0	22.1	21.6	21.5	20.9	20.0	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0/29m	
30.0		19.5	19.4	18.8	19.1	18.1	16.6	16.6	16.5	14.7	12.9	9.5	7.0	
32.0		17.7	17.6	17.0	17.3	16.9	16.6	16.2	16.0	14.7	12.9	9.5	7.0	
34.0			16.1	15.4	15.8	15.3	15.1	14.7	14.5	14.0	12.9	9.5	7.0	
36.0				14.1	14.5	14.0	13.8	13.3	13.1	12.6	12.6	9.5	7.0	
38.0				13.0	13.3	12.8	12.6	12.1	11.9	11.5	11.5	9.5	7.0	
40.0					12.3	11.8	11.5	11.1	10.9	10.4	10.4	9.5	7.0	
42.0						10.8	10.6	10.2	10.0	9.5	9.5	9.5	7.0	
44.0						10.1	9.8	9.3	9.2	8.7	8.7	8.9	7.0	
46.0							9.1	8.6	8.4	7.9	7.9	8.1	7.0	
48.0								8.0	7.8	7.3	7.3	7.4	6.7	
50.0								7.4	7.2	6.7	6.7	6.8	6.1	
54.0										5.7	5.6	5.7	5.0	
58.0											4.8	4.9	4.0	
62.0												4.1	3.1	
66.0													2.4	
(°)	31~56	24~60	27~64	21~68	25~67	19~69	23~67	18~69	27~68	24~70	20~69	24~70	27~71	
条数	3	3	2	2	2	2	2	2	2	2	2	2	2	
LKコード	83	83	83	83	83	83	83	83	83	83	83	83	83	
DSコード	38030	38043	38031	38044	38032	38045	38033	38046	38034	38047	38035	38036	38037	